

Douglas County Surveyor's Record of  
Government Corners Renewed

T 24 T. S. R 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

98

1/4 Corner for Secs. 22 and 27.  
Set - 2 1/2" Alum cap, (1979)  
BT's - 9" D. Fir, S.77°W., 19.8 ft.  
8" D. Fir, N.33°E., 12.6 ft.

11/29/79

T. E. Shrum, Jr.  
For: Champion Inter.  
Corp.  
Nov. 29, 1979  
M 81 - 33

99

Standard Corner for Secs. 13, & 24, on the East Tnsp. bndry.  
Found - 22" downed fir bears S.76°W., 42.9-ft.w/scribe vis. 1893 BT  
30" fir stub bears N.21°E., 141.1-ft. (no marks) 1893 BT  
38" fir stub bears N.59°W., 89.8-ft. (no marks) 1893 BT  
40" fir bears S.79°E., 123-ft. (no marks) 1893 BT

\* Note: distances to BTs . measured on slope.

Set - 1-1/2" x 36" I.P. & Brass Cap.  
New BTs- 13" fir bears N.52°W., 24.8-ft. (scribed).  
24" fir bears S.18°W., 24.2-ft. (scribed). 11/20/81

100

West 1/4 Corner for Sec. 19 only of T.24-7.  
Set - 1-1/2" x 36" I.P. & Brass Cap.  
New BTs- 22" fir bears S.84°E., 9.9-ft. (scribed).  
23" fir bears S.2°W., 20.0-ft. (scribed).

101

South 1/4 corner to Sec. 36 of T.23-8 only.  
No evidence of original corner.  
Set - 1-1/2" x 36" I.P. with B.C. at proportionate distance.  
New BTs- 9" fir bears N.49°W., 12.8-ft. (scribed).  
12" fir bears N.12°E., 10.8-ft. (scribed).

Les Roberts #1039  
For: Int. Paper Co.  
March 30, 1982  
M 91 - 74

102

Section corner for Sections 33 and 34 only T.23-8.  
Found - Area completely covered by fill from new road construction.  
Orig. 40" fir, now 45" (alive) with well healed blaze.  
Orig. 60" fir, now 45" stump with no visible bark scribing remaining.  
16" fir per Ren. #45 now 15" stump with good scar.  
Set - Using record distances from the two remaining orig. BTs and near record dist. from the one remaining Ren. #45 BT, I set a 1" x 30" iron pipe with brass cap attached mkd. "Douglas Co Surveyor T23S S33 S34 R8W 1982" for the sec. cor. to secs. Powell 33 & 34 only. Corner falls on a steep rocky road fill approx. 47 ft. (slope distance) south of a new road. Bearing and dists. to found BTs are:  
60" now 45" fir (stump) bears N.85°E., 19.1 ft. (Rec. N.83°E.)  
40" now 45" fir (alive) bears S.63°W., 40.9 ft. (Rec. S.67°W.)  
16" now 15" fir (stump) bears N.38°E., 22.9 ft. (Rec. N.34 1/2°E. 22.7 ft.)

New BT - 36" fir scribed "T24S R8W S3 CS BT" in single blaze bears S.86°W., 46.8 ft.

Douglas County Surveyor Office BT tags on all trees.

10/13/82

103

Closing corner for Sections 3 and 4 (on township line)  
Found - a 20" D. fir, now 26" which bears S.78°E., 36.2 ft. (OBT)  
a 36" D. fir now a stump, which bears N.57°E., 36.6 ft. (OBT)  
A 36" D. fir (now a stump, which bears N.4°W., 30.5 ft. (OBT)  
A 2" pipe and brass cap in proper position. Ren. #80  
A new road was to be constructed near this corner and it appeared that the corner position could be obliterated, so I removed the pipe and brass cap from its original position and replaced with a 5/8" x 30" iron rod set one foot below the surface of the natural ground line. When construction was completed, I reset the pipe and brass cap in its original position and also left the iron rod in place.

New BT's- 37" D. fir bears S.23 1/2°E., 26.2 ft. marked T24S R8W S3 BT.  
12" maple bears S.23°W., 38.6 ft. marked T24S R8W S4 BT.

The newly constructed road bears North approx. 50 ft. and is approx. 30 ft. above the corner.

10/1/82

Les Roberts  
For: International  
Paper Co.  
November 20, 1981  
M 90 - 12

Gregory Quibell,  
Deputy, Douglas Co.  
Surveyors Office  
Karen Reed - John  
Powell  
October 13, 1982  
C.S. 62/1

Burt Holt  
L.S. #418  
Oct. 1, 1982  
C.S. 58/229