

Douglas County Surveyor's Record of
Government Corners Renewed

24 T. S. 8 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Mark Smalley
For: Roseburg
Forest Prod.
July 1995
CS File 65/1-1

1/4 Corner for Sections 29 & 30 109
Found - B.L.M. brass cap w/iron pipe dated 1962
Stone
Fir, 36", S.27°E., 45.5 ft. - tree is down.
Fir stump, 12", N.76°W., 48.2 ft. - cut low.
New Accessories -
W.Fir, 12", N.70°E., 43.1 ft. scribed "1/4 S BT"
Chinquapin, 5", S.17°W., 9.2 ft. scribed "1/4 S BT"
Hemlock, 16", S.33°E., 17.7 ft. scribed "1/4 S BT"
Fir, 4", N.62°W., 9.2 ft. scribed "1/4 S BT"

Corner for Sections 8, 9, 16 & 17 110
Found - 1959 Cadastral B.C.I.P.
- 28" Fir, N.25°E., 35.6 ft. (healed)
- 34" Fir, S.7°E., 122.1 ft. (snag)
- 26" Fir, S.18 1/2°E., 22.4 ft. (snag, orig. BT)
- 50" Fir, S.57°W., 6.6 ft. (healed, orig. BT)
New BT's - 5" Fir, N.49°E., 8.4 ft. scribed "S 9 BT"
- 13" Fir, S.7°W., 47.0 ft. scribed "S 17 BT"

1/4 Corner for Sections 17 & 16 111
Set - 5/8" x 48" iron rod with aluminum cap marked "LS 2354"
New BTs - 16" Fir, N.22°W., 10.5 ft. scribed "1/4 S 17 BT"
- 17" Fir, N.40°W., 19.2 ft. scribed "1/4 S 17 BT"
- 17" Fir, N.32°E., 19.7 ft. scribed "1/4 S 16 BT"
- 22" Fir, S.64°W., 10.7 ft. scribed "1/4 S 17 BT"

Corner for Sections 16, 17, 20 & 21 112
Found - 1962 Cadastral B.C.I.P.
- 24" Fir, N.86°W., 53.5 ft. (healed)
- 26" Fir, N.27 1/2°E., 37.6 ft. (healed orig. BT)
- 30" Fir, S.4°E., 17.8 ft. (healed orig. BT)
- 16" Fir, S.42°W., 23.8 ft. (healed)

113

Mark Smalley
For: Kenneth Ford
Jan. 1996
M 123 - 38