

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

Weyerhaeuser
Co.
By Donald L.
Peel
April, 1967
C.S. File
No. 55/30

Closing Corner common to Sections 1 & 6, T25S, R8 & 9W. 1

Found - GLO Survey Record, Post -- Gone.

60" cedar S.86°W. 11 lks., now cedar snag, scribe visible.

12" cedar S.60°E. 78 lks., now 16" cedar already copped open,
scribe visible. 13

Set - 4" x 3/4" pipe, 3 1/2' in ground & square post.

Re-referenced with "W" nails & plates only: 30" hemlock S.49°E. 65.6 ft.
50" fir S.28°W. 44.9 ft.

MICROFILM TO HERE 10/67 2

Section Corner to Sections 11 and 14 only.

Found - Orig. 36", now 44" Fir, S.42°W. 11.9 ft., partial barkscribe in
area of "BT". This BT. described in subs. survey as obliterated.

Orig. 24" Fir, now badly decayed stump, N.44°W. 19.8 ft., no scribe.

1905 BT: 16", now 38" Fir N.48°E. 31.7 ft., alive, shows good scar, do not open.

No trace S.E. BT. Orig. NE BT possibly under larger log.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 9 W S 11
Office, 1968 S 14

New BT's: 11" Maple S.28°E. 106.6 ft. mkd. T24S R9W S14 CS BT.

15" D. Fir N.80°E. 43.6 ft. mkd. T24S R9W S11 CS BT.

Note - This corner lies 316 ft. S. of closing corner of Secs. 10 & 15. 3

Closing Corner to Sections 10 and 15 only.

Found - Orig. 40", now 45" Fir, alive, S.31°W. 25.1 ft., shows good scar.

Orig. 40", now 46" Fir, alive, N.62 1/2°W. 53.5 ft., open & find scribe mks

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 9 W S 10 CC
Office, 1968 S 15

Rescribed BT's. in bark below scars:

45" Fir S.31°W. 25.1 ft. mkd. T24S R9W S15 CC CS BT.

46" Fir N.62 1/2°W. 53.5 ft. mkd. T24S R9W S10 CC CS BT.

Note - This corner lies 316 ft. N. of sec. cor. to Secs. 11 & 14, above. 4

1/4 Corner to Sections 15 and 16.

Found - Unrecorded 1/2" Steel Pipe set a corner point & old 4"x4" wood post.

Orig. 24", now 32" Fir, alive, S.27°E. 24.4 ft., shows good scar. Do not open

Orig. 30", now 36" Fir, alive, N.85°W. 5.9 ft., open & find scribe marks.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 9 W
(Reset Steel Pipe Office, 1968 1/4 S 16 S 15
Alongside)

New BT's: 7" Hemlock N. 18° W. 29.0 ft. mkd. 1/4 S16 CS BT.

5" Chinquapin S. 51°E. 27.2 ft. mkd. 1/4 S15 CS BT.

Note - This corner lies on moderate south slope on N. edge of cut off area. 5

Section Corner to Sections 15 - 16 - 21 - 22.

Found - Orig. 40", now 50" Fir, alive, S.11°W. 7.3 ft., shows good scar.
Do not open.

Orig. 30", now 34" Fir Snag, N.43 1/2°W. 33.0 ft., Open & find scribe.

Orig. N.E. & S.E. BT's., now stumps, down & out of place.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 24 S R 9 W
Office S 16 S 15
1968 S 21 S 22

New BT's: 18" Hemlock N.42°E. 18.3 ft. mkd. T24S R9W S15 CS BT.

18" Hemlock S.67°E. 27.4 ft. mkd. T24S R9W S22 CS BT.

15" Hemlock S.43°W. 28.8 ft. mkd. T24S R9W S21 CS BT.

10" Hemlock N.25°W. 26.4 ft. mkd. T24S R9W S16 CS BT.

Note - This corner lies 60 ft. south of road. 6

Section Corner to Sections 9 - 10 - 15 - 16.

Found - Orig. 40", now 48" Fir, alive, N.42°E. 43.6 ft. shows good scar.
We do not open.

Orig. 40", now 52" Fir, alive, S.83°W. 8.6 ft., shows good scar.

Orig. 16", now 17" Fir Snag, S.68 1/2°E. 38.9 ft., opened previously
& shows "2 S" & fragmentary scribe on decayed blaze.

Orig. 48", now 56" Fir, alive, N.45°W. 32.3 ft., shows good scar, do
not open. Rescribed in bark alongside scar. "T24S R9W S9 CS BT".
(continued over)

Vernon "Ray" Tracy
Jack Heritage & V. Perron
February, 1968
C. S. File No. 54/55