

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Set - Brass Cap at Cor.Mkd: County Surveyor's T 24 S R 9 W
Office S 9 S 10
1968 S 16 S 15

New BT: 9" Maple S.68°E. 40.4 ft. mkd. T24S R9W S15 CS BT., also
"W" Nail at base.

Note - "W" Nails at base of original bearing trees. Timber in this
area is large. We do not scribe any other tree.

Closing Corner to Sections 15 and 22.

Found - Orig.40",now 58" Fir, alive, S.12°W. 61.4 ft., shows good scar,
We do not open.

Orig.36",now 48" Fir, alive, N.35°W. 13.2 ft., Open & find scribe.

Set - Brass Cap at Cor:Mkd: County Surveyor's T 24 S R 9 W S15
Office, 1968 S22 CC

New BT's: 6" Hemlock S.82°W. 5.6 ft. mkd. CC S22 CS BT.

8" Hemlock S.12°W. 14.7 ft. mkd. T24S R9W S22 CC CS BT.

13" Hemlock N.22°W. 20.5 ft. mkd. T24S R9W S15 CC CS BT.

Note - This corner lies approx. 380 ft. E. of ridge top, course N.E.

Vernon "Ray" Tracy
J. Heritage & V. Perron
Feb. March 1968
C.S. File No. 54/55

RE-RENEWED, SEE CORNER NO. #11

8 SEPT. 68

1/4 Corner to Section 10 and Section 15.

Found - 2 Weyerhaeuser Trees: One is a 44" D.Fir Stump with tag
and a nail, also cruiser's mark. Tag gives bearing &
distance as N.22 1/2°W. 10.7 ft. One is a 36" D.Fir Stump
with a tag & nail, giving bearing & dist. S.25°W. 40.5 ft.

Set - 1"x30" Galv. Iron Pipe with Brass Cap, 26" in ground & Mkd:

T 24 S R 9 W

1/4

S 10

S 15

1969

OLS 536

From Monument, I marked: 12" Maple, 1/4 S10 BT" which bears
N.57 1/2°E. 100.4 ft.

Set a 5/8" x 30" Iron Rod 26" in the ground which bears S.27°W. 47.0 ft.

9

Closing Corner Sections 14 and 23.

Found - 22" D.Fir with open face & visible scribe with metal BT tags.

40" D.Fir with open face & visible scribe with metal BT tags.

From 22" D.Fir the corner bears N.47°W. 29.4 ft.

From 40" D.Fir the corner bears S.43°W. 25.2 ft.

Set - 1"x30" Galv.Iron Pipe with Brass Cap, 26" in ground & Mkd:

T 24 S R 9 W

CC S 22 S 14

S 23

1969

OLS 536

Mkd: BT's.: 18" D.Fir T24S R9W S14 BT which bears N.23°E. 42.7 ft.

20" Hemlock T24S R9W S23 BT bears S.29°E. 95.3 ft.

16" D.Fir T24S R9W S22 BT which bears N.53°W. 79.6 ft.

I placed bearing tree tags on all bearing trees, facing the monument.

Glenn S. Baughman
For Umpqua Nat'l. Forest - Glide Ranger District
March, 1969
G. S. File No. 55/112 M 37 - 42

10

1/4 Corner East Side of Section 15.

No evidence of corner, set by proportionate measurement.

Set - 1"x30" Galv.I.P. with Brass Cap: T 24 S R 9 W

1/4 S15

1969

From the Monument, I marked: OLS 536

6" D. Fir 1/4 S15 BT" which bears S.68 1/2°W. 64.2 ft.

I set BT. tags on the bearing tree facing the monument.