

Douglas County Surveyor's Record of
Government Corners Renewed

T. 24 S. T. S. R. 9 W. R.W.W.M.

ROBE-CHAPMAN CO., EUGENE, ORE., 21881

Glenn S. Baughman
For Umpqua Nat'l. Forest
March, 1969
C.S. File No. 55/112 M 37 - 42

Closing Corner to Sections 15 and 22. 11
Found - No evidence of corner due to new road construction. Ren. #7
Set - 1"x30" galv. I.P. with Brass Cap Mkd: T 24 S R 9 W
S 15
S 22 | S14 CC
1969

From the I.P. Monument, I marked: OLS 536
11" D. Fir bears N. 80 $\frac{1}{2}$ ° E. 50.5 ft. mkd: "T24SR9W S14 BT."
5" Maple bears S. 87 $\frac{1}{2}$ ° W. 61.6 ft. mkd: "T24SR9W S22 BT".
9" Chinquapin bears N. 27 $\frac{1}{2}$ ° W. 72.4 ft. mkd: "T24SR9W S15 BT".
I set BT. tags on all bearing trees & facing the monument.

Witness Corner to $\frac{1}{4}$ Corner of Sections 15 and 22. 12
Found - 2 Stumps with Weyerhaeuser Tags and Nails:
36" D. Fir Stump S. 28 $\frac{1}{2}$ ° W. 90.9 ft.
30" D. Fir Stump bears N. 81° W. 70.0 ft.
I was unable to set $\frac{1}{4}$ corner due to the point falling on the vertical face of a rock quarry.
Set - 1"x30" galv. I.P. with Brass Cap 10" in ground & then constructed a rock mound 16"x48" around pipe.
From this monument the true corner bears S. 89° 24' 36" E. 125.99 ft.

T 24 S R 9 W
W C
 $\frac{1}{4}$ S 15
S 22
1969
OLS 536

From the iron pipe monument, I marked:
4" Alder X & BTd which bears N. 7° W. 55.9 ft.
Also set a 5/8" X 30" Iron Rod 26" in the ground S. 45° W. 107.0 ft.

Vernon "Ray" Tracy
V. Perron
C.S. File No. 54/72

No. W. Corner Section 6, T25 - 8W. 13
Found - $\frac{1}{2}$ " Steel Pipe set for Corner, See Ren. #1, & Weyerhaeuser Bearing Trees as recorded.
Orig. 60" Cedar, down, S. 86° W. 7.3 ft., scribe visible on decaying blaze.
Orig. 12", now 16" Cedar, alive, S. 60° E. 51.5 ft., open scribe visible.
Rescribe "T25S R8W S 6 CC CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 25 S R9W CC S 6 R8W
(Reset Steel Tube alongside) 1970
New BT: 13" Hemlock S. 15° W. 26.0 ft. mkd: "CC CS BT".
This corner lies on N.E. slope in old growth timber.
Also found 15x12x3" Sandstone mkd: "CR 6", no record at this time.

MARCH 71

8/26/70

Clell Goodwin
Lenora Ladig
C.S. 57/30
June 17, 1975

~~Standard Corner for Sec. 34 & 35 T23-10, only. 14
Found: 3/4" Pipe set by Weyerhaeuser and remains of all original B.T.'s. should be T24 only.
Set: 1 1/2" Iron pipe flanged on bottom projecting 1 ft. out of ground from which a 10" Hemlock bears N. 10° E., 21 1/2 ft. scribed "S35 X" in single blaze.
A. 24" Hemlock bears N. 80° W., 24.4 ft. scribed "X S 34"
Compass Declination 20°~~

SW Corner Sec. 32 only, T. 23-9. 15
Found - 3/4" Gal. I.P. placed by Weyerhaeuser Co. engineers in 1974. (Unrecorded)
From Which:
a 18" Fir stump (OBT) scar evident, bears N. 40° E., 9.9 ft.
a 36" Fir windfall (OBT) face evident bears N. 53° W., 33.0 ft.
a 12" Chinquapin RP bears N. 76° 30' E., 19.9 ft.
a 12" Fir RP bears S. 15° 30' E., 19.8 ft.
a 8" Fir RP bears S. 52° W., 6.8 ft.
a 8" Fir RP bears N. 81° W., 27.6 ft.

2/21/77

JAN 78
1-79

3/77

Michael S. McDowell
For: Weyerhaeuser Co.
Feb. 21, 1977
M 63 - 23
C.S. 58/139