

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 S T. S. R 1 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Closing Corner 30 - 31, T 25 S, R 1 W bears East 46.2 ft. 1
As this closing corner is not the legal terminus of the closing line, therefore at this point, I set a 1" I.P. with steel cap from which #160
which
A Hemlock 8" in diam. bears N 44° E, 18.8 ft. marked T 25 S, R 1 W,
S 30 C.C. P.S. 253, BT
A Cedar 24" in dia. bears S 36° E 32.0 ft. marked T 25 S, R 1 W,
S 31 C.C. P.S. 253, BT

West $\frac{1}{4}$ Cor. Sec. 30 2
At this point, I set a 1" I.P. with steel cap, from which:
A Fir 18" in dia. bears N 52° E 10.9 ft. marked T 25 S, R 1 W,
 $\frac{1}{4}$ S 30 P.S. 253 BT
A Fir 20" in dia. bears S 49° E 49.5 ft. marked T 25 S, R 1 W,
 $\frac{1}{4}$ S 30 P.S. 253 BT

Closing Corner 19 - 30 - 24, T 25 S, R 1 W. At this point I set a 3
 $1\frac{1}{2}$ " I.P. with steel cap from which:
A Fir 22" in dia. bears N 51° E 31.0 ft. marked T 25 S, R 1 W, S 19
C.C. P.S. 253 BT
A Hemlock 16" in dia. bears S 36° E 9.5 ft. marked T 25 S, R 1 W,
S 30 C.C. P.S. 253 BT

West $\frac{1}{4}$ Cor. Sec. 19 T 25 S, R 1 W 4
At this point I set a $1\frac{1}{2}$ " I.P. with steel cap from which:
A Cedar 30" in dia. bears N 32° E 20.7 ft. marked T 25 S, R 1 W
 $\frac{1}{4}$ S 19 P.S. 253 BT

Closing Corner 18 - 19 - 13 bears East 62.1 ft. 5
As this closing corner is not the legal terminus of the closing line, therefore at this point I set a 2" I.P. with steel cap from which: -SEARCHED FOR, NOT FOUND MAY. 1967 - V.R.T.
A Cedar 30" in dia. bears N 81 $\frac{1}{2}$ ° E 53.5 ft. marked T 25 S, R 1 W
S 18 C.C. P.S. 253 BT
A Hemlock 20" in dia. bears S 70° E 13.2 ft. marked T 25 S, R 1 W
S 19 C.C. P.S. 253 BT

West $\frac{1}{4}$ Cor. Sec. 18, T 25 S, R 1 W. At this point I set a 1" I.P. 6
with steel cap from which:
A Fir 30" in dia. bears S 14° W 27.5 ft. marked T 25 S, R 1 W,
 $\frac{1}{4}$ S 18 P.S. 253 BT
A Fir 30" in dia. bears N 57° W 53.1 ft. marked T 25 S, R 1 W,
 $\frac{1}{4}$ S 18 P.S. 253 BT
Note: Section 18 being logged and no suitable trees standing
within a reasonable distance I marked bearing trees in Sec. 13

Closing corner 7 - 18 - 12, T 25 S, R 1 W. At this point I set a 7
1" I.P. with steel cap from which: - FOUND O.K. MAY 1967 V.R.T. #
A Fir 12" in dia. bears N 46 $\frac{1}{2}$ ° E 12.0 ft. marked T 25 S, R 1 W,
S 7 C.C. P.S. 253 BT
A Fir 18" in dia. bears S 55° E 37.8 ft. marked T 25 S, R 1 W,
S 18 C.C. P.S. 253 BT. REFERENCED OUT FOR Logging Purposes
#136
1967 G. L. WRIGHT, C.S. OFFICE. SEE CS 59/30

West $\frac{1}{4}$ Cor. Sec. 7, T 25 S, R 1 W. At this point I set a 1" I.P. with 8
steel cap from which: - FOUND O.K. - MAY, 1967, V.R.T.
A Fir 18" in dia. bears N 85 $\frac{1}{2}$ ° E 32.1 ft. marked T 25 S, R 1 W,
 $\frac{1}{4}$ S 7 P.S. 253 BT
A Fir 14" in dia. bears S 46 $\frac{1}{2}$ ° E 11.6 ft. marked T 25 S, R 1 W,
 $\frac{1}{4}$ S 7 P.S. 253 BT #168

Closing corner 6 - 7 - 1, T 25 S, R 1 W. At this point I set a $1\frac{1}{2}$ " I.P. 9
with steel cap from which: - FOUND OK - MAY, 1967 - V.R.T.
A Fir 16" in dia. bears N 65° E 19.7 ft. marked T 25 S, R 1 W,
S 6 C.C. P.S. 253 BT
A Fir 12" in dia. bears S 29° E 13.3 ft. marked T 25 S, R 1 W,
S 7 C.C. P.S. 253 BT

V. W. Hosford, O.L.S. # 253
April, 1949 to October, 1950

C.S. 40/279
M12-61

RENEWED, SEE CORNER NO #160