

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

Milo E. Godfrey
V. Tracy &
M. Stone
June 4, 1963
C.S. 52/30

54
1/4 Corner to Sec. 2, T25-1W. & Sec. 35, T24-1W.
Found - Rock Mkd: "1/4" on N. face as called for in gov't. notes.
60" Fir N.50°E. 23.1 ft., shows good scar. Did not open.
24" Fir S.5°E. 7.3 ft., shows good scar. Did not open.
Set - Alongside Rock; Brass Cap Mkd: County Surveyor's T24S Office, 1963 T25S RLW S35 S 2 1/4
New BT's: 9" R.Cedar N.53°W. 10.1 ft. Mkd: 1/4 S35 CS BT.
18" R.Cedar S.77°E. 15.0 ft. Mkd: 1/4 S2 CS BT.

Thomas E. Shrum, Jr.
For U. S. Plywood, Inc.
April 19, 1963
C. S. File No. 51/254

55
Section Corner: Sections 22, 23, 26, 27.
Found - Original Stone
10" Hemlock, S. 68° E., 30.4 feet (original)
21" Cedar S. 71° W., 10.6 feet (orig.)
28" Cedar N. 31° W., 33.7 feet (orig.)
7" Maple, N. 66° E., 17.2 feet (orig.)
(Maple rotten, scribe not legible.)
Set - 2 1/2" Aluminum cap.
10" Doug. Fir, N. 40° E., 23.3 feet Mkd: S23 BT.

56
1/4 Section Corner: Sections 22 and 27.
Found - Original Stone (no marks on stone)
8" Doug. Fir N. 29° E., 23.5 feet Mkd: 1/4 S22 RELO79 BT
7" Hemlock, S. 08° E., 19.8 feet Mkd: 1/4 S27 RELO79 BT.
8" Doug. Fir S. 60° W., 18.5 feet (original)
7" Cedar, N. 31° E., 10.6 feet (original) (New Per. Ren #15)
Set - 2 1/2" Aluminum Cap - (Set 1.0 foot west of point on rock).

G.R. Lecklider
For U.S. Plywd.
Aug. 1960
M 19 - 46

57
1/4 Corner Section 12 only. (EAST)
Found - Corner Stone and Two Trees:
24" Fir N.49°W. 35.0 feet
36" Fir S.21°W. 39.6 feet
Set - Steel Tube with Survey Cap.
CORNER NO. 85

Bruce R.
Rogers, Dep.
W. Stoffel &
M. Stone
C. S. File
No. 52/30

58
August 1960
SEE 1998/99 BLK Renewed PGS 206A3-4 FOR NEW STAKE CAP
Section Corner to Sections 8 - 9 - 16 - 17.
Found - 26" Cedar, now stump, S.9°W. 33.0 ft. This is Orig. BT.,
as reported by Shaner, See Ren. #17. No trace of scribing
nor scar, but stump is only 1.5 ft. tall.
58" D. Fir S.89°E. 58.9 ft. scribing visible "S16 BT".
16" D. Fir, blown down, N.36°W. 30.7 ft., scribing visible.
1/2" Brass Rod at Corner. See Ren. #17.
New BT's: - 8" Hemlock S.10°W. 56.0 ft. Mkd: S17 CS BT.
12" Hemlock N.85°W. 43.5 ft. Mkd: T25S RLW S8 CS BT.
No tree close in NE Quadrant.

March 8, 1965

B. R.
Rogers,
Deputy &
Crew
C. S.
File No.
52/30

59
1/4 Section Corner to Sections 3 and 2.
Found - 10" Cedar, now 15", S.52, E. 11.2 ft., scribing visible.
13" Hemlock, now 20", scribing visible.
Rotted remains of Original Stake at Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T 25 S
1/4 S 3 / S 2 RLW
New BT's: 7" Hemlock N.50, W. 83.9 ft. Mkd: 1/4 S3 CS BT.
7" D. Fir S.20, W. Mkd: 1/4 S3 CS BT.
May 25, 1965

Vernon "Ray"
Tracy &
Crew
C. S. File No.
52/30

60
1/4 Corner to Sections 27 and 26.
Found - Orig. 15", now 26" Hemlock, recorded as Fir, S.35°W. 5.3 ft., prev.
opened and shows "S" scribe. Alive.
Orig. 18", now 32" Hemlock N.68°E. 23.1 ft. Alive, shows scar. Do not open
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T25S 1/4 S 27/S 26 RLW
New BT's: 10" Hemlock S. 58° W. 10.8 ft. mkd. 1/4 S27 CS BT.
17" Hemlock N. 29° E. 44.8 ft. mkd. 1/4 S 26 CS BT.
Note - Corner lies on moderate, N.E. slope approx. 120 ft. S. of old Jeep
Trail, course NE - SW on top of spur.
August 2, 1966
CORNER NO. 155