

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 1 W. R. W. W. M.

72  
Sec. Cor. to Sections 25 & 36 only, T25-1W.  
Found - 1927 GLO Brass Cap, properly mkd.  
Orig. 36", now 57" Pine(not fir) Stump, N. 88° W. 33.7 ft., shows fair scar. We do not open.  
Orig. 30", now 30" Fir, 1 ft. high stump, S. 14° W. 43.6 ft.  
14", now 20" Pine, now shattered stump, S. 70° W. 46.2 ft.  
Also find stumps of obliterated BT's. to E. of line.  
New BT's: 14" D. Fir N. 39° W. 42.0 ft. mkd. T25S RLW S25 CS BT.  
14" D. Pine S. 60° W. 108.3 ft. mkd. T25S RLW S36 CS BT.  
Note - This corner lies approx. 85 ft. north of closing corner of sections 30 and 31, T25-1E.

73  
1/4 Corner to Sections 7 and 8.  
Found - Orig. Basalt Stone 24" x 12" x 7" above ground mkd. @ 1/4 X" on top, very solid.  
15", now 16" Hemlock S. 86° W. 10.0 ft., shows "1/4 S7 CSBT" on unhealed blaze. See Ren. #20.  
Both Orig. BT's. destroyed by logging. Because of size & rigidity of Stone, we do not set Brass Cap.  
New BT's: 60" Fir Stump N. 65° E. 25.5 ft. mkd. 1/4 S 8 CS BT.  
19" Hemlock N. 6° W. 13.1 ft., mkd. 1/4 S 7 CS BT.  
Note - Corner lies 40 ft. west of small crekk, course S. 15° W.

74  
1/4 Corner to Sections 35 and 36.  
Found - Basalt outcrop 30" x 12" x 6" above ground, very solid and mkd. with "X" & "1/4" on Top.  
Orig. 36", now 42" Fir, S. 88° E. 34.3 ft.(face), shows good scar. Alive, we do not open.  
Orig. 28", now 28" Fir Stub, N. 88° W. 32.3 ft.(face), Dead, shows "1/4 S35" scribe on prev. opened blaze.  
Set - Brass Cap at Cor. Mkd: County Surveyors T 25 S R 1 W  
(alongside mkd. stone Office, 1966 1/4 S 35/S 36 & 1' south)  
New BT's: 10" D. Fir S. 86° E. 24.8 ft. mkd. 1/4 S 36 CS BT.  
8" D. Fir S. 65° W. 18.2 ft. mkd. 1/4 S 35 CS BT.  
Note - This corner lies on S. slope, approx. 475 ft. N. of old scared man trail.

75  
Section Corner to Sections 25 - 26 - 35 - 36.  
Found - Orig. 5", now 7" Hemlock Corner Tree, alive & in good condition, shows good scars at base of tree. Do not open.  
Orig. 8", now 15" Hemlock N. 89° E. 2.0 ft., shows good scar. Alive, Do not open.  
Orig. 12", now 28" Hemlock S. 51° E. 14.3 ft., now stump, shows "S 36" scribe on prev. opened blaze.  
No trace of N.W. nor S.W. BT's.  
DO NOT SET BRASS CAP. Set 1" x 30" I. Rod at base of Cor. Tree, N.W. Side.  
New BT's: 14" D. Fir S. 41° E. 50.4 ft. mkd. T25S RLW S36 CS BT.  
14" D. Fir S. 6° W. 45.1 ft. mkd. T25S RLW S35 CS BT.  
11" Chinq. N. 82° W. 67.6 ft. mkd. T25S RLW S26 CS BT.  
Note - This corner lies on very steep N. slope of hill

76  
Township Corner, T24S & T25S. - R. 1W. & R1E.  
Found - Orig. 18", now 28" Cedar, N. 64° E. 11.2 ft., prev. opened, many years ago, "SE S3" scribe visible on nearly rehealed blaze. Rescribed: "T24S R1E S31 DCS BT".  
Orig. 28", now 36" Fir S. 37° E. 43.6 ft. Alive, good cond. shows good scar.  
Orig. 30", now 36" Fir S. 86° W. 33.0 ft. Alive, good cond. " " "  
Orig. 18", now 21" Fir N. 25° W. 31.0 ft. Alive, good cond. " " "  
Set - Brass Cap at Cor. Mkd: Doug. Co. Surv. T24S S 36 | S 31 R1E  
Office, 1966 T25S RLW S 1 | S 6  
New BT: 10" Hemlock N. 60° W. 34.8 ft. mkd. "T24S RLW S36 DCS BT.  
No smaller trees close to S.E. nor S.W.  
Note - This corner is on Douglas-Lane County Line.

Nov. 3, 1966

Vernon "Ray" Tracy  
Jack Heritage & F. West.  
October, 1966  
C. S. File No. 52/30

RE-REVIEWED, SEE CORNER NO. #164

RE-REVIEWED, SEE CORNER NO. #125