

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

144

Cl. Corner to Sections 18 and 19, T25S-RLW.
Found - 1927 GLO Brass Cap, properly marked & BT's, as follows:
8", now 11" Fir Snag, N. 61° E. 30.4 ft., shows scar, we do not open.
8", now 10" Fir Snag, S. 40° E. 27.7 ft., shows scar, we do not open.
New BT's: 36" Cedar S. 28° E. 7.4 ft. mkd. T25S RLW S19 CC CS BT.
13" D. Fir N. 1° E. 31.6 ft. mkd. T25S RLW S18 CC CS BT.
Note - This corner lies on S.W. slope approx. 150 ft. S. of corner to
Secs. 13 & 24, T25-LW, Ren. #22, which is O. K.

78

Witness Corner(south) to Sections 12 & 13 only, T25-LW.
Found - Rock marked "WC S12" on N.E. & "S13" on S.W., firmly set 1.3 ft.
N. of C.C. of Secs. 7 & 18, T25-LE, which is a 1927 GLO
Brass Cap, firmly set in mound of stone.
Orig. 40", now 40" Fir Snag, N. 89° W. 13.2 ft. (slope), shows
good scar, we do not open.
30", now 34" Fir, S. 24° W. 31.7 ft., now Stump, shows good scar.
Orig. 20", now 20" Fir Snag, N. 58° E. 13.2 ft., (recorded as
being obliterated, frag. scribe marks visible on chopped face.)
New BT's: 12" Cedar S. 71° W. 40.3 ft. mkd. W.C. T25S RLW S13 CS BT.
12" Pine N. 14° W. 106.3 ft. mkd. W.C. T25S RLW S12 CS BT.
Note - This cor. lies on precip. W. slope on N-S cutting line, cut off to W.

79

Wit. Cor. (north) to Sections 12 & 13 only, T25-LW.
Found - Steel tube & Alumin. Cap & Rock face mkd. S12 B.O. N. 16° W. 17.7 ft
as recorded in Ren. #24.
Orig. Rock with "WC" only.
Set - Brass Cap 482.5 ft. N. of true corner (note, dist.
to true cor. not on Brass Cap) Wit. Cor. T25S RLW $\frac{S}{S} \frac{12}{13}$ RLE
Set Steel tube alongside B.C.
There are no live trees W. of line. Mkd. New BT's. to East.
9" Yew N. 26° E. 39.0 ft. mkd. W.C. CS BT.
5" Yew N. 85° E. 24.9 ft. mkd. W. C. CS BT.
Note - This corner lies on top of verticale rock bluff 60' high
above N. fork of Hi Power Creek.

80

$\frac{1}{4}$ Corner to Section 24 only, T25-LW.
Found - Basalt Stone mkd. "W" on W. face. - No trace 1927 GLO Brass Cap.
26", now 30" Fir Stump, N. 45° W. 66.0 ft., shows good scar, Do not open.
8", now 11" Madrone, N. 64° W. 4.6 ft., prev. opnd. & shows fragments
of scribe. (recorded as S. 64° W.)
Also found obliterated 16" Madrone N. 53° E. 7.9 ft.
Set - Brass Cap Mkd: County Surveyor's T25S RLW $\frac{1}{4}$ S 24 RLE
Office, 1966
New BT's: 6" Madrone N. 39° E. 6.0 ft. mkd. " $\frac{1}{4}$ S CS BT".
5" Madrone N. 21° W. 5.5 ft. mkd. " $\frac{1}{4}$ S24 CS BT".
11" Madrone N. 64° W. 4.6 ft. Remarked " $\frac{1}{4}$ S24 CS BT".
Note - This corner lies at foot of 30 ft. bluff on top of 100' high bluff.

81

Sec. Cor. to Sections 1 & 12 only, T25S-RLW.
Found - 1927 GLO Brass Cap, properly mkd. & nearly out of the ground.
Reset - Brass Cap 12" in ground & built mound of stone 15" high around
Orig. 60", now 60" Fir Stump, cut low, S. 48° W. 19.1 ft., no scribe.
Orig. 30", now 31" Fir, N. 71° W. 26.4 ft. (recorded 4 lks., should
be 40 lks.) Scribe marks visible on nearly healed blaze. Alive.
Obliterated BT's. to N.E. & S.E., now turned out.
New BT's: 11" W. Fir S. 74° W. 61.6 ft. mkd. T25S RLW S12 CS BT.
5" Hemlock N. 59° W. 29.4 ft. mkd. S 1 CS BT.
Note - This cor. lies at N.E. cor. of cut off unit on top of round spur.

Vernon "Ray" Tracy
Jack Heritage & E. West
November, 1966
C. S. File No. 52/30

RE-RENEWED SEE CORNER NO. #144
RE-RENEWED SEE CORNER NO. #145
RE-RENEWED SEE CORNER NO. #165
RE-RENEWED SEE CORNER NO. #166