

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

97

$\frac{1}{4}$  Corner to Sec. 5, T25-1W. & Sec. 32, T24-1W. #131  
Found - Orig. 14", now 17" Cedar, N. 43° W. 5.3 ft. Open & find scribe. Alive.  
Orig. 36", now 40" Fir, S. 74° E. 18.5 ft. Alive, shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyors T24S  $\frac{1}{4}$  S 32 RLW  
Office, 1966 T25S  $\frac{1}{4}$  S 5  
New BT's: 6" Hemlock N. 52° W. 26.7 ft. mkd.  $\frac{1}{4}$  S 32 CS BT.  
5" Hemlock S. 49° E. 32.5 ft. mkd. ° S 5 CS BT.  
Note - This corner lies approx. 100 ft. south of creek, course west.

98

$\frac{1}{4}$  Corner to Sec. 3, T25-1W. & Sec. 34, T24-1W.  
Found - Orig. 24", now 36" Fir, N. 50° E. 28.3 ft. Open & find "B" scribe.  
Reverse. Alive.  
Orig. 42", now 48" Fir, S. 42° W. 23.1 ft. Alive, shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyors T24S  $\frac{1}{4}$  S 34 RLW  
T25S  $\frac{1}{4}$  S 3  
New BT'S; 12" Hemlock N. 31° W. 9.2 ft. mkd.  $\frac{1}{4}$  S34 CS BT.  
8" Hemlock S. 2° W. 3.3 ft. mkd.  $\frac{1}{4}$  S 3 CS BT.  
Note - This corner lies north of Grizzly Creek, approx. 250 ft. on bench.

99

$\frac{1}{4}$  Corner to Sec. 1, T25-1W. & Sec. 36, T24-1W.  
Found - No trace of Stone called for in notes.  
Orig. 12", now 23" Fir, S. 70° E. 11.2 ft., opened & shows scribe.  
Orig. 24", now 30" Fir, N. 75° W. 10.6 ft., shows good scar. Alive.  
Set - Brass Cap at Cor. Mkd: County Surveyors T24S  $\frac{1}{4}$  S 36 RLW  
Office, 1966 T25S  $\frac{1}{4}$  S 1  
New BT's: 24" D. Fir S. 20° W. 35.3 ft. mkd.  $\frac{1}{4}$  S 1 CS BT.  
7" Laurel N. 4° W. 19.3 ft. mkd.  $\frac{1}{4}$  S 36 CS BT.  
Note - This corner lies on S. side of small creek, course S.W. on very steep westerly slope in area of several small bluffs.

100

$\frac{1}{4}$  Corner to Sections 9 and 16.  
Found - Orig. Stone with partial chisel marks only.  
Orig. 15", now 22" Fir, down & dead, S. 25° W. 36.3 ft.,  
scribe visible on opened blaze.  
10", now 14" Hemlock N. 45° E. 38.8 ft., shows @  $\frac{1}{4}$  S9 253 BT" scribe  
on unhealed blaze. Alive. See Ren. #32.  
20", now 24" Cedar S. 71 $\frac{1}{2}$ ° E. 39.0 ft., shows scribe on unhealed blz.  
Set - Brass Cap at Cor. Mkd: County Surveyors T25S RLW  
Office, 1966  $\frac{1}{4}$  S 9  
S 16  
Do not mark new BT's.  
Note - This corner lies approx. 32 ft. west of small creek, course South.

101

$\frac{1}{4}$  Corner to Sections 5 and 8.  
Found - Orig. 9", now 18" Fir Snag, S. 29° E. 17.8 ft. Open & find "S" Scribe  
No trace of N.W. Orig. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyors T25S RLW  
Office 1966  $\frac{1}{4}$  S 5  
S 8  
New BT's: 12" D. Fir S. 11° E. 55.7 ft. mkd.  $\frac{1}{4}$  S 8 CS BT.  
22" I. Cedar N. 79° W. 5.9 ft. mkd.  $\frac{1}{4}$  S 5 CS BT.  
5" Chinq. N. 14° W. 24.6 ft. mkd.  $\frac{1}{4}$  S 5 CS BT.  
Note - This corner lies on very steep, S.Ws. slope, approx. 240 ft. west  
of top of spur, course north.

102

Sec. Corner to Sections 1 - 2 - 11 - 12.  
Found - Alumn. Cap, See Ren. #52.  
Orig. BT, down & pushed out of place.  
5" Vine Maple, now 4' high stub, S. 81 $\frac{1}{2}$ ° W. 6.4 ft., scribe visible.  
60" Fir Stump, unrecorded, N. 24° E. 28.6 ft. mkd. "S1 BT".  
All other BT's. destroyed by recent logging.  
New BT's: 6" Vine Maple S. 74° W. 76.2 ft. mkd. S11 CS BT.  
60" Fir Stump S. 49° E. 43.0 ft. mkd. S 12 CS BT.  
Note - No trees available to N.E. nor N.W.

Vernon "Ray" Tracy  
Jack Heritage & E. West.  
November, 1966  
C. S. File No. 52/30