

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

103

Section Corner to Sections 4 - 5 - 8 - 9.

Found - Orig. Corner Stone 12"x6"x5" mkd. with 4 notches on E. and 5 notches on S. faces.

Orig. 10", now 20" Hemlock, N. 21° W. 29.0 ft. Open & find "25 R" Scribe.

Orig. S. W. BT., turned out & lying downhill from corner, shows "1 S8" scribe on unhealed blaze.

Set - Brass Cap at Cor. Mkd: County Surveyors Office T25S RLW  
(Set Rock Alongside) 1966 S 5 S 4  
S 8 S 9

New BT's: 16" Hemlock N. 80° W. 24.0 ft. mkd. T25S RLW S5 CS BT.  
17" R. Cedar S. 22° W. 56.5 ft. mkd. T25S RLW S 8 CS BT.  
14" Hemlock S. 70° E. 65.1 ft. mkd. T25S RLW S 9 CS BT.  
6" Hemlock N. 71½° E. 54.5 ft. mkd. S 4 CS BT.

Note - This corner lies on N.E. slope 15 ft. west of creek, course N.

104

¼ Corner to Sections 16 and 21.

Found - 1½" I.P., 30" long, loosely set for corner (unrecorded).

Orig. 6", now 9" Cedar, down & face burned, S. 4° W. 5.3 ft., fragmentary scribe & reverse.

Orig. 8", now 9" Cedar, down & face burned, N. 39° W. 9.9 ft., only axe marks found.

Set - Brass Cap at Cor. Mkd: County Surveyors Office T25S RLW  
(Reset I.P. Alongside) 1966 ¼ S 16  
S 21

New BT's: 60" D. Fir Stump N. 18° E. 47.8 ft. mkd. ¼ S16 CS BT.  
9" Cedar Snag N. 63° E. 21.3 ft. mkd. ¼ S16 CS BT.  
48" D. Fir Stump S. 82° W. 43.5 ft. mkd. ¼ S21 CS BT.

Note - This corner lies in large, cut-off area on top of small spur, sloping west, curving to S.W.

105

Section Corner to Sections 15 - 16 - 21 - 22.

Found - Orig. Corner Tree, prev. opened & shows frag. scribe marks on N.W. side, shows good scars on S.W.-S.E. & faint notches on E. Side.

9", now 15" Chinq., down & badly rotted, possible SE. Orig. BT., no scribe found.

(12", now 14" Hemlock, Alive, N. 83½° E. 29.0 ft. scribe visible on unhealed blaze.

Hosford (10", now 11" Hemlock, Alive, S. 73½° E. 18.3 ft. scribe visible.

Ren. #35 (12", now 15" Yew, alive, S. 13½° W. 14.7 ft., scribe visible.

(6", now 6" Yew, N. 34" W. 13.4 ft., Alive, scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyors Office T25S RLW  
1966 S 16 S 15  
S 21 S 22

Note - Corner lies on spur, course East.

106

¼ Corner to Sections 23 and 26.

Found - Orig. Basalt Stone 18"x16"x7" mkd. "¼" on N. face.

Orig. 10", now 13" Fir, N. 35° W. 3.3 ft. Alive, shows good scar. We do not open.

Orig. 18", now 22" Cedar, S. 30° W. 12.5 ft., now down & out of place. Shows "¼ SBT" on unhealed blaze. #130

Set - Brass Cap at Cor. Mkd: County Surveyors Office T25S RLW  
(Set Rock Alongside) 1966 ¼ S 23  
S 26

New BT's: 8" D. Fir N. 73° W. 23.6 ft. mkd. ¼ S 23 CS BT.

5" Cedar S. 12° W. 47.2 ft. mkd. ¼ S26 CS BT.

Note - This corner lies approx. 50 ft. East of N.W. Cor. of cut off unit.

VERNON "Ray" DIFRACY  
Jack Heritage & Elmer West  
November, 1966  
C. S. File No. 52/30

RE-RENEWED, SEE CORNER NO. 130