

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

118

$\frac{1}{4}$ Corner to Sections 6 and 7.
Found - 8" x 10" x 18" Basalt Stone mkd: "X" on top & $\frac{1}{4}$ " on N. face,
loosely set and leaning.
Orig. 10", now 26" Cedar N. 2° W. 23.1 ft., open & find "4" scribe
(Rescribed Cedar, $\frac{1}{4}$ " S6 CS BT".) & reverse. Alive.
No trace of S.W. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 1 W
(In place of Cor. Stone Office $\frac{1}{4}$ S 6
& reset Rock alongside) 1967 S 7
New BT's: 6" D. Fir N. 27° E. 14.2 ft. mkd. $\frac{1}{4}$ " S6 CS BT.
9" Hemlock S. 34° W. 19.1 ft. mkd. $\frac{1}{4}$ " S 7 CS BT.
Note - This corner lies 35 ft. W. of creek, course S. 30° W.

FOOK BY T. HOSTETTER 4/03 M 142-3 119

Section Corner to Sections 19 - 20 - 29 - 30.
Found - Orig. 7", now 9" Fir, now badly decayed stump, S. 51° W. 11.9 ft.,
find fragmentary scribe.
Orig. 7", now 9" Fir, badly decayed stump, N. 77° W. 9.9 ft.,
find "BT" scribe.
No trace of other Orig. BT's.
16" Fir N. 68 $\frac{1}{2}$ ° E. 12.2 ft., alive, healed blaze. See Ren. #11.
18" Fir S. 68 $\frac{1}{2}$ ° E. 8.1 ft. Alive, scribe visible on nearly healed blaze.
28" Fir S. 48° W. 32.5 ft. Alive with healed blaze.
22" Fir N. 44 $\frac{1}{2}$ ° W. 54.0 ft. Alive, healed blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 1 W
Office S 19 S 20
1967 S 30 S 29
Note - Did not find the rock called for. Corner lies on very steep,
northerly slope on spur.

120

Section Corner to Sections 21 - 22 - 27 - 28.
Found - 12" x 12" x 14" above ground, Basalt Stone mkd. "X" on top
& 2 notches on S. & 3 notches on E. sides.
Orig. 4", now 15" Hemlock S. 40° E. 23.1 ft., chopped open &
find "RLW" scribe. Alive.
Orig. 8" ?, now 14" Cedar, N29°E. 27.1 ft, prev. opened &
shows "T25S RLW S22 BT"., scribe. Alive.
Orig. 5", now 8" chinquapin, sawed stump, S. 44° W. 13.2 ft.,
possible reverse scribe.
No trace of N.W. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 1 W
(Set on S. side of Cor. Office S 21 S 22
Stone, 6" S. of "X") 1967 S 28 S 27
New BT's: 7" Hemlock S. 69° E. 17.9 ft. mkd. T25S RLW S27 CS BT.
7" Cedar S. 10° W. 16.6 ft. mkd. T25S RLW S28 CS BT.
14" Hemlock N. 51° W. 18.0 ft. mkd. T25S RLW S21 CS BT.
Orig. BT. to N.E. alive & in good condition, scribing O.E.

FOOK BY T. HOSTETTER 121

Section Corner to Sections 20 - 21 - 28 - 29.
Found - 6" x 10" x 12" above ground, Basalt Stone mkd. "X" on top &
4 notches on E. & 2 notches on S. sides at base of 10" D. Fir
on E. side, apparently held in place by roots.
Orig. 48", now 48" badly decayed Fir Snag, with "25 RLW S21"
scribe exposed on upper blaze, & scribe marks visible on lower
blaze, bears N. 44° E. 39.6 ft.
17" Laurel bears N. 70° W. 16.5 ft., record calls for 7" Arbutus,
N. 68° W. 15.8 ft. We do not open.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 25 S R 1 W
(4" south of "X" Office S 20 S 21
on Rock) 1967 S 29 S 28
New BT's: 6" D. Fir N. 40° W. 7.5 ft. mkd. T25S RLW S20 CS BT.
9" Laurel N. 2° E. 34.4 ft. mkd. T25S RLW S21 CS BT.
8" D. Fir S. 83° W. 13.1 ft. mkd. T25S RLW S29 CS BT.
11" D. Fir S. 59° E. 25.9 ft. mkd. T25S RLW S28 CS BT.
Note - Corner lies on steep W. slope.

Vernon "Ray" Tracy
Jack Heritage & E. West
May, 1967
C.S. File No. 52/30

re survey
SEE 1998/99 BLM
Pgs 20 687-90