

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

122

Sec. Corner to Sections 25 and 36, T25-2W.  
Found - Original Corner Tree, 6", now 17" Hemlock, showing faint scars.  
Orig. 30", now 48" Fir, S. 26° E. 20.5 ft. Alive, shows good scar.  
Orig. 6", now 8" Fir, S. 25° W. 42.9 ft. Alive, scribe marks visible on unhealed blaze.  
Orig. 6", now 10" Fir, N. 55° W. 17.8 ft. Alive, scribe marks visible on unhealed blaze.  
Orig. N.E. BT, gone.  
Set - 3/4" Iron Rod on W. side & at base of corner tree 1 ft. from center.  
New BT: 8" W. Fir S. 43° W. 29.3 ft. mkd. T25S R2W S36 CS BT.  
Note - This corner lies 175 ft. south of old scared man jeep road at cutting corner, logged to N.W.

#146  
SEE ALSO 1912-61  
C.S. 40/279  
WEYERHAEUSER  
SURVEY

RE-RENEWED, SEE CORNER NO. #154

123

1/4 Corner to Section 36 only, T25-2W.  
Found - Orig. 6", now 10" Hemlock, S. 55° W. 14.5 ft. Alive & chopped open showing "1/4 S36" scribe & unopened lower scar.  
Orig. 14" Fir, now down & badly decayed, S. 88° E. 14.5 ft., find edge of old axe face.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T 25 S R2W 1/4 S 36 R1W  
New BT's: 17" Hemlock S. 47° W. 35.7 ft. mkd. 1/4 S36 CS BT.  
8" Hemlock N. 46° W. 20/8 ft. mkd. 1/4 S36 CS BT.  
Note - This corner lies 50 ft. E. of creek, course S.

RE-RENEWED, SEE CORNER NO. #154

124

Closing Corner to Sec. 31, T25-1W. & Sec. 6, T26-1W.  
Found - Original Corner Stone 17"x14"x7" set in mound of stone & mkd. "CC" & 6 notches on N. & S.  
Orig. 24", now 33" Fir, N. 58° E. 41.6 ft., alive, shows good scar. Do not open.  
Orig. 6", now 21" Fir, S. 71° E. 29.7 ft., alive, shows good scar. Do not open. Rescribe "CC T26S R1W S6 CS BT".  
Set - Brass Cap in Mound of Stone Mkd: County Surveyor's Office, 1967  
R2W CC | S 31 T25S R1W  
S 6 T26S  
New BT: 10" D. Fir N. 37° E. 17.3 ft. mkd. CC T25S R1W S31 CS BT.  
Note - This corner lies approx. 100 ft. S. of creek, course S.E.

Vernon "Ray" Tracy  
Jack Heritage & E. West  
May, 1967  
C.S. File No. 52/30

MICROFILM TO HERE 10/67 May 31, 1967

125  
126

Section Corner for Secs. 26, 25, 35 and 36  
Found - Corner tree with iron rod at base and bearing tree as noted in Ren. No. 75 with one exception, the 14" D. Fir BT to the SW marked in 1966 is now down.  
New BT - 11" Hemlock, bears N.44°E., 42.2 ft. scribed "T25S R1W S25 CS BT".

Gary Langlitz  
P. Earle  
C.S. 56/49  
3/29/74

3/29/74

JAN 75

Sec. 7 & 18 Corner to Lots 16, 17, 5 and 4  
Found U.S. General Land Office Brass Cap Stamped 1957  
D. Fir 16" dia. bears N65°E., 31.2 ft. Tree Blazed and scribed "S7 L17 CS BT"  
D. Fir 11" dia. bears S30 1/2°W., 45.2 ft. Tree blazed and scribed "S 18 L5 CS BT"  
Mag. Dec. 20"E. 1/26/76

L.E. Monrean  
P.L. Earle  
J.H. Cook  
CS. 59/2  
1/26/76

127

Closing Corner For Secs. 24 and 25 only, T25-2.  
Found - A 1 1/2" I. Pipe with steel cap.  
A Fir, 32" now 38" stump bears S.78 1/2° W., 37.0 ft. to center & 35.7 ft. to face. (Rec. 35.9 ft.) Stump is scribed "T25S R2W S 25 P.S. 253 BT".  
Set - I removed iron pipe and steel cap & replace with a Brass cap at 1/4 Corner stamped: "Douglas County Surveyors Office"  
T 25 S  
R S 24 R  
2 S 25 S 30 1  
W W

L. E. Monrean  
K. Cheney  
Dougl. Co. Surveyors  
June 10, 1976  
C.S. 59/15

New BT - A 10" Hemlock bears S.50°W., 121.9 ft. double blazed & scribed "T25S R2W S25 CS BT"

6/10/76