

Douglas County Surveyor's Record of
Government Corners Renewed

T 25

T. S.

R 1


R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

131

Section Corner for Secs. 28, 27, 33 and 34.

Found - Marks on bed rock as follows:



139

A 17" Fir snag bears N.74°E., scribing visible on partly burned blaze, "T 2 S R S 2 BT"

A rock point bears S.65°W., 19.1 ft. (Rec. 25.7 ft.) No marks visible.

Bearing trees to the NW and SE are gone.

New Accessories: A point of rock bears S.65 1/2°W., 20.4 ft. marked "X B0" I chiseled the existing marks on the bed rock so they show better.

New BT's- A 12" D. Fir bears S.87°E., 90.0 ft. scribed "T25S R1W., S.34 CS BT" on a double blaze.

A 16" D. Fir bears N.36°E., 24.3 ft. scribed "T25S R1W S27 CS BT" on a double blaze.

A 11" D. Fir bears N.29°30'W., 37.1 ft. scribed "T25S R1W S28 CS BT" on a double blaze.

Placed BT signs on all trees.

Corner lies approx 1000 ft. south of end of new U.S. Plywood Road.

7/5/77

132

Section Corner For Secs. 1 and 2 and Secs. 35, 36 of T.24-1

Found - 1963 County Surveyors Office Brass cap and iron pipe separated and badly bent, below surface of cat trail.

Orig. 16" Fir now 26" snag bears N.14°E., 15.8 ft. Tree has well healed blaze.

A 10" Fir now dead bears S.30°E., 13.2 ft. (orig. Rec. S.10°E. 1963 renewal Rec. S.30°E.) Tree has partially opened blaze scribed "T25S R1W S1"

A 48" Pine stump bears S.15°W., 13.9 ft. Tree has well healed blaze.

A 10" now 16" Fir bears N.26°W., 20.5 ft. Tree has well healed blaze.

A 21" Fir stump bears S.55°W., 11.0 ft. Tree has partially healed blaze scribed "25S R1W S2 CS" visible. Ren. #53.

An 12" Incense cedar bears N.47°E., 24.1 ft. Tree has open blaze scribed "T24S R1W S36 CS BT"

Set - 30" x 1" iron pipe at section corner 22" deep. attached brass cap is stamped "Douglas County Surveyor" T24S S35 S36 S2 S1 R1W T25S

No trees to scribe in southerly quadrants.

8/11/77

133

1/4 section corner to section 35 only.

Found - A stone, 15" x 10" x 10" marked "X" on top, and 1/4 on the North face. Stone is firmly set in the ground.

Orig. 24" D. Fir, now 38" bears N. 35° E., 69.4 ft. (Record 96.4 ft.) with healed blaze.

Orig. 15" D. fir. now 41" bears N. 70° W., 13.5 ft. (Record, 14.52 ft.) with healed scar.

Placed county tag on both, which are alive and well.

Orig. 14" D. fir, now 41" bears S. 5° E., 22.8 ft. (Record, S. 6 1/2° E., 17.82 ft.) with healed car. (Scribing supposedly destroyed by Mensch in 1910) Placed County B.T. tag on tree.

Set - Brass Cap at Cor. mkd.

COUNTY SURVEYORS OFFICE

T 25 S R 1 W

1/4 S 35

ONLY

1977

Buried stone alongside cap. Corner lies 100' East of ridge top and old cat road.

1/4 Corner for Sec. 1 only, T26-1.

Found - A 26" Broken Fir stob bears S.50°E., 25.74 ft. Has a healed scar. Open & find scribing & reverse "S1BT".

A 33" Cedar, orig. 20", bears S.11°W., 29.7 ft. Has a healed scar. Cedar is alive & well. Placed County BT sign on both tree & stob.

No monument found. Apparently the corner stone has broken & rolled down hill.

Set - 2 1/2" Brass cap on a 1" I.P. set by reference to orig. BT's. Set in a mound of stone 4 ft. wide at base by 4 ft. high on down-hill side. Brass cap stamped County Surveyors Office T26S R1W 1/4 only S1 1977.

134

Dennis Gaylord, U.S. F.S.
Deputy, Doug. Co. Surveyors Office
Travis Worthen, witness
July 5, 1977
C.S. 59/38

Dennis Gaylord, U.S. F. S.
Deputy, Doug. Co. Surveyors Office
Travis Worthen, witness
Sept. 15, 1977
C.S. 59/40