

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25

T. S. R 1

R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

William Ruppert  
L.S. #866  
For: U.S. Forest  
Service  
November 1978  
C.S. 58/176

Closing Corner for Secs. 18 and 19 of T.25-1E.

Found - 2" I.P. with 2 1/2" 1927 GLO brass cap properly marked.  
30" Cedar snag, S.28°E., 6.4 ft.  
9" D. Fir snag, S.40°E., 27.7 ft. Ren. #77

New BT's- 15" D. Fir, blazed & scribed "T25S R1E S19 CC BT" with brass  
washer marked "LS 866" attached bears S.07°30'E., 31.3 ft.  
10" D. Fir, blazed and scribed "T25S R1E S18 CC BT" with brass  
washer marked "LS 866" attached N.77°00'E., 80.5 ft.

144

Witness corner (south) for Secs. 12 and 13 only.

Found - 39" D. Fir, N.87°06'W., 13.2 ft. with good scar Ren. #78  
33" D. Fir stump, S.25°04'W., 31.7 ft. scribing partially visible.  
11" Cedar, bears S.73°12'W., 39.9 ft. scribing partially visible.  
12" Pine, N.14°08'W., 107.9 ft. with good scar.  
Set - A 2" x 30" Galv. Steel pipe 24" into the ground and constructed  
a mound of stones around it. Brass cap marked T25S WC S12 S13  
R1W R1E P1S 866 1978.

145

Section Corner for Secs. 25 and 36 only, T.25-2

Found - 56" Fir, face grown over, bears S.26°E., 20.5 ft., Orig.  
17" Hemlock with visible scribe (down), Orig.  
8" Fir bears S.25°W., 42.9 ft. Orig.  
10" Fir bears S.43°W., 30.3 ft. Ren. #122  
10" Fir bears N.48°W., 20.5 ft.

All trees previously opened, scribes still visible.

Set - Brass Cap.

8/75

146

1-79  
Glenn Baughman  
For: Weyerhaeuser Co.  
in 1975 - Filed 6/79  
M 77 - 57

Center 1/4 for Sec. 30

Set - 2 1/2" x 30" Gal. I. Pipe with 3" dia. brass cap stamped:  
T25S R1W C 1/4 + S30 PLS 961 1979

From which:

A 8" Fir bears N.40 3/4°E., 13.3 ft. scribed C 1/4 S30 BT.  
A 8" Fir bears S.0 3/4°E., 12.3 ft. scribed C 1/4 S30 BT.

4/79

147

Larry J. Friar  
For: Umpqua National  
Forest  
April 1979  
M 70 - 70

Section corner for Secs. 15, 14, 22 and 23.

Found - A 1962 County brass cap properly marked. Ren. #94  
A burnt cedar stump bears N.87°E., 12.2 ft. size indeterminate.  
(orig.)  
A 25" cedar, now 45" rescribed "T25S R1W S23 CS BT" Ren. #41  
"BT" rescribed Ren. #94 bears S.79 1/2°E., 9.9 ft. (orig.)  
A 15" R. cedar, now 20" bears N.62°W., 29.0 ft. scribed "T25S  
R1W S15 CS" in partially healed blaze. Ren. #41  
A 5" Hemlock now 0" bears N.60°E., 85.9 ft. scribed "S14 CS BT".  
A 24" Fir stump, now 30", 6 ft. high bears S.40°W., 63.4 ft. scribe  
"T25S R1W S22 CS BT"  
A 3" Fir bears N.70°E., 20.2 ft. scribed "X BT". (unrecorded)  
A 6" Fir bears S.9°W., 56.3 ft. scribed "T25S R1W S22 BT" (unrec.)

200 ft. west of Rd. 25-1-25.

NO NEW ACCESSORIES SET

7/22/79

148

Karen Reed  
P. Earle  
Doug. Co. Surveyors  
Office  
July 22, 1979  
C.S. 60/34

Closing Corner for Secs. 6 and 7 only of T.25-1E.

Found - 1927 U.S. GLO brass cap, properly marked, on a 2" iron post  
firmly set, 10" above the ground. (C.S. Vol. 21 Pg. 9120)  
21" D. Fir, orig. with healed blaze, bears N.61 E., 6.6 ft.  
24" wind fallen D. Fir, orig., with healed blaze bears S.17 E.,  
49.5 ft.

New BT - a 17" D. Fir bears S.7 E., 42.7 ft. marked "T25S R1E S7 CC BT"  
on a double blaze with a brass washer stamped "LS 536" nailed  
into lower blaze.

9/80

149

Glenn Baughman  
For: U.S. Forest  
Service  
Sept. 1980  
C.S. 58/229