

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25

T. S.

R 1

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

150

1/4 Corner for Sec. 31 only of T.25-1E.

- Found - 1927 US GLO brass cap properly marked, laying on top of the ground. Monument was disturbed by two windthrown trees which pulled it out of the ground. See Ren. #70  
A 20" D. Fir, orig. BT, with healed blaze bears S.28°E., 29.0 ft.  
A 12" Windthrown D. Fir, with healed blaze bears N.41°E., 4.0 ft.  
Set - RESET the monument in its orig. position., 15" in the ground in a 3 ft. diam. mound of stone, 2 ft. high.  
New BT - A 26" D. Fir, bears N.62°E., 104.5 ft. marked "1/4 S31 BT" on a double blaze with a brass washer stamped "LS 536" nailed into lower blaze.

9/80

151

1/4 Corner for Sec. 36 only. (East)

- Found - 1966 County brass cap properly marked, on a 1" I.P. firmly set 15" above the ground. Ren. #69  
A 50" D. Fir stump, orig. BT, with scribe mark "4" visible bears N.80 1/2°W., 28.4 ft.  
A 8" D. Fir snag, with scribe marks "1/4 S36 CSBT" visible on an unhealed blaze bears S.89°W., 12.9 ft.  
A 24" Hemlock snag, with scribe marks, "1/4 S36 CSBT" visible on an unhealed blaze bears S.k8°W., 18.6 ft. (Rec. 16°W.)  
New BT's- A 10" Cedar, bears S.52°W., 33.8 ft. marked: "1/4 S36 BT" on a double blaze with a brass washer "LS 536" nailed into lower blaze.  
A 16" D. Fir, bears N.38°W., 61.3 ft. marked "1/4 S36 BT" on a double blaze with a brass washer "LS 536" nailed into lower blaze.

152

Section corner for Sec. 36; and Sec. 31 of T.25-1E. (Twp. corner)

- Found - 18" x 12" x 8" basalt stone with 6 notches in the north, south, east, and west faces. Stone was laying on top of the ground.  
A 62" D. Fir, orig. BT, with healed blaze bears S.36°E., 47.5 ft. (Scribe marks destroyed in 1927 resurvey).  
A 28" D. Fir, orig. BT., with healed blaze bears S.11 1/2°E., 30.0 ft. (Rec. 33.0 ft.) (Scribe marks destroyed in 1927 resurvey).  
A 45" D. Fir, orig. BT., with healed blaze bears N.54 1/2°W., 52.8'  
A 22" D. Fir, orig. BT., with healed blaze bears N.67 1/2°E., 56.8'  
A 24" Cedar (not of record) with healed blaze bears N.32°E., 30.1 ft.  
Set - At the corner point I SET a 2 1/2" x 30" iron pipe, 6" in the ground on bedrock in concrete, and in a 3 ft. diam. mound of stone, 3 ft. high with a 3" brass cap projecting 12" above the mound of stone and marked: T25S R1 W S36 R1E S31 T25 1/2S R1E S31 1980 LS 536".

9/80

153

Closing corner for Sec. 1 of T.26-1 and Sec. 31 of T.25 1/2-R1E.

- Found - 1928 US GLO brass cap on 3" I.P. firmly set 10" above the ground  
A 48" Fir stump, badly rotted with scribe marks "T2" visible bears S.31°W., 48.2 ft.  
A 30" D. Fir with healed blaze bears S.36°E., 72.6 ft. (Rec. S.38°E., 71.9ft.)  
A 16" Pine snag, with scribe marks visible on a partially healed blaze, bears S.64°W., 23.6 ft. Ren. #65  
New BT - A 20" D. Fir, bears S.16°W., 17.8 ft. marked "T 26 S R 1 W S 1 CG BT" on a double blaze with a brass washer stamped "LS 536" nailed into lower blaze.

9/80

154

1/4 Corner for Sec. 36 of T.25-2. (East)

- Found - No trace of Orig. Fir post, 1900.  
6" now 10" Hemlock scribing visible bears S.55°W., 14.5 ft. center measurement.  
1967 County brass cap. Ren. #123  
18" Hemlock, scribing visible bears S.47°W., 35.7 ft. center measurement. Ren. #123  
8" dead Hemlock, scribing visible bears N.46°W., 20.8 ft. center measurement.

Accessories added this date:

- 48" Fir, N.15°W., 17.8 ft. with W nail and plate  
48" Red cedar, S.51°W., 37.3 ft. with W nail and plate.

Note: CC corner for Sec. 31, T.25-1 and S. 6, T.26-1 is appx. 401' South and 2 ft. East.

Glenn Baughman LS 536  
For: U.S. Forest Service  
September, 1980  
C.S. 58/229

Glen Mc Chesney  
For: Weyerhaeuser Co.  
Labor Day, 1975  
(Filed 12/80)  
C.S. 58/8