Douglas County Surveyor's Record of Government Corners Renewed

T 25 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

159

Section Corner for Sections 3 and 4; and 33 & 34 of T.24-1

Found - County monument dated 1966 leaning at 45° angle but not displaced. Ren. #96. Straightned monument and placed stones at base.
Checked measurements to BTs, found OK.
Found all BTs per notes of County Surveyors Office, 1966, with the following exceptions:
Orig. 48" fir now a stump.
Two new bTs set by County, 1966, are Doug. fir; Orig. 6" fir is a hemlock.

No new accessories established. Corner is now in recent cut-over.

Thomas D. scherner
For: Woodstock Logging
June 19, 1989
C. S. 63/85

6/19/89

160

Witness Corner to Closing Corner of Secs. 30 and 31.

Found - 1¼" iron pipe 5" above ground with stone mound. Ren. No. 1
18" hemlock bears N.43°15'E., 18.8 ft' partial scribing visible.
28" cedar bears S.36°E., 32.0 ft. partial scribing visible.

Note: 34" cedar stump (Orig. CC BT) bears N.82°E., 74.0 ft. to face, partial scribing visible.
20" W. fir snag (orig. CC BT) bears S.76°45'E., 68.3 ft. to face, partial scribing visible.

Note: 34" cedar stump is a triple trunked tree stump, bearings and distance is the trunk stump most southwesterly (approx. 16" in diameter).

Set - 2" galv. iron pipe 30" in length 25" in the ground with a 3" brass cap in a 36" diam. rock mound, Cap marked:

T 25 S
R R
2 S 30 1
W S 25 |-----CC W
S 31
RLS 2268 1990

James Artman
LS No. 2268
For: USFS
1990
C.S. 63/124

1990

161

Closing Corner for Secs. 6 & 7 only, of T.25-1E.

Found - 2" I.P. with 1927 BLM brass cap, firmly set, projecting 9" above ground. Cap properly marked.
24" D.Fir stump bears N.61°E., 6.6 ft. with a healed blaze. (1927)
24" windfallen D.Fir bears S.17°E., 49.5 ft. with a healed blaze.
14" grand Fir bears S.7°E., 42.7 ft. with a healed blaze. Ren.149

New BT - 8" Grand Fir bears N.44°E., 56.6 ft. scribed "T25S R1E S6 BT"

All BTs have a 6" red band painted around the tree and the blazed face painted red. U.S.F.S. sign 54-3, BEARING TREE, and sign 54-9 LAND SURVEYING MONUMENT, are nailed to all bearing trees. All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown, and distance are measured to the root crown at the side and center of the tree. Bearing and distances were measured with a staff compass (dec. 20°E) and steel tape.

5/13/92

162

1/4 Corner for Sec. 7 only of T.25-1E

Found - 1" Iron pipe with 1927 GLO brass cap, firmly set, flush with the ground. Cap properly marked.
30" broken top D.Fir bears N.50°E., 47.5 ft. with a healed blaze. (Rec. N.49°E., 71 lks.) (1927 BT)
52" uprooted D.Fir bears S.46°E., 43.0 ft. with a burned blaze. (Rec. S.51°E., 65 lks.) (1927 BT)
42" D.Fir stump bears N.2°E., 14.0 ft. with scribe marks "1/4 S7 CS BT" visible. Ren. No. 84
48" D.Fir stump bears S.78°E., 27.2 ft. with scribe marks "1/4 S7 CS BT" visible. Ren. No. 84

New BT - 10" D.Fir bears S.59°E., 33.8 ft. scribed "1/4 S7 BT".

5/14/92

Kristian DeGroot, L.S. #1941
For: U.S.F.S.
May, 1992
C.S. File 63/138

181