

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 25                      T. S.    R 1                      R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97101

**163**

(Note-All BTs have a 6" red band painted around the tree & the blazed face painted red. U.S.F.S. sign 54-3 BEARING TREE & sign 54-9 LAND SURVEYING MONUMENT, are nailed to all BTs. All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze.

Kristian DeGroot, L.S. #1941  
 For: U.S.F.S. - April/May 1992  
 C.S. File 63/138

1/4 Corner for Sec. 12 only. (East)

Found - 1 1/4" I.P. with 1966 DCSO brass cap, firmly set, projecting 16" above the ground. Ren. No. 85

43" Fir bears N.60°E., 10.5 ft. with a healed blaze. (Rec. N.63°E. 18 lks.) 1896 BT.

21" Fir stump bears N.47°W., 35.0 ft. with a healed blaze. (Rec. N.49°W.) 1896 BT

36" Fir stump bears S.21°W., 42.4 ft. with scribe marks "12" visible. (Rec. 60 lks.) 1927 BT.

20" D.Fir bears N.78°E., 24.9 ft. with a healed blaze. 1927 BT.

1/2" steel tube with a 1" survey cap, bears S.58°E., 1.6 ft. Ren. No. 85

New BT - 9" D.Fir bears S.30°W., 59.9 ft. scribed "1/4 S12 BT".

5/14/92

**164**

Sec. Cor. for 25 and 36 only. (East)

Found - 2" I.P. with 1927 GLO brass cap, properly mkd. firmly set, projecting 20" above ground.

1896 BT, a 42" Pine stump bears N.23°W., 33.7 ft. with a healed blaze.

23" x 15 ft. tall Pine snag bears S.60°W., 106.5 ft. with a healed blaze. ( Rec.108.3 ft.) Ren. No. 72

23" D.Fir bears N.39°W., 42.9 ft. with a healed blaze. (Rec. 42 ft. Ren. No. 72

New BT - 6" D.Fir bears S.25°W., 31.9 ft. scribed "T25S R1W S36 BT".

4/27/92

**165**

Wit. Cor. for Secs. 12 & 13 only, (NE Cor. Sec. 13)

Found - 1966 DCSO brass cap on 1 1/4" I.P., firmly set, projecting 16" above the ground with a 2 1/2" properly mkd. cap. Ren. No. 79

12" Yew bears N.26°E., 39.0 ft. with scribe marks "WC CS BT" visible. Ren. No. 79

8" Yew bears N.85°E., 24.9 ft. with scribe marks "WC CS BT" visible. Ren. No. 79

1/2" steel tube with a 1" alum. cap is set flush with the south edge of the 1" BC/IP. Ren. No. 24

New BT - 6" D.Fir bears N.42°W/. 31.1 ft. scribed "T25S R1W WC S12 BT".

5/15/92

**166**

Section Corner for Secs. 1 and 12 only.

Found - 2" GLO 1927 Iron pipe, firmly set, projecting 9" above a 30" dia. mound of stone, with a 2 1/2" properly mkd. brass cap.

60" D.Fir stump bears S.48°W., 19.1 ft. with a healed blaze. (1896)

32" D.Fir stump bears N.71°W., 26.4 ft. with a healed blaze and a sheet metal cap over the stump. (1896 BT)

6" W.Fir bears N.59°W., 29.4 ft. with scribe marks visible. (Rec. Hemlock) 1966 BT. Ren. #81

14" W.Fir snag bears S.74°W., 61.6 ft. with scribe marks visible. 1966 BT.

New BT - 10" W.Fir bears S.23°W., 73.0 ft. scribed "T25S R1W S12 BT"

5/13/92

**167**

East 1/4 cor. sec. 12 only, T25S R2W

Found - 2 1/2" GLO brass cap on 1" iron post.

14" D.Fir broken stump, S.6°13'W., 13.8. No marks visible. (S.7°W., 13.2)

20" D.Fir, S.11°30'W., 17.5. Large healed face (Ren. #16 T25-2). (S.13°W., 17.7' from GLO monument)

29" D.Fir snag, N.51°42'W., 16.0' to center. 14.0 to "W" nail. Face healed. "W" nail in small low blaze (N.52°W., 16.4 to center. 14.2 to "W" nail)

20" I.Cedar, N.18°32'W., 32.5. Face healed. (N.20°W., 32.3)

**168**

West 1/4 Cor. sec. 7, only

Found - 1 3/4" unmarked stell cap on 1 1/4" iron post. (Ren. #8)

35" D.Fir stump, N.85°07'E., 33.2. Face healed. Face has been sawn with a large wedge taken out.

27" D.Fir, S.48°20'E., 12.0. Face Healed.

Steven Ness  
 For: Weyerhaeuser Co.  
 Oct. 1995  
 M 123-3 A & B