

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 S., R 2 W

T. S.

R. W. W. M.

Aug 17
1943

A Boyer
Geo Piper
Jerry.

C.S. File 3178

$\frac{1}{4}$ Sec Cor bet Secs 21 ^{Aug 28} Found decayed remains of O.B.T.
10" Map. + 30" Fir - found Orig (marked $\frac{1}{2}$ n. face) Rock ^{and set}
2 new B.T's 30" Fir N 87° E 19.7'
10" Maple S 13 $\frac{1}{2}$ ° E 35'

SEE CORNER NO. 28

1-28-48

SEC. COR. 10-11-14-15

Identified from all O. B. T. Set 1" iron pipe with brass cap
marked County Surveyor's Office, T 25 S, R 2 W, 10/11
15/14

RE-NEWED, SEE CORNER NO. 83

Remarked 14" Cedar, S 56° W 9.7 ft.

New B. T's 24" Cedar N 80° W 58.9 ft.

16" Fir, N 57° E 33.4 ft.

18" Cedar S 84° E 51.7 ft.

MARCH, 1967 - FOUND O.K. V.R.T.

2-5-48

SEC. COR. 14-15-22-23

Identified from O. B. T's., Set 4"x4"x60" Fir Post.

Remarked O. B. T.

18" Pine, N 46° E 6 lks.

24" Pine, N 35° W 18 lks.

Marked New B. T.

8" Hemlock S 83° E, 38.3 ft.

16" Pine, S 29° W, 18.4 ft.

SEE CORNER NO. 34

2-9-48

$\frac{1}{4}$ COR. 14-15

NOT IN RIGHT PLACE Refer to C.S. File No. 49/102 - 7-16-58

Set by proportional measurement, Set 1" x 30" I. P. 24" in ground.

Marked B. T.

16" Pine, N 75° E, 12.3 ft., mkd. $\frac{1}{4}$ S 14 C S B T.

12" Pine, S 51° W, 39.6 ft., mkd. $\frac{1}{4}$ S 15 C S B T.

SEE CORNER NO. 35

February 1948

$\frac{1}{4}$ COR. 16-15

Set 1" Iron pipe and brass cap mkd. $\frac{1}{4}$ S 15, S 16, Co. Surveyors
Office. Set from old B. T. and other local topog. evidence.

Marked New B. T.

10" Maple, N 49° E 44.5 ft.

14" Maple, West 52.8 ft.

SEE CORNER NO. 74

6-3-48

SEC. COR. 9-10-15-16

Found Rock Corner, identified from O. B. T's.

O. B. T. 60" Fir, N 44° E, 17 lks.

14" Fir, N 33° W, 40 lks.

New B.T. 30" Fir, S 5° W, 38.2 ft.

30" Fir, S 45° E, 50.0 ft.

$\frac{1}{4}$ SEC. COR. 10-15

Found rock corner, identified from O. B. T's.

Marked New B. T.

66" Fir, N 58° E 20.0 ft.

6" Fir, S 46° E, 37.6 ft.

$\frac{1}{4}$ SEC. COR. 16-21

Rock noted in official notes gone. Stump 20" Fir S 39° W 29 lks.
(17.1 ft.) with old scribe mks. S 21 visible. B. T. scar not chopped
out. O. B. T. N 46° E 33 lks (22 ft.) stump knocked out. Old
blaze badly burned. B.T. scar not chopped.

Set 1" x 36" iron pipe with brass cap in ground mkd. $\frac{1}{4}$ S 16/S 21. Mkd. New B T.

Co. Surveyor Office T 25 S, R 2 W, $\frac{1}{4}$ S 16/S 21. Mkd. New B T.

36" Fir, N 51 $\frac{1}{2}$ ° W 34.7 ft. $\frac{1}{4}$ S 16 C S B T.

24" Cedar S 34 $\frac{1}{2}$ ° W 223.5 ft. mkd. $\frac{1}{4}$ S 21 C S B T.

$\frac{1}{4}$ COR. BET. 12-13

Found O. B. T's.

15" Fir (now 20") N 34° E 19 lks.

26" Fir (now 30") S 54° W 17 lks.

Set $\frac{1}{4}$ x 30" iron rod for corner at intersection of distances

SEE CORNER NO. 78

These corners set by Ben. B. Irving, County Surveyor and A. R. Evans, Deputy.
with Witnesses Milo Godfrey, Les Kershner, J.I. Clinton

A. R. Evans
Surveyor
B.B. Irving) Witness
M. E Godfrey)
C.S. File 43/158

Sept. 1949

C.S. File 39/169

M 12 - 34