

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 S T. S. R 2 W R. W. W. M.

East $\frac{1}{4}$ Cor. of Sec. 25, T 25 S, R 2 W. At this point I set a $1\frac{1}{2}$ " I.P. with steel cap from which: 10

A Fir 24" in dia. bears S $11\frac{1}{2}^\circ$ W 58.6 ft. marked T 25 S, R 2 W,
 $\frac{1}{4}$ S 25 P.S. 253, BT

A Fir 24" in dia. bears N $55\frac{1}{2}^\circ$ W 37.7 ft. marked T 25 S, R 2 W,
 $\frac{1}{4}$ S 25 P.S. 253 BT

Cor. 24 - 25 - 30, T 25 S, R 2 W.

At this point I set a $1\frac{1}{2}$ " I.P. with steel cap, from which: 11

A Fir 32" in dia. bears S $78\frac{3}{4}^\circ$ W 35.9 ft. marked T 25 S, R 2 W,
S 25 P.S. 253 BT

A Fir 30" in dia. bears N 39° W 16.4 ft. marked T 25 S, R 2 W,
S 24 P.S. 253 BT

East $\frac{1}{4}$ Cor. Sec. 24, T 25 S, R 2 W

At this point I set a $1\frac{1}{2}$ " I.P. with steel cap from which: 12

A Fir 32" in dia. bears S 57° W 14.6 ft. marked T 25 S, R 2 W
 $\frac{1}{4}$ S 24, P.S. 253 BT

A Fir 24" in dia. bears N 27° W 19.0 ft. marked T 25 S, R 2 W
 $\frac{1}{4}$ S 24, P.S. 253 BT

Cor. Secs. 24 - 13 - 19, T 25 S, R 2 W

At this point I set a 2" I.P. with steel cap from which: 13

A Hemlock 10" in dia. bears S $58\frac{1}{2}^\circ$ W 12.0 ft. marked T 25 S,
R 2 W, S 24, P.S. 253 BT

A Fir 30" in dia. bears N 36° W 21.2 ft. marked T 25 S, R 2 W,
S 13, P.S. 253 BT

East $\frac{1}{4}$ Cor. Sec. 13, T 25 S, R 2 W

At this point I set a 2" I.P. with steel cap from which: 14

A Yew 8" in dia. bears N 65° W 20.0 ft. marked T 25 S, R 2 W,
 $\frac{1}{4}$ S 13 P.S. 253 BT

A Cedar 8" in dia. bears N 18° W 12.2 ft. marked T 25 S, R 2 W,
 $\frac{1}{4}$ S 13 P.S. 253 BT

Cor. Secs. 13 - 12 - 18, T 25 S, R 2 W

At this point I set a 1" I.P. with steel cap from which: 15

A Fir 22" in dia. bears S $51\frac{1}{2}^\circ$ W 25.5 ft. marked T 25 S, R 2 W
S 13 P.S. 253 BT

A Cedar 30" in dia. bears N 73° W 35.0 ft. marked T 25 S, R 2 W
S 12 P.S. 253 BT

FD. OK 9/23/76 L. MURPHY C.S. OFFICE C.S. #59/24

East $\frac{1}{4}$ Cor. Sec. 12, T 25 S, R 2 W.

At this point I set a 2" I.P. with steel cap from which: 16

A Fir 12" in dia. bears S 23° W 91.4 ft. marked T 25 S, R 2 W,
 $\frac{1}{4}$ S 12 P.S. 253 BT

A Fir 18" in dia. bears N 35° W 21.0 ft. marked T 25 S, R 2 W,
 $\frac{1}{4}$ S 12 P.S. 253 BT

SEE ALSO WEYERHAEUSER NOTES. C.S. 59/11

Cor. Secs. 12 - 1 - 7, T 25 S, R 2 W.

At this point I set a 2" I.P. with steel cap, from which: 17

A Pine 16" in dia. bears S 15° W 17.4 ft. marked T 25 S, R 2 W
S 12 P.S. 253 BT

A Fir 42" in dia. bears N $54\frac{1}{2}^\circ$ W 42.6 ft. marked T 25 S, R 2 W
S 1 P.S. 253 BT

East $\frac{1}{4}$ Cor. Sec. 1

At this point I set a 1" I.P. with steel cap from which: 18

A Hemlock 14" in dia. bears S 84° W 14.2 ft. marked T 25 S, R 2 W
 $\frac{1}{4}$ S 1 P.S. 253 BT

A Hemlock 20" in dia. bears N $28\frac{1}{2}^\circ$ W 36.4 ft. marked T 25 S, R 2 W
 $\frac{1}{4}$ S, 1 P.S. 253 BT

Closing Cor. T 25 S, R's 1 & 2 W

Set a 2" I.P. with steel cap for the closing corner from which: 19

A Fir 22" in dia. bears S 30° E 20.2 ft. marked T 25 S, R 1 W
S 6 C.C. P.S. 253 BT

A Fir 24" in dia. bears S 35° W 8.7 ft. marked T 25 S, R 2 W
S 1 C.C. P.S. 253 BT

RE-REVIEWED SEE CORNER NO. 79

V. W. Hosford - Surveyor
May, 1949 - October, 1950
C.S. File 40/279