

Douglas County Surveyor's Record of  
Government Corners Renewed

25 T. S. 2 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97196

The B. T.'s for Sections 21 & 16 are gone.

At the true point of the corner I drove a  $1\frac{1}{2}$ " iron pipe 36" long 20" in the ground, from which:

- A Hemlock 8" in diam. bears N.  $28\frac{1}{2}^{\circ}$ E. 25.2 ft. marked S 15 253 B.T.
- A Hemlock 20" in diam. bears S.  $45^{\circ}$ E. 26 links(orig. BT not re-marked)
- A Hemlock 12" in diam. bears S.  $21^{\circ}$ W. 87.4 ft. marked S 21. 253 B.T.
- A Cedar 10" in diam. bears N.  $43^{\circ}$ W. 14.2 ft. marked S 16 253 B.T.

C. S. File  
No. 42/308

Section Corner to Sections 20, 21, 28, & 29.

After logging in Sections 21 & 29 I was unable to find the original marked stone corner. The N. E. B. T. is living. This tree is a White Fir, now 18" in diam. The S. E. B. T. is living, now 24" in diam. The S.W. B.T. is a stump with scribing visible. The N.W. B.T. is dead and shows an overgrown scar.

At the true point of the corner, I drove a  $1\frac{1}{2}$ " iron pipe 36" long 24" in the ground, from which:

- A Hemlock 5" in diam. bears S.  $14^{\circ}$ W. 60.4 ft. marked S 29 253 B.T.
- A Cedar 20" in diam. bears N.  $89^{\circ}$ W. 33.2 ft. markd S 20 253 B.T.

V. W. Hosford  
Sept. 24, 1957  
C. S. File No. 42/308

$\frac{1}{4}$  Section Corner to Sections 21 & 28.

After logging in Section 21, I found the original marked stone corner in place. The original bearing tree for Section 21 is down & badly rotted. The original B.T. for Section 28 is a rotten stub showing an old face but with scribing rotted away. The County Surveyor's B.T. for Section 28 is living. I drove  $1\frac{1}{2}$ " iron pipe 36" long 18" in the ground on the West edge of the corner stone, from which:

- A Maple 12" in diam. bears S.  $13\frac{1}{2}^{\circ}$ E. 34.3 ft. (County Surveyor's B.T. not re-marked)
- A Hemlock 10" in diam. bears N.  $61^{\circ}$ W. 21.0 ft. marked  $\frac{1}{4}$  S 21 253 B.T.

V. W. Hosford, Surveyor  
Oct. 16 & 17, 1957  
C. S. File No. 42/308

$\frac{1}{4}$  Section Corner 11 & 12.

Before logging I found the original marked stone corner in place, and the arbutus bearing tree for Section 11 in good condition. The Maple bearing tree for Section 12 was gone.

After logging in Section 11 and the N.  $\frac{1}{2}$  of Section 12, I was not able to find the corner stone. The Arbutus bearing tree has been broken down and badly burned and its original position lost.

I found old transit hubs on my random E. & W. center line of Sec. 12, which I had established in 1949. The terminus of this survey line was the  $\frac{1}{4}$  corner 11 & 12. From station 53 + 39.1 re-produced this line S.  $89^{\circ}02'$  W. 145.6 ft.; thence, N.  $12^{\circ}39'$  E. 15.1 ft. to the point of the original corner, where I drove a  $1\frac{1}{2}$ " iron pipe 36" long 24" in the ground, from which:

- A Fir 40" in diam. bears S.  $64\frac{1}{2}^{\circ}$ E. 23.7 ft. marked  $\frac{1}{4}$ S 12 253 B.T.
- An Incense Cedar 18" diam. bears S.  $71\frac{1}{2}^{\circ}$ W. 81.1 ft. marked  $\frac{1}{4}$ S 11 253 B. T.

Oct. 16, 1957

Section Corner Common to Sections 7, 8, 17, & 18.

After logging in Section 18, I found the original corner stone moved approximately two feet East from its original position. I did not re-set this stone. The original bearing tree for Section 8 is a dead snag. The original B.T. for Section 17 is entirely gone. The original B.T. for Section 18 is a stump with scribing visible. The original B. T. for Section 7 is in good condition.

At the true point of the corner, I drove a  $1\frac{1}{2}$ " iron pipe 36" long, 24" in the ground, from which;

- A Red Cedar 44" in diam. bears N.  $4^{\circ}$ E. 56.0 ft. marked S 8 253 B.T.
- A Fir 60" in diam. bears S.  $54^{\circ}$ E. 51.5 ft. marked S17 253 B.T.
- A Hemlock 22" in diam. bears S.  $32\frac{1}{2}^{\circ}$ W. 109.4 ft. marked S18 253 B.T.
- A Fir 48" in diam. bears N.  $64^{\circ}$ W. 56 links, original B.T.

Oct. 17, 1957

226

27

28

29

30

147