

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

By - G. Robert Lecklider
For - Evans Products Co.
August 1960
Map File M 19 - 40

Section Corner to Sections 27, 28, 33 and 34. 42
Found - Corner Stone - Mound Stone - West 3 feet.
Set - Steel Tube with survey cap
14" S. Pine N.88°E. 119.2 ft.
4" Fir N. 9°W. 22.4 ft.
12" Fir S.73°W. 47.1 ft.
12" Fir S.21°E. 52.8 ft.

----- 43
 $\frac{1}{4}$ Section Corner Sections 27 and 34.
Found - Corner Stone
9" Cedar N.53°W. 10.6 ft.
12" Cedar S.21°E. 5.3 ft. (Down)
Set - 16" Fir N.46°W. 30.8 ft.
22" Cedar West 11.5 ft.

----- 44
Section Corner to Sections 26, 27, 34 and 35.
Found - Corner Stone
10" Hem. N.15°E. 9.2 ft.
12" Hem. S.85°E. 17.2 ft.
10" Hem. S.22°W. 28.4 ft.
16" Hem. N.59°W. 23.1 ft.
Set - Steel Tube with Survey Cap
14" Hem. N.89°E. 33.6 ft.
10" Hem. N.52°W. 30.2 ft.
10" Hem. S.72°W. 29.0 ft.
12" Hem. S.45°E. 30.0 ft.

----- 45
 $\frac{1}{4}$ Section Corner to Section 34 and 35.
Set by Proportionate Measurement.
Set - Steel Tube with Survey Cap
18" Fir N.35°W. 35.5 ft.
18" Fir S.23°W. 13.6 ft.
28" Fir S.32°E. 59.3 ft.

----- 46
Center $\frac{1}{4}$ Corner Section 34.
Set - Steel Tube with Survey Cap.
14" Fir N.63°E. 24.8 ft.
24" Fir N.73°W. 1.9 ft.

----- 47
 $\frac{1}{4}$ Section Corner to Sections 33 and 34.
Found - Corner Stone
46" Fir N.62°E. 52.8 ft.
20" Fir S.52°W. 33.0 ft.
Set - 14" Fir N.20°W. 14.5 ft.
14" Fir S.44°E. 14.2 ft.

----- 48
C. C. Section 33 and 34.
Found - Corner Stone Mound Stone - North - 3 feet.
Set - Steel Tube with Survey Cap
16" Fir N.12°E. 17.4 ft.
12" Fir N.15°W. 10.5 ft.

----- 49
 $\frac{1}{4}$ Corner Section 34.
Set - Steel Tube with Survey Cap
40" Fir N.86°E. 114.3 ft.
8" Fir N.53°W. 33.0 ft.

----- 50
C. C. Section 34 and 35.
Set Record Distance from the Sec. Cor. 2 & 3, T26S, R2W.
Set - Steel Tube with Survey Cap
14" Fir N.45°W. 9.7 ft.
30" x 40" x 54" Boulder N.12°E. 6.6 feet
Mkd: " C BO" on South Face

RE-NEWED CORNER NO. 94