

**Douglas County Surveyor's Record of  
Government Corners Renewed**

25 T. S. 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

**51**

$\frac{1}{4}$  Corner common to Sections 32 and 33.  
Established at proportionate distance.  
A thorough search failed to reveal any evidence of the  
Orig. corner purported to have been established at this point by  
H. Johnson in 1900.  
At the true point of the  $\frac{1}{4}$  corner I drove a  $1\frac{1}{2}$ " I. P. 36" long,  
12" above the ground from which:  
28" Fir bears S.  $35\frac{1}{2}^{\circ}$  E. 30.6 ft. mkd.  $\frac{1}{4}$  S33 253 BT.  
14" Fir bears S.  $48\frac{1}{2}^{\circ}$  W. 12.6 ft. mkd.  $\frac{1}{4}$  S32 253 BT.

**52**

Closing Corner of Sections 32 and 33.  
From the corner of sections 33 on the line between Townships  
25 & 26 S., R.2W., which is  $5\frac{7}{14}$  a brass cap set by Cad. Eng.  
in 1959, I run S.  $89^{\circ}45'$  W. on the S. boundary of Section 33.  
At 408.6 ft., I established the C. C. of Secs. 32 & 33,  
T.25S., R.2W. At this point I could find no evidence of the  
corner Johnson describes in his notes of 1900. At the true  
point of the Closing Corner I drove a  $1\frac{1}{2}$ " iron pipe 36" long,  
12" above ground, from which:  
10" Hemlock bears N.  $47\frac{1}{2}^{\circ}$  E. 11.4 ft. mkd. T25S C.C. S33 253 BT.  
16" Hemlock bears N.  $14\frac{1}{4}^{\circ}$  W. 45.2 ft. mkd. R2W C. C. S32 253 BT.

**53**

South  $\frac{1}{4}$  Corner of Section 32.  
From the brass cap which marks the north  $\frac{1}{4}$  corner of Sec. 5  
T.26S., R.2W., I run S.  $89^{\circ}55'$  W. on the south boundary of Sec. 32.  
At 451.2 ft. I drove a  $1\frac{1}{2}$ " iron pipe 36" long, 12" above the  
ground, from the south  $\frac{1}{4}$  corner of section 32, T.25S., R.2W.  
from which: 8" Madrone bears N.  $70\frac{1}{2}^{\circ}$  W. 11.4 ft. mkd. S.  $\frac{1}{4}$  S. 32253 BT (in bark)  
8" Madrone Bears N.  $4^{\circ}$  W. 12.5 ft. mkd. S.  $\frac{1}{4}$  S. 32 253 BT (in bark)

**54**

Closing Corner of Sections 31 and 32.  
I could find no evidence of the corner described in Johnson's  
survey of 1900. At the point of the corner I set a 4" fir post  
marked C.C. 31 and 32, from which:  
21" Cedar bears N.  $67^{\circ}$  E. 20.3 ft. mkd. C.C. S. 32 253 B.T.  
25" Cedar bears N.  $68^{\circ}$  W. 27.8 ft. marked C.C. S. 31 253 B.T.  
This corner is 20 ft. south of ridge top between Rock Creek  
and North Umpqua River.

**55**

Center  $\frac{1}{4}$  Corner of Section 32.  
Drove a  $1\frac{1}{2}$ " iron pipe 36" long, 12" above the ground, from which:  
20" Fir bears S.  $83\frac{1}{2}^{\circ}$  E. 25.0 ft. mkd. C.  $\frac{1}{4}$  S. 32 253 B.T.  
14" Hemlock N.  $57^{\circ}$  W. 5.4 ft. mkd. C.  $\frac{1}{4}$  S. 32 253 B.T.

**56**

$\frac{1}{4}$  Corner common to Sections 31 and 32.  
At this corner, I found the original marked stone, displaced  
by logging. At the true point of the corner, I drove a hub  
and placed the marked stone beside it. Both Original  
bearing trees are living. The fir is now 18" in diam.  
The Pine is now 50".

**57**

62

Closing Corner for Sections 18 and 19.  
Found - Iron Pipe with Brass Cap Mkd: U.S. General Land  
Office Survey 1942

R3W	S 24	S18	T25S C.
		S19	R2W C.

13" R. Cedar N.  $70^{\circ}$  E. 18.6 ft. scribing visible  
on still open scar.  
54" D. Fir S.  $70^{\circ}$  E. 35.6 ft., shows good scars.  
New BT's: 14" Hemlock S.  $28^{\circ}$  E. 55.2 ft. Mkd: T25SR2W CC S19 CS BT.  
8" Hemlock S.  $82\frac{1}{2}^{\circ}$  W. 20.8 ft. Mkd: T25SR3W S24 CS BT.

V. W. Hosford  
For Evans Products Company  
Feb. until Oct. 1960  
C. S. File No. 51/144

Map File M 19 - 77

Milo E. Godfrey, Deputy  
Vernon Tracy  
Clete Putnam  
June 6, 1962  
C.S. 49/102

RE-RENEWED, SEE CORNER