

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25

T. S.

R 2

R. W. W. M.

HOKES-CHAPMAN CO., EUGENE, ORE. 21881

119

(Cont. from prev. pg.)

(1/4 Cor. for Secs. 20 and 29)

New BTs - 5" D. fir double blazed and scribed "1/4 S29 CS BT" bears S.25°W.  
28.9 ft.

8" D. fir double blazed and scribed "1/4 S29 CS BT" bears S.86°W.  
22.7 ft.

5" D. fir double blazed and scribed "1/4 S20 CS BT" bears  
N.18½°E., 23.7 ft.

8" chinquipin double blazed and scribed "1/4 S20 CS BT" bears  
N.75°E., 28.9 ft.

Corner lies near top of a rock bluff.

Douglas County  
Surveyors Office  
R. Smith - S. Flause  
Feb. 25, 1986  
C.S. 62/31

120

1/4 Corner Section 30 and 29

Found - A 1962 BLM brass cap 3¼" dia. on a 2½" I.P. firmly set flush with  
ground.

Possible original stone evident 2" below ground surface at NW  
edge of BC monument. We do not disturb monument to examine stone.

Orig. BT, a 11" now 28" dia. 50 ft. high W. fir snag, we opened  
and found scribing "BT" bears S.72½°E., 34.3 ft. (agrees well  
with 1962 BLM rec.; orig. rec. S.68°E., 31.7 ft.)

30" now 42" dia. 2 ft. high D. fir stump with evidence of a partial  
lower blaze no scribing found., bears N.55°W., 83.5 ft. (agrees  
with orig. Brg, dist. agrees with 1962 BLM resurvey, Orig.  
Rec. N.55°W., 84.5 ft.)

1962 BT, a 15" now 24" dia. 1/2 ft. high D. fir stump with a  
fully healed lower blaze, bears N.15°W., 33.0 ft. (agrees with  
record)

New BTs - A double trunked O. Ash, double blazed and scribed on 11" North  
trunk "1/4 S29 CS BT" bears S.03°E., 14.5 ft.

10" dia. R. Cedar double blazed and scribed "1/4 S30 CS BT" bears  
N.11°W., 34.9 ft.

10" dia. Maple double blazed and scribed "1/4 S30 CS BT" bears  
S.89°W., 13.6 ft.

Corner lies at North edge flat valley bottom.

Douglas County  
Surveyors Office  
Randall Smith  
Stephen J. Flause  
Feb. 25, 1986  
C.S. 62/31

121

Closing Corner for Secs. 3 and 4 only of T.26-2

Found - 1959 BLM 3½" brass cap on a 2½" iron pipe extends 4" above  
ground. Also found basalt stone alongside monument.

24" D. fir stump bears S.14¼°W., 35.3 ft. Face cut off (1959)

New BT - 15" D. fir bears S.55°E., 13.2 ft. scribed "T26S R2W S3 CC BT".  
6/30/87

Ronald Geisler  
For: Champion Int'l.  
Crew: Lynn Sibley  
Dean Turner  
June 30, 1097  
C.S. 63/60

122

1/4 Corner for Sections 17 and 18

Found - Original stone, firmly set measuring 6" x 8" on top and  
protruding 7" above ground. Orig. stone is clearly marked  
"1/4" on west side. (When removed stone measured 18" long)  
40" now 49" dia. D. fir with a fully healed double blaze and  
axed marks on bark "X" bears S.75°E., 4.5 ft. (Rec. S.75°E.,  
2.0 ft. possible face measurement) Orig. BT.

20" now 32" dia. 2 ft. high cedar stump, with a lower healed  
blaze; stump has a rotted out center with an axe mark at  
bottom of blaze. No scribing found. Bears N.71½°W., 35.0 ft.  
(Orig. rec. N.65°W., 35.0 ft.) Orig. BT.

Set - Orig. stone is referenced and a 8¼" long boat spike with a  
1¼" dia. head stamped "DCSO 1/4 1989" is set at reference positio  
15" below ground.

A 2 3/8" dia. brass cap on a 1 3/8" O.D. by 32" long I.P. is set  
over boat spike at referenced position and protrudes 13" above  
ground. Original stone is set along east edge of BC/IP with  
side mkd. "1/4" facing west, stone protrudes 4" above ground.  
BC/IP and orig. stone are surrounded by a 2 ft. dia. mound  
of stone.

New BTs - 4" D. fir double blazed and scribed "X BT" bears S.44°W., 41.0 f  
3" D. fir double blazed and scribed "X BT" bears N.72½°W, 23.6 f

A double trunked cedar double blazed and scribed on 11" dia.  
East trunk "1/4 S17 CS BT" bears North 24.2 ft.

Corner lies in a north-south cut line near the west edge of a small bench.  
Trees to the east are targeted for harvest in near future.

Douglas County  
Surveyors  
Office  
Randall Smith  
Stephen Flause  
April 6, 1989  
C.S. 62/6263

4/6/89