

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

123

1/4 Corner for Sections 18 and 19
Found - A 1962 BLM 3 1/4" dia. brass cap on a 2 1/2" dia. iron pipe leaning
9" southwest of plumb. BC/IP is found 8" below ground.
Measurements taken to plumb position of BC/IP:
7" fir now broken stump and roots of indeterminable size hemlock
no scribing or blazes found, bears S.40°E., 8.6 ft. (agrees
with 1962 BLM record) Orig. BT.
(Northwest madrone gone, falls in cat road)
6" now 6" dia. 6 inches high rotted D. fir stump with healed over
axe marks found at bottom of lower blaze, no scribing, bears
N.2°E., 22.1 ft. (agrees with record) (1962 BLM BT)
15" now 18" dia. 1 1/2 ft. high hemlock stump, no blazes or
scribing found, bears S.20°E., 23.1 ft. (agrees with rec.)
(1962 BLM BT.)
35" dia. 4 ft. high cedar stump with "W" nail in west base.
One W. Co yellow tag with a bearing and dist. of S.81 1/2°W.,
30.6 ft. We measure N.81 1/2°E., 30.6 ft. (Not of record)
9" hemlock with a silver and a yellow tag. Silver tag with a
bearing and dist. of S.25°E., 1 ft; Yellow tag with a bearing
and dist. of N.18°E., 1.5 ft. We measure S.13°W., 1.8 ft.
(Not of record.)
Set - 1962 BLM BC/IP is returned to plumb position, now protrudes
2" above ground.
New BTs- A multi trunked madrone double blazed and scribed "X BT" on 4"
south trunk, bears N.2 1/2°E., 17.5 ft. (to root crown)
12" hemlock double blazed and scribed "1/4 S18 CS BT" bears
N.89 1/2°W., 25.7 ft.
9" hemlock double blazed and scribed "1/4 S19 CS BT" bears
S.13°W., 1.8 ft.

Douglas County
Surveyors office
Randall Smith
Stephen Flause
April 12, 1989
C.S. 62/63

Corner lies on an east-west cut line at south edge of cat road.

4/12/89

ADDENDUM TO ABOVE NOTES: Weyerhaeuser notes from 1982 submitted to this office for
record on June 20, 1989. Notes are attached to the above
field notes in C. S. File 62/63.

124

1/4 Corner for Sections 27 and 28
Found - A 1962 3 1/2" BLM brass cap on 2 1/2" dia. iron pipe protruding
10" above ground.
36" now 43" dia. D. fir with a fully healed single blaze, bears
S.42°E., 17.8 ft. (agrees w/rec) Orig. BT. (This BT to be cut
in future timber sale.)
18" now 18" dia. dead hemlock with a partially healed blaze,
scribing is visible "S28B" bears N.10°W., 16.5 ft. (Reccord
N.10°W., 15.8 ft.) 1962 BLM
New BTs - 3" dia. Hemlock double blazed and scribed "X BT" bears
S.46°W., 50.1 ft.
7" dia. R. Cedar double blazed and scribed "1/4 S27 CS BT"
bears N.15 3/4°E., 32.6 ft.
8" dia. R. Cedar double blazed and scribed "1/4 S27 CS BT"
bears N.69°E., 19.3 ft.

Randall Smith
Stephen Flause
Terrie Franssen
Aug. 16, 1990
C.S. 64/10

8/16/90

125

Section Corner for Secs. 22, 23, 26 and 27
Found - A 2 1/2" dia. 1958 DCSO brass cap on a 1 1/2" O.D. iron pipe, protruding
15" above ground. Ren. #36. BC/IP surrounded by loose stones,
no unnatural marks found.
60" now 48" dia. 5 ft. high pine stump with a healed blaze bears
N.37°E., 38.9 ft. (agrees w/orig. rec) Orig. BT.
30" now 26" dia. 4 ft. high D. fir stump with a healed double blaze
bears S.25°E., 21.1 ft. (agrees w/orig. rec.) Orig. BT.
26" now 39" dia. 2 ft. tall D. fir stump with a healed lower blaze
bears N.44°W., 37.4 ft. (Rec. N.44°W., 38.9 ft.) Orig. BT.
18" orig. southwest BT is gone.
4" now 9" dia. hemlock with a fully healed double blaze bears
S.80 1/2°W., 22.3 ft. (Rec. S.80 1/2°W. 1974 BLM and agrees with
Ren. No. 36 dist. of 22.3 ft.) Ren. No. 36
7" now 7" dia. down and out of position hemlock with scribing
visible on an unhealed blaze "T25S R2W S26 BT" a broken portion
of stump remains which bears S.53°E., 10.6 ft. 1975 BLM BT.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Terrie Franssen
Aug. 16, 1990
C.S. 64/10