

4" dia. D.Fir, double blazed and scribed "X BT", bears
Douglas County Surveyor's Record of
Government Corners Renewed

T 25 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

125

Cont. from prev. pg. New BTs - 10" dia. hemlock double blazed and scribed "T25S R2W S22 CS BT" bears N.43½°W., 8.1 ft.
Doug. Co. Surveyors Off. 11" dia. forked trunked hemlock blazed and scribed "T25S R2W S27 CS BT" on easterly main trunk bears S.18½°W., 24.4 ft.
R. Smith; S. Flause; Corner lies on a steep west slope approx. 60 ft. west of a gravel road.
T. Franssen
Aug. 16, 1990
C.S. 64/10 8/16/90

Greg Lang L.S. No. 2205 1/4 Corner for Sec's 10 and 15
For: Roseburg Res. & Found - 1962 brass cap See renewal no. 7.
R. McKenzie Fnd BTs- 72" fir bears approx N.68°E. 23.3 ft. healed blaze. (record NW per BLM resurvey; record NE per Ben Irving renewal)
Feb. 1992 now 14" fir bears approx S.3½°E., 39.3 ft. healed face.
-M 114 - 57 3/19/92

1/4 Corner for Section 36 only of T.25-3
Found - 2½" dia. GLO brass cap on a 1" O.D. Iron pipe, protrudes 1 ft. above ground. Ren. No. 65
9" now 9" dia. 2 ft. high rotted D.Fir stump, no blazes or scribing found, bears S.8½°W., 4.6 ft. (agrees w/rec) GLO 1943
Doug. Co. Surveyors Office 13" now 13" dia. down and rotted D.Fir, no blazes or scribing found, bears N.38°W., 5.9 ft. (agrees w/rec.) GLO 1943
Randall Smith, deputy 7" now 13" dia. 2 ft. high Hemlock stump with a fully healed double blaze, bears N.23°W., 22.4 ft. (agrees w/rec.) 1966 DCSO
Stephen Flause SW BT from 1966 DCSO renewal is gone.
Aug. 10, 1992 BLM 1972 BC/I (W ¼ S.31 of T25S R2W only) bears South
C.S. File 64/32 73.9 ft. (agrees w/rec.)
New BTs - 14" dia. D.Fir double blazed and scribed "1/4 S36 CS BT" bears S.2½°W., 39.1 ft.
12" dia. D.Fir double blazed and scribed "1/4 S36 CS BT" bears S.45½°W., 40.5 ft.
4" dia. Madrone bark scribed "1/4 S36 CS BT" bears S.53°W., 3.6 ft.
14" dia. Alder bark scribed "1/4 S36 CS BT" bears N.26½°W., 20.8'.
8/10/92

1/4 Corner for Section 31 only (West)
Found - 3¼" dia. BLM brass cap on a 2½" O.D. Iron pipe, protrudes 6" above ground. (1972 BLM) See Ren. No. 66
18" now 23" dia. D.Fir with a fully healed single blaze, bears N.53½°E., 68.0 ft. (agrees w/rec.) 1972 BLM
Doug. County Surveyors Office 10" now 14" dia. Hemlock with a fully healed single blaze bears S.60°E., 58.6 ft. (Rec. S.60°E., 60.1 ft. is a slope dist.)
Randall Smith, Deputy 1972 BLM
Stephen Flause GLO 1943 BC/IP (E 1/4 S36 T25S R3W only) bears North 73.9 ft. (agrees w/rec.)
Aug. 10, 1992
C.S. File 64/32
New BTs - 14" dia. D.Fir double blazed and scribed "1/4 S31 CS BT" bears N.1½°E., 2.4 ft.
8" dia. D.Fir double blazed and scribed "1/4 S31 CS BT" bears S.55½°E., 24.7 ft.
8/10/92

Section corner for 13 & 24 only (east side)
Monument Fd. - 2½" dia. Glo Brass cap on a 2" O.D. I.P. protrudes 7" above ground (1943).
Accessories Fd. -
24" now 34" dia. 6' high tipped out D.Fir stump with a fully healed single blaze. estimated root wade bears S.57½°E., 17.8' (agrees w/ rec) OBT.
30" now 46" dia. 5' high D.Fir stump with a fully healed single blaze, bears S.17½°W., 17.5' (rec. S.17½°W 15.8', dist. could be a face measurement) OBT (stump is solid in good shape).
Doug. County Surveyors Office No other OBT's or 1943 ren BT are Found
Randall Smith, Deputy 13" now 14" dia. 6' high Hemlock stub with scribing visible on an unhealed open blaze "T25S R2W S18 CS" bears S.1°E., 36.8' (agrees with rec.) 1981 DCSO.
Stephen Flause 10" now 12" dia. 2' high Hemlock stub with scribing visible on an unhealed open blaze "S BT", bears N.87°W., 18' (agrees with rec.) 1981 DCSO.
Mar. 30, 1995
C.S. file 64/58-8 1981 DCSO Hemlock BT bearing N.45°W., 62' is now gone.