

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 25 S. T. S. R. 2 W. R. W. W. M.

FOXE-CHAPMAN CO., EUGENE, ORE. 97401

132

Cont.

New Mon. - BC/IP is returned to plumb position protrudes 3" above ground. marks on top of BC are orientated east.

New Accessories -

9" dia. Chinquapin, double blazed and scribed "T25S R2W S14 CS BT", bears N.80°E., 33.1'.

Boat spike through BT tag, top stamped "DCSO B01 1995" in top center 36" dia. 2' high pine stump boat spike, bears S.47½°W., 62.4'

133

Sec. 14 SW Cor.

Mon. Fd. - 2½" DCSO Brass cap on a 1½" Iron pipe leaning 9" NW of plumb. (marks on brass cap are orientated east)

Accessories Fd. -

8" now 26" dia, 45' high pine snag with a fully healed double blaze, bears N.38°E., 5' (rec. N.46°E., 4', dist could be a face meas.)

7" now 39" dia, 50' high pine snag with a previously opened burnt blaze, no scribing visible lower blaze is fully healed, bears N.35°W., 13' (rec N.35°W., 11.9', dist could be a face meas.)

No other orig BT's Found

8" now down and rotted hemlock of indeterminable size, roothole falls near rec bearing & dist. (rec S.83°E., 38.3')

16" now 22" dia, 6' high pine stump with a fully healed double blaze, bears S.29°W., 18.4'.

New Mon.- BC/IP is returned to plumb position, protrudes 3" above ground. Marks on top of BC are orientated east.

New Accessories -

9" dia, chinquapin, double blazed and scribed "T25SR2WS14CSBT", bears N.80°E., 33.1'.

Boat spike through BT tag, top Stamped "DCSO B01 1995", in top center 36" dia. 2' high pine stump. Boat spike, bears S.47½°W. 62.4'.

134

E ¼ sec. 24 of T25-3

Mon. Fd. - 2½" GLO Brass cap on a 1" OD Iron pipe, protrudes 1' above ground .

Accessories Fd. -

10" now 13" dia, 25' high maple snag, with a fully healed single blaze, bears N.16°W., 12' (rec. N.16°W., 11.2' dist possible face measurement) new sprouts growing from base.

16" now 24" dia, 2' high cedar stump, no blazes or scribing visible, bears S.48½°E., 17.8'.

50" now 50" dia, 2' high D.Fir stump, no blazes or scribing visible, bears S.79½°W., 27.1'.

36" now 36" dia, 6' high D.Fir stump, with a fully healed single blaze, bears N.15½°W., 32.3'.

New Accessories -

6" D.Fir, double blazed and scribed "¼ S24 CS BT", bears N.73°W., 26.3'.

4" Hemlock, double blazed and scribed "X BT", bears N.1½°W., 23.7'.

12" Hemlock, double blazed and scribed "¼ S24 CS BT" on a single 5' high blaze, bears S.79°W., 11.6' (lower trunk is scared).

135

W ¼ sec. 19

Found - 2½" dia GLO Brass cap on a 1" OD Iron Pipe, protrudes 11" above ground.

Accessories found -

32" now 36" dia, 2' high D.Fir stump, with a fully healed blaze, bears N.22°E., 36.3'.

30" now 33" dia, D.Fir, with a fully healed single blaze, bears S.23°E., 27.7' (rec. S.21°E., 27.7').

6" now 11" dia, Hemlock, with a fully healed double blaze, bears N.88°E., 39.1' (rec. N.89°E., 39.1').

1966 DCSO SE BT now gone.

CONT. NEXT PAGE

Douglas County Surveyors Office
Randall Smith & Stephen Flause
Mar. 1995 - C.S. 64/58

Douglas County Surveyors Office
Randall Smith & Stephen Flause
Apr. 1995
C.S. 64/63