

Douglas County Surveyor's Record of
Government Corners Renewed

T.25 T. S. R.2 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 21881

135

(cont. from next page)

New Accessories -

10" Hemlock, single blazed and scribed "¼ S19 CS BT", on a low blaze, (note: upper trunk is scared) bears S.76°E., 18.3'.
4" dia, D.Fir, double blazed and scribed "X BT", bears S.76°E., 18.3'.

6'x4'x4' boulder 1' west of BC/IP

136

¼ COR. OF SEC. 16 & 21

MON FD. - 2½" DCSO Brass cap on a 1½" OD Iron pipe protrudes 7" above ground.

Note: Brass cap is orientated NE & is surrounded by a 2½' dia mound of stone.

Orig. stone laying on side, measures 20"x14"x8", with marks "¼" found, bears N.41°W., 1.2' from BC/IP. Brg. & Dist. taken to center of stone.

Accessories Fd. -

16" now 20" dia, 2½' high rotted D.Fir stump, with scribing visible "S21", bears S.39°E., 17.1'.

24" now 33" dia Cedar, with a unhealed blaze no scribing visible. We double blaze and rescribed "¼ S21 CS BT", bears S.34½°W., 223.5'.

22" now 35" dia R.Cedar, with a fully healed double blaze, bears N.57°E., 64.1'.

New Accessories -

10" dia D.Fir, double blazed and scribed "¼ S21 CS BT", bears S.41°W., 26.8'.

15" dia D.Fir, double blazed and scribed "¼ S16 CS BT", Bears N.29°E., 28.6'.

137

¼ COR. SEC. 7 & 18

MON. FD. - 3¼" DIA BLM Brass Cap on a 2½" OD Iron pipe is flush with top of a 2' dia. mound of stone.

One of the stones along north edge of Bc/Ip is firmly set vertically with evidence of marks on north face its top measures 6"x6". (orig. stone) we did not disturb to measure or check marks.

Accessories FD. -

14" now 28" dia, 7' high rotting hemlock stump, shows evidence of axe marks and healed blaze, bears S.13°W., 40.9'.

15" now 16" dia., 6' high hemlock stump, with a fully healed single blaze, bears N.50°W., 50.1' (stump has a galvanized metal cap on top).

New Accessories -

19" dia., D.Fir double blazed and scribed "¼ S18 CS BT", bears S.44°E., 3.7'.

4" dia., D.Fir double blazed and scribed "x BT" bears N.29°E., 8' to root crown (pistol butt).

6" dia., Chinquapin, double blazed and scribed "¼ S18 CS BT", bears S.88°E., 9.9'.

138

1/4 Cor. secs. 11 & 14

Found - 3¼" BLM brass cap on 2½" iron post.

38" D.Fir, stump, S.81°55'E., 26.3 to center, 24.94 to "W" nail. "W": nail is in small low blaze. (S.81°E., 24.8)

Remains of Hemlock windfall, S.67°04'W., 15.2. measure to root hole. (S.62°W. 17.2)

44" D.Fir, N.43°07'W., 7.5'. Small low blaze healed. (N.44°W., 6.1 to "W" nail)

24" W.R. Cedar, N.8°09'W., 7.2. No face visible. (N.4°W., 7.3)

11" W.R. Cedar, N.6°07'E., 22.9. Face healed. (N.8°E., 22.4)

Douglas County Surveyors Office
Randall Smith & Stephen Flause
April 1995 - C.S. 64/63

Steven Ness,
For Weyerhaeuser Co
Oct. 1995
M 123-3 A&B