

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25 S T. S. R 2 W R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Cor. Secs. 2 & 11

139

Found - 2 1/2" GLO brass cap on 1" iron post.

38" D.Fir stump, N.19°35'E., 32.0' to center 30.65 to "W" nail. No face visible. Bark has fallen off. "W" in small low blaze. (N.19°E., 30.4)

20" W.R. Cedar, S.37°37'E., 75.7. Face healed. (S. 37°E., 77.3)

25" G.Fir, N.32°25'W., 30.2. Face healed. (N.31 1/2°W., 30.0)

15" W.R. Cedar stump. N.14°43'W., 42.7. Cruiser's mark "KM". (No Rec.)

~~1/4 Cor. Secs. 10 & 11~~ E14 S11

140

Found - 1 3/4" iron pipe.

46" D.Fir stump, S.65°50'E., 25.4 to center, 23.32 to "W" nail. Face not healed. Scribing "253 BT" visible. (S.65°E., 23.2)

30" I.Cedar, S.71°15'W., 81.2. Face healed. (S.72°W., 81.10)

BTs mkd-11" D.Fir, S.7°16'W., 25.1 to center. 24.4 to "W" nail. Scribed "1/4 S11 BT"

10" D.Fir, N.66°05'W., 38.3 to center. 37.8 to "W" nail. Scribed "1/4 S11 BT"

East 1/4 cor. sec. 12 only

141

Found - 2 1/2" GLO brass cap on 1" iron post.

14" D.Fir broken stump, S.6°13'W., 13.8. No marks visible. (S.7°W., 13.2)

20" D.Fir, S.11°30'W., 17.5. Large healed face (Ren. #16). (S.13°W., 17.7' from GLO monument)

29" D.Fir snag, N.51°42'W., 16.0' to center. 14.0 to "W" nail. Face healed. "W" nail in small low blaze (Ren. #16). (N.52°W., 16.4 to center. 14.2 to "W" nail)

20" I.Cedar, N.18°32'W., 32.5. Face healed. (N.20°W., 32.3)

West 1/4 Cor. sec. 7, T25-1 only

142

Found - 1 3/4" unmarked stell cap on 1 1/4" iron post. (Ren. #8 T25-1)

35" D.Fir stump, N.85°07'E., 33.2. Face healed. Face has been sawn with a large wedge taken out.

27" D.Fir, S.48°20'E., 12.0. Face Healed.

Center 1/4 Cor. Sec. 11

143

Set - 2 3/4" brass cap cemented to the top of a 2"x42" iron pipe.

BTs - 11" D.Fir, N.4°38'W., 82.1 to center, 81.75 to "W" nail. Scribed, "C 1/4 S11 BT"

10" D.Fir, S.39°08'E., 31.5 to center, 31.02 to "W" nail. Scribed, "C 1/4 S11 BT"

10" D.Fir, S.8°16'W., 22.9 to center, 22.51 to "W" nail. Scribed, "C 1/4 S11 BT"

10" D.Fir, S.78°00'W., 14.9 to center, 14.16 to "W" nail. Scribed, "C 1/4 S11 BT"

Center 1/4 Cor. Sec. 12

144

Set - 2 3/4" brass cap cemented to the top of a 2"x42" iron pipe.

BTs - 32" D.Fir, N.25°54'E., 31.2 to center, 30.60 to "W" nail. Bark scribed, "C 1/4 S12 BT"

35" D.Fir, N.55°14'E., 19.6 to center, 18.75 to "W" nail. Bark scribed, "C 1/4 S12 BT"

8" D.Fir, S.21°44'E., 57.3 to center, 56.87 to "W" nail. Scribed, "C 1/4 S12 BT"

8" D.Fir, S.27°43'W., 33.8 to center, 33.45 to "W" nail. Scribed, "C 1/4 S12 BT"

Steven Ness, L.S. #811  
For: Weyerhaeuser Co.  
Oct. 1995  
M 123-3 A & B