

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 S T. S. R 2 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

145

1/4 Section Corner to Sections 15 & 22
Found - 3 1/4" dia. brass cap on a 2 1/2" O.D. iron pipe, protrudes 3" above ground. (1962 BLM)
1 1/2" I.D. iron pipe, protrudes 13" above ground, along NE'ly edge of BC/IP See renewal #33
A broken stone that measures 24" x 10" x 6". No marks found. Stone is along north edge of BC/IP. (orig. cor. stone)
Accessories Found -
30" now 29" dia. 15 ft. high Hemlock snag with scribing visible on an unhealed blaze "1/4 S22 53 BT", bears S.54 1/2°W., 21.8 ft. (agrees with rec.)
12" now 23" dia. 3 ft. high Hemlock stump, scribing Fd. "1/4 S1" and a healed blaze, bears N.39°W., 5.3 ft. (agrees with rec.)
8" now 10" dia. 25 ft. high Cedar snag with a rotted blaze, no scribing visible, bears S.15°E., 21.1 ft. (agrees with rec.) O.B.T.
New Accessories -
7" dia. Cedar, double blazed and scribed "1/4 S15 CS BT" bears N.42°W., 7.0 ft.
12" dia. D.Fir, double blazed and scribed "1/4 S22 CS BT" bears S.26 1/2°E., 11.6 ft.
5" dia. D.Fir, double blazed and scribed "1/4 S15 CS BT" bears S.38°W., 22.5 ft.

Douglas Co. Surveyor's Office
R. Smith; S. Flause
Sept. 26, 1996
C.S. File 65/9-19

CC sec. 6 & 7

146

Mon. Fd.- 2 1/2" brass cap on a 2" O.D. iron pipe protrudes 12" above ground.
New Accessories -
30" now 34" dia. 6' high D.Fir stump, with illegible scribing on a partially healed single blaze, bears N.50 3/4°, 15.2' (agrees with rec.) 1940 GLO.
32" now 36" dia. 5' high D.Fir stump, with scribing "T25S R2" visible on a partially healed single blaze, bears S.20 1/2°E., 13.9' (agrees with rec.) 1940 GLO.
(Area around corner is over grown with brush Brg's and dist's to 1966 DCSO BT's not checked.)
8" now 10" dia. Yew, with a partially healed double blaze, scribing visible "25S R2W S7 CC CS BT", (rec. S.63°E., 168.2') 1966.
12" now 26" dia. Hemlock, with illegible scribing visible on a partially healed double blaze, (rec. N.7°E., 222.3') 1966.
New Accessories -
10" dia. D.Fir, double blazed and scribed "T25S R2W S6 CC CS BT", bears N.66 1/2°E., 6.4'.
7" dia. D.Fir, double blazed and scribed "T25S R2W S7 CC CS BT", bears S.12 1/2°E., 36.3'.

see previous ren.#75

Cor. Secs. 7, 8, 17, & 18

147

Found - 3 1/4" BLM brass cap on 2 1/2" IP, protruding 2" above ground, set firmly, Steel post North 1.0 ft
53" Fir N.65°W. 38.3' to ctr. w/chopped-out blaze
23" Hemlock stump N.28°E. 137.0' to ctr. Painted
22" Hemlock stump S.76 1/2°E. 113.5' to ctr. Painted
New BTs - 8" D.Fir, N.62°E., 14.3 ft. to ctr. blazed & scribed "T25S R2W S8 BT"
8" D.Fir, S.71°E., 35.4 ft. to ctr. blazed & scribed "T25S R2W S17 BT"
9" D.Fir S.80°W., 12.3 ft. to ctr. Blazed & scribed "T25S R2W S18 BT"

Harvey Christensen -
1/1999 - C.S.
File 65/23-12

(Ren # 30)

Douglas County Surveyors Office
Randall Smith & Stephen Flause
Sept. 25, 1997 - C.S. 64/78-7