

Douglas County Surveyor's Record of
Government Corners Renewed

25 T.S. 2 R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORG. 21921

Harvey Christensen
1/1999
C.S. File 65/23-11

1/4 Corner Secs. 8 & 17 148

Found - 3 1/4" dia., BLM brass cap on 1 1/2" iron pipe, protruding 3" above ground level.
18" Hemlock stump, S.6°W., 12.9 ft. to ctr. with visible scribing.
19" Hemlock stump N.17°W., 24.9 ft., to ctr. with visible scribing
1 1/2" dia., IP protruding 1.0 ft. above ground. Set firmly in place, next to found corner brass cap monument.

New BTs - 5" D.Fir N.40°E., 11.8 ft. to ctr. Blazed at breast high & scribed "X" and low blaze scribed "BT"
5" D.Fir S.52°E., 40.0 ft. to ctr. Blazed at breast high & scribed "X" and low blaze scribed "BT"
5" D.Fir N.84°W., 28.1 ft. to ctr. Blaze & scribed at breast high "X" & low blazed & scribed "BT"
5" D.Fir S.78°W., 32.2 ft. to ctr. Blazed & scribe at breast high "X" & low blaze and scribed "BT"

(Ren #38)

Mark Smalley
Roseburg Forest
Products

1/4 Cor. Secs. 3 & 10 149

Referenced out

Found - 1951 GLO brass cap properly marked.
Maple cluster S.20 1/2°E., 8.6 good condition.
Fir stump N.14°W., 14.0 gone.

New BTs - 6" Fir N.48°W., 35.0 ft. scribe "S3 BT"
16" Fir S.48°E., 34.3 ft. scribe "S10 BT"
14" Fir N.79°E., 28.1 ft. scribe "S3 BT"

C.S. File 65/45-28 4/22/2003

Crew:
Bill Olson
&
Mike Fromdahl

Cor. Secs. 2, 3, 10, & 11 150

Found - 1951 GLO IPBC (properly marked)
51" Fir N.57°W., 40.3 healed.

New BTs - 6" Hemlock S.60°W., 8.1 scribed "S10 BT"
8" Hemlock S.27°E., 12.3 scribed "S11 BT"
10" Hemlock S.56°E., 20.1 scribed "S11 BT"

C.S. File 65/45-29 4/29/2003

Mark Smalley
For: Rsbg Forest
Products
5/2003
C.S. 65/48-6

1/4 Cor. Secs. 10 & 11 151

Found - 1962 Steel pipe & brass cap (properly marked)
17" Hemlock S.24 1/2°E., 23.1' no face.
40" Cedar S.64°E., 35.6' found face chopped into.
57" Fir stump N.52°W., 26.4' fd. face chopped into.

New - 15" Hemlock S.18°W., 11.6' scribed "1/4 S BT"