

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. ~~R. 3 W.~~ R. 3 W. ~~R. 3 W.~~ W. M.

Oct. 28-1941
A. Boyer Dep. Co. Surveyor
Wit.
Bill Crear
Wilbur Williams

Apr. 21-22-23-1940
A. Boyer Dep. Co. Surveyor
Wit.
Ted Shellabarger
Joe Murphy

A. Boyer D. C. S.
Wit.
Floyd Norris
Clint Bamber
June 1939

C.S. 35/38
Vol. 1 P. 80
C.S. 16/68

1
1/4 Cor. Bet. Secs. 33 & 4
Set corner from orig. Laurel S. 75° W. 66 Lks. and clump of
Laurels N. 55° E. 47 Lks.
Marked new trees
Fir 42" bears N. 21° W. 31.0 Ft.
Fir 36" " S. 55° E. 17.0 Ft.

2
Center of Sec. 4
Set 4"x4" Post from which
A Cedar 8" bears N. 55° E. 9.0 Ft.
A R. Fir 10" " S. 63° W. 9.5 Ft.

3
Cor. Secs. 3-4-33 & 34
Set Cor. from old original B. Ts. as follows
A Fir 30" bears N. 52° E. 10 Lks.
" " 8" " S. 50° E. 46 "
" " 36" " S. 5° W. 56 "
" " 24" " N. 40° W. 56 "
Marked new tree
A Fir 4" bears S. 31° E. 13.0 Ft.

4
1/4 Cor. Bet. Secs. 3 & 4
Set a Cedar post 6"x6" from which
A Fir 15" bears S. 73° E. 15.3 Ft.
" " 8" " N. 50° W. 25.0 Ft.

5
Cor. of Secs. 3-4-9-10
Set Cor. from 60" Fir Scribed by Oscar Edwards
Drove a 4"x4" Fir post from which I set new trees
A Maple 6" bears S. 41° E. 23.0 Ft.
A Fir 6" " S. 60° W. 23.6 Ft.
A " 5" " N. 45° W. 3.0 Ft.

6
1/4 Cor. Bet. Secs. 4 & 9
Set a 6"x6" Fir post from which
A Fir 6" bears N. 40° E. 4.0 Ft.
" " 5" " S. 82° W. 7.0 Ft.

7
1/4 COR BET. 4 and 5.
No evidence of orig. corner round (probably never set).
Set by prop distant bet. NE. and SE. Cors. of Section 5.
a/o letter of 6/16/39 from Jos. A. Ganong Cad. Engrs. Office.
Set 4"x4" Yew Post for corner from which:
36" Fir bears N. 45° W., 22 ft. Marked 1/4 S. 5 T 25 S. R 3 W.
C. S. B. T.
18" Fir bears S 26 1/2° E., 12 ft. Marked 1/4 S. 4 T. 25 S. R. 3 W.
C. S. B. T.

8
SEC. COR. 4, 5, 8 and 9
B. T. (S 10° E., 24 lks.) which is now laying on ground and
stump is still standing. Set 4" x 4" Laurel Post for Corner,
from which: - Fo. GLO Brass Cap - O.K. 8-19-66 LL
8" Fir bears N 60° W., 23.5 ft., mkd. S 5, T 25 S R 3 W
C. S. B. T.
10" Fir bears N. 31° E., 30.0 ft. on slope, Marked S 4
R 3 W C. S. B. T.
36" Fir Bears N. 81° E., 79.0 ft. on slope scribed marks
by some C. S. still show on blaze (no Record of this
tree).
24" Fir bears S. 39° E., 118.0 on slope, marked S 9 T 25 S
R 3 W C. S. B. T.

RE-RENEWED, SEE CORNER NO. 126

RE-RENEWED, SEE CORNER NO. 125

RE-RENEWED, SEE CORNER NO. 132

RE-RENEWED, SEE CORNER NO. 91

RE-RENEWED, SEE CORNER NO. 118

RE-RENEWED, SEE CORNER NO. 95

COR. RENEWALS # 1 THROUGH # 15 MADE PRIOR TO GOV'T RESURVEY OF TOWNSHIP.