

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 3 W. R. W. W. M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 21881

35

$\frac{1}{4}$  Corner to Sections 31 and 32.  
Found - 11" Fir, now stump, S.11°E. 63 lks., shows good scribing.  
18" Fir, now burnt stump, S.4°W. 109 lks., shows scribng.  
Brass Cap at Corner, GLO 1943.  
New BT's: 12" Oak S.24°E. 25.3 ft. Mkd:  $\frac{1}{4}$  S32 CS BT.  
5" Oak S.61°W. 28.2 ft. Mkd:  $\frac{1}{4}$  S31 CS BT.

July 15, 1965

Bruce R.  
Rogers, Deputy  
Wm. Stoffel &  
Mike Stone  
C. S. File  
No. 54/7

36

Sec. Cor. to Secs. 34 & 35, T25-3W. &  
Secs. 2 & 3, T26-3W.  
Found - 1943 US GLO Brass Cap set from Orig. NE. & SW. BT's.  
22" Fir Stub N.69°E. 23.1 ft., fair bark scrib. visible.  
36" Fir S.45°W. 6.6 ft., face healed over on  
42" Fir.  
10" I. Cedar N.20 $\frac{1}{2}$ °E. 29.7 ft., scribing visible.  
22" W. Fir Stub 8' high S.67°E. 27.1 ft. - Face.  
12" I. Cedar N.62 $\frac{1}{2}$ °W. 12.5 ft., scribing visible.  
New BT's: 46" Fir N. 1° E. 21.4 ft. "W" Nail & Plate added.  
24" x 8' White Fir Stub. S.67°E. 27.0 ft. "W" Nail &  
Plate added.  
42" Fir S.60°W. 5.7 ft. "W" Nail & Plate added.  
14" I. Cedar N.59°W. 12.1 ft. "W" Nail & Plate added.

37

$\frac{1}{4}$  Corner to Sec. 35, T25-3W. & Sec. 2, T26-3W.  
Found - 1943 Brass Cap set by Prop. Measurement.  
22" W. Fir N.22 $\frac{1}{2}$ °E. 23. lks. 15.2 ft., found scribing  
on down 26" White Fir.  
50" D. Fir S.51°W. 35.6 ft., now stump of recently  
felled 50" Fir Snag, part of scribed face visible.  
New BT's: 18" W. Fir N.20°E. 12.3 ft. "W" Nail & Plate added.  
38" Cedar N.52°W. 42.0 ft. "W" Nail & Plate added.  
50" Fir Stump S.51°W. 34.0 ft. " "(1943 BT)

38

$\frac{1}{4}$  Corner to Sec. 31, T25-3W. & Sec. 6, T26-3W.  
Found - Brass Cap set by GLO in 1943, mkd. " $\frac{1}{4}$  S31".  
Fir Stumps refered to in Ren. #24. S 6  
11" D. Fir S. 11° E. 12.8 ft. Alive. Face pitched over.  
Weddo not disturb.  
13" D. Fir N. 4° W. 17.4 ft. Dead. Burned, partial scribe  
visible.  
New BT: 8" D. Fir N. 86° W. 51.1 ft. mkd. " $\frac{1}{4}$  S31 CS BT."  
Note - Corner is 70 ft. North of E. - W. Fence and 20 ft. East  
of Creek, course South.

39

$\frac{1}{4}$  Corner to Sec. 33, T25-3 and Sec. 4, T26-3W.  
Found - 1943 GLO Brass Cap for Corner.  
Orig. 42" D. Fir S. 85° E. 114.2 ft. (face) prev. opened,  
face pitched over.  
12", now 18" D. Fir N. 52 $\frac{3}{4}$ ° W. 17.8 ft., shows very good scar.  
12", now 14" D. Fir S. 10 $\frac{3}{4}$ ° W. 10.6 ft., shows good scar,  
fence wire wrapped around BT & grown over.  
New BT: 9" D. Fir S. 51° W. 22.3 ft. Mkd:  $\frac{1}{4}$  S 4 CS BT.

40

Sec. Cor. to Secs. 32 & 33, T25-3 and Secs. 4 & 5, T26-3W.  
Found - 1943 GLO Brass Cap at & BT's; in E-W Fence 76 ft. W. of Fence Corner.  
Orig. 50" Fir N. 25° E. 15.8 ft., bark scribed, alive.  
Only rotted remnants left of other Orig. BT's.  
BT's. as recorded in Ren. #13, T25-3W, as follows:  
7", now 10" Yew N. 20° W. 17.8 ft. Alive, scribe visible  
on partially healed face.  
8", now 13" Yew N. 37 $\frac{1}{2}$ ° E. 35.6 ft. Alive, scribe visible.  
50" Fir Stump S. 76° E. 48.2 ft., scribe visible on face.  
8", now 11" Yew S. 62° W. 9.9 ft. Alive, scribe visible on  
partially healed face.  
New BT: 18" W. Fir S. 22° E. 44.6 ft. Mkd: T26S R3W S4 CS BT.

Weyerhaeuser Co.  
Glen McChesney, Land Agent  
March 10, 1964 - March 11, 1965  
C. S. File No. 53/115

Vernon "Ray" Tracy  
Mike Stone & J. Layne  
Feb. 1, 1966  
C. S. File No. 54/7