

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 3W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray" Tracy
Joe Brady & Jack Heritage
June and July 1966
C. S. File No. 54/27

75
Sec. Corner to Sections 22 - 23 - 26 - 27.
Found - 1943 GLO Brass Cap mkd. with steel fence post alongside.
Original BT's, now snags.
12", now 16" Hemlock S. 23° W. 15.8 ft., Alive, nearly healed blaze, we do not open.
12", now 16" Hemlock N. 21½° E. 13.2 ft., scribe visible on nearly healed blaze.
N.W. BT lying face down & SE. BT., now burned stump.
New BT's: 16" Hemlock N. 58° W. 42.9 ft. Mkd: T25S R3W S22 CS BT.
11" Hemlock S. 43½° E. 49.1 ft. Mkd: T25S R3W S26 CS BT.
Note - Corner lies on top of spur, sloping S. 61½° E.

76
Sec. Corner to Sections 26 - 27 - 34 - 35.
Found - 1943 GLO Brass Cap mkd.
Orig. 12" Dogwood N. 19° E. 23.8 ft., shows frag. scribe, alive.
Orig. 30" Fir, now snag, N. 45° W. 29.7 ft., not opened.
10", now 15" S. Pine N. 19½° E. 14.5 ft., alive, shows good scar.
48", now 57" Fir N. 82¼° W. 38.3 ft., alive, face pitched over.
SE & SW. BT's., now stumps.
New BT's: 10" Hemlock S. 7½° W. 39.8 ft. mkd: T25S R3W S34 CS BT.
14" Hemlock S. 51° E. 37.8 ft. Mkd: T25S R3W S35 CS BT.
Note - This corner lies in N.W. corner of cut off unit.

77
¼ Corner to Sections 34 and 35.
Found - 1943 GLO Brass Cap mkd.
11", now 12" Fir S. 35° E. 3.3 ft., now snag 12 ft. high, shows scribe on unhealed blaze.
22", now 34" Fir S. 88° W. 23.8 ft., shows good scar. Alive, we do not open.
Orig. N.E. BT. is now shattered stump, no scribe found.
New BT: 14" W. Fir S. 54° E. 31.9 ft. Mkd: ¼ S35 CS BT.
Note - This corner lies at S.E. corner of cut off unit & N. W. corner of cut off unit.

78
¼ Corner to Sections 35 and 36.
Found - 1943 GLO Brass Cap mkd.
48", now 51" I. Cedar N. 88½° W. 7.3 ft. scribe marks visible on nearly healed blaze. Alive.
30", now 37" S. Pine, now stump 40" high, S. 18½° E. 11.9 ft., shows scar.
New BT's: 10" D. Fir S. 18° E. 8.2 ft. mkd: ¼ S36 CS BT.
9" Chinqupin S. 63° W. 21.9 ft. Mkd: ¼ S35 CS BT.
Note - This corner lies on moderate N. E. slope on old cutting line, cut off to East.

79
¼ Corner to Sec. 35, T25-3W. & Sec. 2, T26-3W.
Found - 1943 GLO Brass Cap mkd.
50" D. Fir, now 50" Stump, S. 51° W. 35.6 ft., partial face visible, "W" nail added.
22", now 26" W. Fir N. 2½° E. 15.2 ft., down, face burned, no scribe found.
Weyerhaeuser BT's. as recorded in Ren. #37, as follows:
18" W. Fir N. 20° E. 12.9 ft. (center) "W" nail at base, we scribe ¼ S35 CS BT".
38" Cedar N. 52° W. 42.0 ft. (to "W" nail)
New BT: 6" Hemlock S. 25° W. 68.2 ft. Mkd: ¼ S 2 CS BT.
Note - This corner lies on E. - W. cutting line, cut off to south.

80
¼ Corner Section 1 only, T25-3W.
Found - GLO Brass Cap mkd. "¼ S1/1943", bent over. Straighten & Reset in Mound of Stone.
N.W. BT. gone, Stumps of SE & SW BT's. remain.
New BT: 12" Fir, snag 15' high, N. 73° W. 39.4 ft. mkd. ¼ S1 CS BT.
No live trees available. Corner lies on very steep, N. slope, 10 ft. N. of rock face 6.0 ft. high X 25.0 ft. long, course E. & W.