

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99

Section Corner to Sections 8 - 9 - 16 - 17.
Found - GLO Brass Cap mkd. 1944, with steel fence post set alongside.
Orig. 30", now 36" Fir S. 65° E. 21.8 ft. Alive, shows old scar. Do not open.
12", now 21" R. Cedar N. 50° E. 56.9 ft. shows scribe on partially healed blaze.
10", now 14" Fir S. 60° W. 67.3 ft., shows good scar. Do not open.
6", now 11" Red Cedar N. 29° W. 33.0 ft., healed blaze. Do not open,
Roots wrapped around old log.
New BT's: 26" R. Cedar S. 56° E. 22.0 ft. mkd. T25S R3W S16 CS BT.
9" Hemlock N. 37° W. 16.1 ft. mkd. T25S R3W S 8 CS BT.
Note - Corner lies on bench between small spurs.

100

¼ Corner to Sections 10 and 15.
Found - GLO Brass Cap mkd, 1943, with steel fence post set alongside.
54", now 60" Fir Stump N. 2½° E. 48.8 ft., shows "S" & partial scribe on nearly healed blaze.
14" Hemlock, now shattered stump, S. 89° E. 33.0 ft. No scribe found.
New BT's: 6" I. Cedar S. 85° E. 4.8 ft. mkd. ¼ S15 CS BT.
13" Hemlock N. 17° E. 41.7 ft. mkd. ¼ S10 CS BT.
Note - This corner lies on N.W. slope approx. 60 ft. E. of bence, course NE-SW in old logged unit with reprdctn. Fir, Hemlock, Cedar & Maple.

101

¼ Corner to Sections 10 and 11.
Found - GLO Brass Cap mkd., 1943, with steel fence post set alongside.
Orig. 60" Fir Stump S. 48° E. 5.3 ft. (recorded as S. 48° W.), shows "BT" scribe on burned face.
Orig. 30" Hemlock Stump N. 37° W. 13.2 ft., burned, no scribe found.
42", now 43" Fir S. 35° W. 34.3 ft., now burned stump, axe marks, no scribe fd.
New BT's: 5" D. Fir N. 65° W. 41.6 ft. mkd. ¼ S10 CS BT.
5" D. Fir N. 36° E. 28.3 ft. mkd. ¼ S11 CS BT.
Note - Corner lies on top of rounded spur, sloping south.

102

Sec. Corner to Sections 2 - 3 - 10 - 11.
Found - GLO Brass Cap mkd., 1943, with steel fence post set alongside.
Orig. 36" Fir, now shattered blow-down, lying face down, N. 55° E. 13.2 ft.
Orig. 48", now 50" Burned Fir Stump, S. 51° W. 7.9 ft., no scribe.
10", now 11" badly burned Fir Stump, S. 40° E. 23.8 ft., no scribe.
8", now 11" Fir, 6' high snag, N. 38° W. 19.8 ft., shows very good scar,
To preserve scribe, we do not open.
New BT: 3" Chinq. S. 7½° W. 40.7 ft. Mkd. S 10 CS BT. (Only available trees)
3" Laurel N. 84° E. 18.5 ft. mkd. S 2 CS BT.
Note - This corner lies on very sttep, N.W. slope of ridge, course West.

103

¼ Corner to Sections 3 and 10.
Found - GLO Brass Cap mkd., 1944,
40", now 40" Fir Stump, N. 37° E. 21.8 ft., shows "¼ S3 BT" on unhealed blaze. Norman Price calls this tree a CS. BT.
Orig. 24", now 25" Fir Stump, S. 10° E. 17.2 ft., shows "¼ S10 BT" on unhealed blaze.
New BT's: 5" D. Fir N. 68° E. 17.6 ft. mkd. ¼ S 3 CS BT.
5" Hemlock S. 30° E. 6.3 ft. mkd. ¼ S10 CS BT.
Note - This corner lies on fairly steep, south slope in heavy brush & reproduction of Fir, Hemlock & Cedar.

104

Section Corner to Sections 7 - 8 - 17 - 18.
Found - GLO Brass Cap, 1944.
36", now 50" I. Cedar N. 78° E. 141.2 ft., shows scribe on unhealed blaze. N. & NE side of tree badly burned. Tree Alive.
30", now 42" Fir, S. 42° E. 57.4 ft. Alive, blaze pitched over.
5" Madrone, now stub only, 6' high, S. 41° W. 2.0 ft.
24", now 28" Fir, turned out, face down, N. 61° W. 17.8 ft., blaze visible
New BT's: 10" Laurel N. 56° W. 26.6 ft. Mkd: T25S R3W S7 CS BT.
4" D. Fir S. 71½° W. 29.6 ft. mkd. S18 CS BT.
20" D. Fir N. 78° E. 12.7 ft. mkd. T25SR3W S8 CS BT.
Note - Corner lies on top of rocky spur, course S. 40° E.

Vernon "Ray" Tracy
Joe Brady & Jack Heritage
August, 1966
C. S. File No. 54/27