

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 25 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Cont. - - - - - 1/4 Corner for Secs. 28 and 29.

138

bearing S.83 1/2°E., 44.4 ft.
Scribed a 18" I. Cedar, bearing S.1°W., 78.4 ft. Tree has
a double blaze scribed "1/4 S29 CS BT"

We tag new B.O. stump and new tree with DCSO BT tags.

Note: Corner is now on the N-S edge of a reprod. unit. 5/7/80

Ed Monrean, Deputy
Doug. Co. Surveyor
Office.
T. Plouff; S. Flause
S. Means; K. Mosley
May 7, 1-80
C.S. 61/6

West 1/4 Corner for Section 34.

139

Found - Orig. 32" Fir, now a 34" tipped over stump, part of chopped
face remains. 1959 found bearing, S.24°E., 17.8 ft.

Orig. 5" vine maple, now clump, but no scribe marks remain.
Record N.60°W., 6.6 ft.

1943 GLO brass cap in original position.

14" now 20" Incense cedar, bears N.86°E., 27.7 ft. scribing
partly overgrown.

20" now 24" Fir stump, moved out of position by logging, now
S.61°W., 22.2 ft. (Rec. S.86 1/4°W., 37 lks.) Scribed face
removed with butt log.

"W" nails and plates referenced in 1959.

Accessories added this date:

48" Fir, N.47°E., 76.4 ft.

10/31/78

Glen Mc Chesney
For: Weyerhaeuser Co.
Oct. 31, 1978
(filed 12/80)
C.S. 58/8

Section corner for Secs. 13 and 24 only. (east)

140

Found - 1943 GLO brass cap, properly mkd., firmly set.

Orig. 24" now 38" Fir, alive with large pitched over scar,
bears S.55°E., 17.8 ft.

Orig. 30" now 47" Fir stump (7 ft. high) with well healed
scar, bears S.21°W., 17.2 ft. (rec. 15.8 ft. fits to face
fairly good)

Orig. 18" now 16" rotted fir snag (10 ft. tall) bears
N.38°W., 84.6 ft. (rec. 85.1 ft.) scribed "T25S R3W S13 BT"
visible on East side of tree.

9" now 12" Hemlock per 1943 resurvey, down with well healed
scar bears N.38 1/2°W., 12.5 ft. to root hole.

New BT's- 13" Hemlock bears S.1°E., 36.8 ft. scribed "T25S R2W S18 CS
BT" in double blaze.

10" Hemlock bears N.87°W., 18.0 ft. scribed "T25S R3W S13 CS
BT" in double blaze.

9" Hemlock bears N.45°W., 62.0 ft. scribed "T25S R3W S13 CS BT"
in double blaze.

Note - Corner lies in cut line west of Rock Rd. approx. 50 ft.

10/13/81

Gregory Quibell
Deputy, Douglas
Co. Surveyors
Office
Witnesses: Terrie
Plouff/ Teresa
Buley
Oct. 13, 1981
C.S. 61/29

1/4 Corner for Sections 19 and 30

141

Found - 1966 County brass cap, properly marked, firmly set protruding
12" out of ground. Ren. #67

20" hemlock now 22" and down with scribed "1/4 S19 BT" visible
on partially healed blaze bears N.22°E., 50.5 ft. to center
of root hole. (rec. 51.5 ft.)

11" fir now 15" stump with BT tag bears S.53°W., 11.9 ft.
(rec. S.51°W.)

16" fir now 22" stump with BT tag bears S.12°W., 19.8 ft. Ren. #67

New BT's- 12" cedar scribed "1/4 S19 CS BT" in double blaze bears N.89°E.,
25.0 ft.

9" maple scribed "1/4 S30 CS BT" in double blaze bears S.84°E.,
26.8 ft.

8" fir scribed "1/4 S30 CS BT" in double blaze bears S.26°W.,
48.0 ft.

6" maple scribed "1/4 S30 CS BT" in double blaze bears S.37°W.,
17.8 ft.

"X" in top of 54" corrugated steel culvert bears S.26°W.,
3.7 ft. and "1/4 cor. bears N.26 E. 3.7" is stamped next
to X.

Note: Due to closeness of metal culvert all bearings were taken from
the tree to the brass cap. (sketch in C.S. file)

3/1/82

Gregory Quibell
Deputy, Doug.
Co. Surveyors
Office
Witness: Terrie
Plouff
March 1, 1982
C.S. 61/30