

Douglas County Surveyor's Record of  
Government Corners Renewed

25 T. S. 4 R. W. W. M.

01

J. Cole Dep. Co. Sur.  
Wit- Robt. Hall  
J. L. Mohr  
A. V. Abeene.  
April 24, 1913  
F. B. 39, Page 30 to 33 inc.

Jan. 23, 1917  
M. B. Germond  
Wit. Thomas Harvey  
John Abeen  
R. H. Manning  
Cockran

Jan. 25, 1917  
M. B. Germond  
Wit. Thomas Harvey  
R. H. Manning  
John Abeene  
Roland Corkran  
F. B. 42, Page 20

June 8 to 16, 1927  
Ben B. Irving  
Wit. R. L. Irving  
R. A. Kent  
W. A. Finley  
C. 5. 37/147

1928  
Ben B. Irving  
Wit. Geo. Kolhagen  
McNeece

SW CORNER OF CL. 39

Renew corner from remains of original trees. Set from which:  
A Fir 30 ins. dia. brs. S.14°E., 194 lks.  
A Fir 34 ins. dia. brs. N.65½°W., 282 lks.

COR N. MARKHAM CL. 39 (W.S.W)

Renew Cor. from original trees. Set post from which:  
A W. Oak 5 in. dia. S.81½°W., 27 lks.  
A W. Oak 5 in. dia. N.64°E., 32 lks.

COR TO SECS. 15, 16, 21 and 22

Renew Cor. from remains of orig. trees. Set post from which:  
A W. Oak 4 ins. dia. S.45°E., 60 lks.  
A W. Oak 4 ins. dia. S.31°W., 53 lks.  
A B. Oak 6 ins. dia. N.36°W., 128 lks.  
A B. Oak 6 ins. dia. N.62½°E., 180 lks.

COR ON S. SIDE OF SEC. 22

Renew corner from remains of original B. T's. Set a post which:  
A Fir 12 ins. dia., bears N.23°W., 6 lks.  
A Fir 18 ins. dia., bears S.14°E., 31 lks.

CORNER TO SECTIONS 5-6-7-8.

Reset corner from original bearing trees. Set in S. Stone  
6"x8"x16" from which:  
W. Oak 30" dia. bears S.1°E., 368 lks. Orig. T. 84  
W. Oak 12" dia. bears S.69°55'W., 216 lks. Orig. T.  
W. Oak 15" dia. bears N.29°20'W., 118 lks. Orig. T.  
W. Oak 8" dia. bears N.46°E., 40½ lks.  
SW. Cor of D. L. C. # 48 brs. S.89°20'E., 4.75 chs.

I REEST. NE. COR CLAIM # 48

From one original tree. Set in S. Stone 4"x4"x14" from which:  
A W. Oak 4" in dia. brs. S.24½°W., 13 lks. 87  
A W. Oak 7" in dia. brs. S.17°E., 23 lks.

RESET NW. COR. CL. # 48

I intersected lines. Set in S. Stone 4"x14"x28" from which:  
A W. Oak 12" dia. brs. S.17½°W., 4.78 chs. 89  
A W. Oak 10" dia. brs. S.76°10'E., 3.66 chs.

SEC. CORNER BETWEEN SECS. 25 and 36.

This corner is a 12" Fir Tree with O. B. T's. as described  
in the original notes except the Fir S.40°E is 4 lks. dist.  
instead of 40 lks.

SECTION CORNER 26-25-35-36.

Identified this corner by means of all 4 original BTs. located  
as recorded in the original notes. Two of the old BT's were  
standing and in good shape but have been fire killed. I set  
a 4" seasoned Yew Wood post for the corner and replace the 2  
dead BTs by a  
10" Cedar S.10°E., 42.6 ft.  
10" Cedar S.60°W., 19 ft.

SEC. COR SO. SIDE SEC. 36

Identified position from Orig. BTs. one existing as snag  
bearing proper scribe marks and stump of OBT in location  
called for in orig. notes. Set a dead Oak Post 4"x4"x36"  
for corner scribed from which:  
A 36" Fir bears N.34°E., 275 lks.  
A 36" W. Oak bears N.20°W., 302 lks.

2-25-65- SEARCHED FOR, NOT FOUND V.R.T. LL.

2

3

4

5

6

7

8

9

10