

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
December 2, 1958
C.S. File No. 49/124

Renew Township Corner Twp. 24 & 25 S., R's. 4 & 5 W. 48
Found - Laurel Tree, now 30" diam., standing but dead. Chopped
open & found good scribing "BT" (N.41°E. 13.2 ft.)
Laurel Tree, standing & alive but rotted out inside,
now 40" diam. N.74°W. 207.9 ft.
Stump Hole S.22°E. 25.7 ft.
Oak Tree (dead & down), now 16" diam. S.22°W., instead
of S.29½°W. 82.5 ft., chopped out upper blaze &
found reverse scribe "R5W T25S & S". T24S
Set Brass Cap at Corner Mkd: County Surveyor's R5W S36 S31 R4W
Office, 1958 S 1 S 6
T25S
New BT's: 8" W. Oak S.52½°W. 24.4 ft. mkd. T25S R5W S 1 CS BT.
10" W. Oak S.44°E. 45.0 ft. mkd. T25S R4W S 6 CS BT.
8" W. Oak N.48°W. 15.6 ft. mkd. T24S R5W S36 CS BT.
7" W. Oak N.15°E. 25.9 ft. mkd. T24S R4W S31 CS BT.

C.E. Roberts
For J.S. Hunt
May 28, 1903
F.B. # 7, Pg. 8-9

¼ Corner to Sections 25 & 36. - See Cor. # 8 By B. Trumbo, 1927 49
Reset Post & made new Witness Tree:
Fir 48 N.67°E. 22 lks.

¼ Corner East Side of Section 36. 50
Reset Post.
Madrone 10 N 72° W . 10 lks.
Cedar 48 S 59° E 31 lks.

C. E. Roberts
For B. Norris, et al
June 8, 1903
Recorded in
F.B. # 7, Page 10

S.W. Corner Section 13. 51
Established by running from quar. posts N. & S.
Cedar 18 S 54 E 12 lks.
Cedar 10 N 55 W 27 lks.

¼ Corner between Sections 13 & 24. 52
Set Post -W.Fir 22 S 56 E 36 lks.
Cedar 28 S 86 W 8 lks.

CORNER NO. #82 83

South from quar. post between Sections 13 & 24, (Center of Sec. 24) 53
40.00 chains., Set Post: Cedar 12 N 10 W 7 lks.
Fir 28 East 27 lks.

James W. Byron, Deputy
S. A. Bilow
For T. W. Jones
May 11, 1959
C.S. File No. 49/155
M 15 - 15

¼ Section Corner to Sec. 34, T.25S. R4W. & Sec. 3, T26S R4W. 54
Found - Orig. Cedar BT., now 48", shows good bark scribing "¼ S BT"
S.61°W. 20.0 ft.
Orig. BT. R. Fir, now 36", N.33°W. 25.0 ft., shows good
bark scribing "¼ S".
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959
¼ S34 T25S R4W
S 3 T26S
New BT's: 18" Laurel bears N.51°E. 3.5 ft. scribed ¼ S34 CS BT.
8" W. Fir bears S.13°W. 21.9 ft. scribed ¼ S3 CS BT.

James W. Byron, Deputy
Clete Putnam
June 27, 1961
C.S. File No. 49/124

N. E. Corner D. L. C. No. 49. 79
Found - Orig. 15", now 36" Oak, partly rotted, shows old scribe
marks, N.4°W. 79.2 ft.
Also find 1¼" Car Axle at Corner. We find Eppstein's 12",
now 16" Fir Stump, N.32°W. 49.5 ft., not N.40°W. 30.0 ft.,
shows good reverse scribing on old chip. We do not find
Epp's. N.E. BT. We find 12" B.Oak Stump, shows good scribing
with Evans disk. This BT not of record, N.6°W. 21.7 ft.,
probably scribed by Evans.
26" W.Oak used for Gate Post bears S.61°W. 61.4 ft., shows scribing.
New BT: 8" R.Fir bears N.34°W. 68.6 ft. scribed N.E. Cl 49 CS BT. 55