

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 4-W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

84

$\frac{1}{4}$ Corner to Sec. 6, T25-4W. & Sec. 31, T24-4W.
Found - Mound of Rock at Corner, (No record)
Old Oak, down & partly rotted, N.11 $\frac{1}{2}$ °W. 231.7 ft., opened & found
fragmentary but legible reverse scribing " $\frac{1}{4}$ S".
30" Bl. Oak S.69°W. 351.1 ft., alive & standing, shows good
scars, did not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S R4W $\frac{1}{4}$ S31
Office, 1963 T25S R4W S 6
Replace Rocks around Cap.
New BT's: 15" W.Oak N.10 $\frac{1}{2}$ °W. 148.5 ft. Mkd: $\frac{1}{4}$ S31 CS BT.
9" W.Oak S.28°E. 59.6 ft. Mkd: $\frac{1}{4}$ S 6 CS BT.
Corner lies 8 feet West of a North and South Fence Line.

85

Wit. Corner $\frac{1}{4}$ Corner Sec. 5, T25-4W. & Sec. 32, T24-4W.
Found - W. Oak, recently uprooted & down, now 32", N.3 $\frac{1}{2}$ °E. 83.8 ft.,
opened & found good scribing "S BT". Ring Count shows this
to be Frear's scribing.
Rotten remnants of Oak Log S.81°W. 140 feet, Too far gone to find mks.
Did not find Rock set by Frear, Cor. location falls in gravel road.
Set - Brass Cap for Wit. Cor. 14 ft. West of $\frac{1}{4}$ Corner.
County Surveyor's Office, 1963 W.C. $\frac{1}{4}$ T24S R4W S32
14 feet E. to Corner. T25S R4W S 5
New BT's: 5" W.Oak N.82°E. 69.9 ft. Mkd: W C $\frac{1}{4}$ S32 CS BT.
6" W.Oak S.78°W. 38.2 ft. Mkd: W C $\frac{1}{4}$ S 5 CS BT.
Brass Cap set in fence line along S. W. side of Road to Manning's Place.

86

Township Corner
R4W S36 | S31 T24S
S 1 | S 6 T25S R3W
Found - Brass Cap set by Norman Price in 1944 (buried under fill on
W. side of Logging Railroad) - Dig around and
straighten up Brass Cap - Drive Cedar Stake Alongside.
18" D.Fir S.58°E. 71.9 ft. Cut open & found traces of scribing
on badly rotted face.
Stump of 50" Fir S.69°W. 219.8 ft. (across Calapooia from corner)
Shows good scar.
No trace remains of N. E. or N.W. Bearing Trees.
Blaze & Rescribe: 18" D.Fir S.58°E. 71.9 ft. Mkd: T25SR3W S6 CS BT.
New BT's: 9" D.Fir N.82 $\frac{1}{2}$ °E. 66.1 ft. Mkd: T24S R3W S31 CS BT.
10" D.Fir S.81°W. 34.5 ft. Mkd: T25S R4W S 1 CS BT.
18" D.Fir N. 4°W. 50.4 ft. Mkd: T24S R4W S36 CS BT.

87

Sec. Cor. to Secs. 1 & 2, T25-4W. & Secs. 35 & 36, T25-4
Found - 14" W.Oak N.30°E. 63.4 ft. (to face) Opened & fd. good scribing "CS".
14" W.Oak N.54°W. 18.5 ft. (to face) Shows good scar. Did not open.
10" W.Oak, in clump of 7, S.42°W. 21.8 ft. (to face) Shows scar.
Dead Oak Snag S.37°E. 119.0 ft. Had been opened previously, shows
old axe marks. Face Rotted (Original)
Shell of old Oak Stump S.84°W. 103.5 ft. (possible Orig. BT.)
Does not fit bear. or dist. on Gov't. notes.
No trace of other Original BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's T24S S35 | S36 R4W
Office, 1963 T25S S 2 | S 1
Rescribed: 10" W.Oak S.42°W. 21.8 ft. Mkd: T25S R4W S2 CS BT.
New BT's: 10" W.Oak N.4 $\frac{1}{2}$ °E. 62.6 ft. Mkd: T24S R4W S36 CS BT.
11" W.Oak S.3 $\frac{1}{2}$ °E. 35.3 ft. Mkd: T25S R4W S1 CS BT.
10" W.Oak N.88°W. 26.1 ft. Mkd: T24S R4W S35 CS BT.

88

$\frac{1}{4}$ Corner to Secs. 2 and 1.
Found - 2" Sq. Wooden Stake, still standing but rotten.
26" D.Fir S.68 $\frac{1}{2}$ °E. 30.7 ft., bark scribing visible " $\frac{1}{4}$ S1". REN.#29
16" D.Fir N.36°W. 19.5 ft. -2 good axe scars visible, Didn't open.
Down & Rotten Old Oak S.56°W. 39.6 ft., scribing Visible-Orig. BT.
No trace of Original N.E. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
T25S R4W $\frac{1}{4}$ S2/S1
Rescribe - 26" D.Fir S.68 $\frac{1}{2}$ °E. 30.7 ft. Mkd: $\frac{1}{4}$ S1 CS BT. (All in one blaze)
Cor. lies on very steep S.E. slope, approx. 200' N.W. of mail road up
Calapooia (at nearest point).

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Mike Stone
May and June 1963
C. S. File No. 53/9.

(SEE REN #31)