

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

75

Sec. Corner to Secs. 18 & 19, T25-3W. & Secs. 13 & 24, T25-4W.  
Found - GLO Brass Cap in place, 1943 & BT's. as follows:  
30", now 30" D.Fir S.70<sup>3</sup>/<sub>4</sub>°E. 13.9 ft., down & dead, shows old scar.  
36", now 36" I.Cedar S.45<sup>3</sup>/<sub>4</sub>°W. 11.9 ft., now stump.  
30", now 32" D.Fir N.26°W. 11.2 ft., dead, still standing, shows old scar.  
6", now 12" I.Cedar N.60<sup>3</sup>/<sub>4</sub>°E. 27.7 ft., snag, scribe visible on open face.  
New BT's: 8" I.Cedar N.61°E. 29.6 ft. Mkd: T25S R3W S18 CS BT.  
7" D.Fir S.16°E. 17.4 ft. Mkd: T25S R3W S19 CS BT.  
8" D.Fir S.41°W. 43.7 ft. Mkd: T25S R4W S24 CS BT.  
6" I.Cedar N.75°W. 41.2 ft. Mkd: T25S R4W S13 CS BT.

76

Sec. Cor. to Secs. 6 & 7, T25-3W. & Secs. 1 & 12, T25-4W.  
Found - GLO Brass Cap in small spring branch & 2 BT's:  
No trace of 18"x18"x12" Pits.  
5", now 18" D.Fir N.64°E. 99.0 ft., shows good scar. Didn't open.  
5", now D.Fir S.6<sup>1</sup>/<sub>2</sub>°W. 61.4 ft., shows good scar, Didn't open.  
New BT's: 15" D.Fir S.55°E. 21.9 ft. Mkd: T25S R3W S7 CS BT.  
5" Cedar N.76°W. 6.1 ft. Mkd: S 1 CS BT.  
Note - Spring is S.40°W. 53.0 ft.

77

$\frac{1}{4}$  Corner to Section 6, T25-3W. & Sec. 1, T25-4W.  
Found - 1944 U.S. Brass Cap & both BT's:  
5", now 16" D.Fir S.41°W. 141.9 ft., shows faint scar. Didn't open.  
7", now 16" Laurel S.44°E. 83.2 ft., shows faint bark scribe.  
We rescribe Laurel & Mark New Fir:  
16" Laurel S.44°E. 83.2 ft. Mkd:  $\frac{1}{4}$  S1 CS BT.  
9" D.Fir N.36°W. 20.7 ft. Mkd:  $\frac{1}{4}$  S1 CS BT.  
Note - This corner lies in small opening surrounded by young fir on West slope of hill.

78

Center  $\frac{1}{4}$  Corner of Sections 13.  
Found - 2" I.P. & Brass Cap set in 1958, by Cad. Eng. & BT's:  
27", now 29" D.Fir S.41°45'E. 48.8 ft., " $\frac{1}{4}$ " visible on pitched over face.  
11", Cedar N.7<sup>1</sup>/<sub>2</sub>°W. 25.4 ft., burned snag Mkd: C $\frac{1}{4}$  S13 BT.  
New BT: 13" I. Cedar N.51<sup>1</sup>/<sub>2</sub>°W. 212.9 ft. Mkd: C $\frac{1}{4}$  S13 CS BT.

79

N. E. Corner D. L. C. No. 49. - Witness Corner  
Found - 1 $\frac{1}{4}$ " Axle & following BT's: - See Ren. No. 55  
28" W.Oak S.61°W. 61.4 ft., shows scar. Tree was used as gate post.  
8" Fir N.34°W. 68.6 ft., now stump  
12" B.Oak Stump N.6°W. 21.7 ft.  
Old Oak Snag N.4°W. 79.2 ft., badly burned.  
Set - Wit. Cor. 20 ft. North of Axle, Brass Cap Mkd:  
County Surveyor's Office, 1964 T25S R4W W.C. 20 ft. So. to N.E. DLC 49  
New BT's: 21" W.Oak S.53°W. 94.6 ft. Mkd: W.C. NE DLC 49 CS BT.  
No other trees near.  
Note - This corner lies S. 5.0 ft. of fence bearing S.70°W.  
The stump of Evan's B.Oak bears N.70°W. 2.5 ft. We drive axle flush with ground.

80

Section Corner to Sections 11 - 12 - 13 - 14.  
Found - Cadastral Brass Cap and BT:  
13", now 16" Maple N.67°W. 41.6 ft., shows scribe on partially overgrown face. All other BT's. down & burned. REN.#11  
New BT's: 7" R.Cedar S.17°E. 8.6 ft. Mkd: S13 CS BT. This BT in fence line.  
12" R.Cedar N.39°E. 128.5 ft. (level) Mkd: T25S R4W S12 CS BT.  
Note - This corner lies in bottom of a draw bearing N. & S.  
Brass Cap is in a fence corner with fences going N. S. & W.

Mernon "Ray" Tracy,  
Mike Darby & Jack Barnett  
November 1964  
C. S. File No. 53/47

Fd. ox  
R.W.W.M.  
10/64  
M.S.S.-30