

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

81

$\frac{1}{4}$ Section Corner to Sections 14 and 13.
Found - 1957 Cadastral Brass Cap & BT:
12", now 14" Red Cedar S.29 $\frac{1}{2}$ °W, not S.39 $\frac{1}{2}$ °W., 7.9 ft.
Mkd: $\frac{1}{4}$ S14 BT on partially grown over face.
12" Fir Stump S.31°E. 23.1 ft. Mkd: $\frac{1}{4}$ S13 BT.
Apparently cut shortly after being scribed.
New BT: 10" Red Cedar S.77°E. 12.5 ft. Mkd: $\frac{1}{4}$ S13 CS BT.
Note - This corner lies S.45°E. 3.0 ft. from the top of bank
of Norris Creek which bears N.25°E.

82

~~$\frac{1}{4}$ Section Corner to Sections 13 and 24.
Found - No trace of Cadastral Brass Cap, Cor. falls in old cat road.
20", now 21" Cedar S.13 $\frac{1}{2}$ °W. 68.6 ft. shows $\frac{1}{4}$ S24 BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T25S R4W $\frac{1}{4}$ S 13
Office, 1964 S24
New BT: 7" Alder N.15°E. 37.2 ft. Mkd: $\frac{1}{4}$ S13 CS BT.
Note - This corner lies on west side of Gassy Creek, 16 ft.
from W. bank. *SEE ALSO COR.#52*
SEE BELOW~~

83

$\frac{1}{4}$ Corner to Sections 13 and 24.
Found - 1957 Cadastral Brass Cap at corner.
20", now 21" Cedar S.13 $\frac{1}{2}$ °W. 204 lks. instead of 104 lks.,
as there is no trace of where the Alder BT was located,
we measure the calls 3 ways from corner. - *REN.#52*
New BT: 6" Alder N.55°W. 10.7 ft. Mkd: $\frac{1}{4}$ S13 CS BT.
Note - This corner is on a point of land with Gassy Creek on the
S., E. & N. sides. Also there is a steel fence post set
alongside brass cap extending 48" above ground.

84

Section Corner to Sections 5 - 6 - 7 - 8.
Found - Sandstone 6" x 8" x 12", buried, & 2 Orig. BT's: (See Ren.#5)
12", now 30" W.Oak S.70°W. 142.6 ft., find reverse "S" scribe.
15", now 34" W.Oak N.29°20'W. 77.9 ft., shows very faint
scar. Did not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's T25S R4W S 6 | S 5
Office, 1964 S 7 | S 8
New BT's: 34" W.Oak N.29°W. 77.9 ft. (Orig.) Mkd: T25S R4W S6 CS BT.
15" W. Oak S.14°W. 94.1 ft. Mkd: T25S R4W S7 CS BT.
(This tree has fence on S. Side)
12" W.Oak S.15°E. 89.6 ft. Mkd: T25S R4W S8 CS BT.
No trees close to N. E.
Most westerly guy ring on P.P.&L. Line bears N.50°E. 90.2 ft.

85

Section Corner to Sections 1 - 2 - 11 - 12.
Found - BT's. as recorded in Ren. #16, as follows:
6", 12" W. Oak S.6°E. 9.9 ft., shows scar, Didn't open.
7", now 13" Ash S.21°W. 11.2 ft. Open & find "S" Scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T25S R4W S 2 | S 1
Office, 1964 S11 | S12
New BT's: 8" W.Oak N.8°W. 24.9 ft. Mkd: T25S R4W S2 CS BT.
6" W.Oak N.36°W. 24.1 ft. Mkd: T25S R4W S1 CS BT.
Note - This corner lies 5 ft. S. & 65 ft. W. of Fence Corner, with
fences running N. & E. on E. edge of old Cat Road.

86

$\frac{1}{4}$ Corner to Sections 11 and 12.
Found - 1 $\frac{1}{4}$ " Iron Axel Shaft, as called for in Ren. #12.
Stump of one BT. No trac of other BT.
24", now 30" D.Fir Stump N.70°E. 19.1 ft., shows scar, we
open & find burned face.
New BT's: 8" R. Cedar N. 1° E. 5.6 ft. Mkd: $\frac{1}{4}$ S12 CS BT.
7" R. Cedar S.34°W. 37.5 ft. Mkd: $\frac{1}{4}$ S11 CS BT.
Note - This corner lies on E. edge of old cat road, 3.0 ft.
north of fence corner.

Vernon "Ray" Tracy
M. Darby & J. Barnett
November 1964
C. S. File No. 53/43

FD OK 11/87
M 105-17
D. BENTZ