

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 4 W. R. W. W. M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 21881

114

$\frac{1}{4}$ Corner to Sections 27 and 26.
Found - Co. Surv. Brass Cap, See Ren. #39 & B.L.M. Brass Cap in place.
8", now 10" Fir S.21 $\frac{1}{2}$ °W. 32.3 ft. " $\frac{1}{4}$ S" visible on partially grown
over face.
44" Cedar Snag S.10°E. 19.8 ft., shows "S" scribe on face &
rescribed " $\frac{1}{4}$ S" on outer face.
New BT: 10" D.Fir S.70°E. 35.7 ft. Mkd: $\frac{1}{4}$ S26 CS BT.

Feb. 23, 1965

115

Section Corner to Sections 28 - 29 - 32 - 33.
Found - BLM Brass Cap, 1957 & two live BT's:
25", now 25" Cedar S.57 $\frac{1}{2}$ °E. 108.2 ft., shows "T25S R4W S33 BT"
on partially healed blaze.
7", now 10" Fir N.64 $\frac{1}{4}$ °W. 141.2 ft., face pitched over. Did not open.
Other BT's. turned out & out of place.
New BT's: 9" D.Fir N.40°E. 6.4 ft. Mkd: T25S R4W S28 CS BT.
8" D.Fir S.71°W. 29.0 ft. Mkd: T25S R4W S32 CS BT.
Note - This corner lies on very steep south slope 25.0 ft. south of
E - W Fence.

116

$\frac{1}{4}$ Corner to Sections 26 and 35.
Found - BLM & County Brass Cap (See Ren. #36).
10", now 16" Cedar N.29 $\frac{3}{4}$ °E. 254.8 ft., scribe visible on
partially grown over blaze. This tree recorded in Ren. #36
as N.33°47'E. 255.01 ft.
13", now 16" Cedar N.39 $\frac{1}{2}$ °E. 335.3 ft. " $\frac{1}{4}$ S26 BT" visible on
partially grown over blaze.
Both BT's. to south down & out of place.
New BT's: 9" Cedar S.50°E. 98.5 ft. Mkd: $\frac{1}{4}$ S35 CS BT.

117

$\frac{1}{4}$ Corner to Sections 27 and 26.
Found - BLM Brass Cap & County Brass Cap (Ren. #39) in place.
8", now 10" Fir S.21 $\frac{1}{2}$ °W. 32.3 ft. " $\frac{1}{4}$ S" visible on partially
grown over face.
44" Cedar Snag S.10°E. 19.8 ft., shows "S" scribe on face &
rescribed " $\frac{1}{4}$ S" on outer face. (Repeat of Cor. #114)
New BT: 10" D.Fir S.70°E. 35.7 ft. Mkd: $\frac{1}{4}$ S26 CS BT.

118

$\frac{1}{4}$ Corner to Sections 28 and 33.
Found - Orig. 16", now 22" Fir Snag, S. 50° E. 19.1 ft., upper scar
prev. opened & shows frag. scribe, Chop out lower scar & find
"T", also scribe on ground at base of tree.
No trace of other Orig. Bearing Tree.
41" D. Fir S. 77° W. 32.1 ft., bark scribed " $\frac{1}{4}$ S BT".
Set - Brass Cap Mkd: County Surveyor's Office, 1966 T25S R4W $\frac{1}{4}$ S 28
S 33
New BT's: 11" W. Fir S. 51° W. 9.7 ft. Mkd: $\frac{1}{4}$ S33 CS BT.
9" D. Fir N. 70° W. 11.2 ft. Mkd: $\frac{1}{4}$ S28 CSBT.
Note - Corner lies approximately 150 ft. east of creek, course N.
May 26, 1966

SEPT. '68

MICROFILM TO HERE 10/67

119

S. E. Corner D. L. C. No. 46.
Found - County Surveyor Brass Cap flush with surface of ground marked
"C.S. Office, 1954 S.E. Cor. Cl.46", as recorded in Ren. #46,
& BT recorded in Ren. #99, as follows:
11", now 13" D.Fir, alive, N. 82°E. 159.7 ft., scribe visible
on nearly healed blaze.
N. E. Bearing Tree cut off 10" above ground.
New BT: 16" D.Fir N. 5° W. 88.6 ft. mkd. "S E DLC 46 CS BT".
and S. E. Corner of Fair Oaks Community Church bears N.38 $\frac{1}{2}$ °W. 66.2 ft.
(not N.42 $\frac{1}{2}$ W) 9/19/68

Vernon "Ray" Tracy
M. Darby & J. Barnett
February & March 1965
C. S. File No. 53/47

FO OK
11/87
105-17
D. BENTZ

RE-DEVELOPED, SEE CORNER NO. #130

OF REN. #114