

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 25S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner common to Sec. 25, T25-5W. & Sec. 30, T25-4W.  
This corner is S.35°E. 25.0 ft. from Skid Road and  
S.35°E. 40.0 ft. from Creek.

Set = 5/8" I.Rod, 1.0 ft. south of corner which fell in  
center of large uprooted fir, from which:

Mkd: A 38" Fir N.27°W. 56.3 ft. (Mkd: "1/4 S25 BT")  
A 4" Fir S. 9°E. 5.7 ft. (Mkd: "X")

March 1970

120

Donald A  
Bentz  
For Denley  
Map File  
M 33 - 71

121

Interior "L" Corner D. L. C. No. 49.  
Found 1/2" X 30" I. Pipe, (See Ren. #61 ?)  
Set - 5" Triangular Top by 13" Long Sandstone,  
0.5 ft. north of pipe marked "+" on top.

June, 1969

Garrett,  
Don E.  
For:  
Faas, W.  
C.S. M 38-7

122

Section Corner to Secs. 18 & 19, T25-4W. and  
Secs. 13 & 24, T25-5W.

1957 B. L. M. Brass Cap, not found.

I Re-Set Corner from BT's., as follows:

12" Ash bears N. 6 1/2° E. 281.8 feet  
11" Ash bears S. 37° E. 390.1 feet  
7" Ash bears S.22° W. 345.2 feet  
10" Ash bears N. 67 1/4° W 206.6 feet

Set - 5/8" Iron Rod at Corner.

10/18/71

McLind, Victor  
For: Bob  
Wiley  
Map File  
M 43 = 79

123

Section Corner Sections 3, 2, 10, and 11.

Found - 6" x 6" x 18" Stone, 14" underground, + on top. Ren. No. 73  
44" D. Fir, N.60°W., 105.5 ft. Bark Scribe visible.  
36" D. Fir, now stump, N.8°E., 140.4 ft. Bark scribe visible.  
8" W. Oak, now 14", S.81 3/4°W., 199.0 ft. (Record Dist.  
189.8 ft.)

SE BT logged.

New BT - 9" W. Oak, N.19°E., 212.3 ft. Scribed T25S R4W S2 CS BT.

Note - As this corner falls in field I do not put any thing at sec.  
corner. Stone used.

3/5/73

JAN 1972

John M. Powell  
C.S. File 56/25  
March 1973

124

1/4 Corner, Sections 23 and 24.

Found - 42" Fir, S.10°E., 9.24 ft. Blown down. Bark scribe visible.  
18" Cedar, N.50°, 9.90 ft. Cut out with power saw. Scribe  
visible.

Set - Brass Cap mkd. County Surveyor's Office, 1956 1/4 S 23 T 25  
S R 4 W. 24

New BT's - 13" Cedar, N.45'0"E., 29.5 ft. Scribed 1/4 S24 CS BT.  
20" Cedar, S.50'45"W., 28.5 ft. Scribed 1/4 S 23 CS BT.

11/20/56

125

1/4 Corner, Sections 12 and 13.

Found - Orig. NE BT, now 42". Bark scribed 1/4 S12. Top scribe 5' above  
ground. has yellow tag set by Haines 1943. Also tag set  
by ELM 1956.

SW BT is gone. Would be in roadway. Cor. check call to creek.  
NE BT alive and good condition.

Set - Brass cap at cor. mkd. County Surveyor's Office 1956, 1/4 S 12  
T 25 S R 4 W. Set cap 1" below surface. 13

From which - 14" Hemlock bears S.17°W., 53.0 ft. Scribed 1/4 S13 CS BT.  
10" Maple, S.17°W., 33.0 ft. scribed 1/4 S13 CS BT, 20 years +  
down. Var. 21 1/4°

James Byron, Surveyor's Office  
G. Welker  
J. Fee  
Nov. 20, 1956  
e s #1/33  
C. S. 36/58