

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 25 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

131

Center 1/4 corner of Sec. 16.
 Found - Aluminum tag on 15" fir mkd, Sec. 16, T. 25-4. Approx. Hub bearing
 N. 76° 30' E. dist. 46.2-ft. Decl. 20-1/2°. BLM 1-29-65 (not of record)
 Set - 5/8" x 30" Iron Rod w/cap marked LS 1076.
 New BTs- 12" fir bears S. 5° W., 28.1-ft. scribed C 1/4 S16 BT.
 8" fir bears N. 33° E., 25.0-ft. scribed C 1/4 S16 BT. 9/82

Robert L. Dolan
 PLS # 1076
 For: John Boatman
 Sept., 1982
 M 93 - 17

132

Section corner for Secs. 7 and 18; and 12 & 13 of T. 25-5
 Set - Oregon St. Bd. of Forestry 1 1/2" x 36" Alum. pipe with 3 1/2"
 Alum. cap with magnetic insert, 50" in ground.
 Reference Monuments:
 5/8" x 30" iron rod, 24" in ground bears S. 56 1/2° W., 275.8 ft. in
 fence line.
 5/8" x 30" iron rod, 24" in ground bears S. 79 3/4° E., 226.6 ft.
 5/8" x 30" iron rod, 24" in ground bears N. 32 1/2° E., 135.8 ft.
 5/8" x 30" iron rod, 24" in ground bears N. 39 1/4° W., 351.0 ft. in
 fence line.

133 (See Ren. #126)

1/4 Corner for Secs. 18 and 7
 Set - Oreg. ST. Bd. of Forestry 1 1/2" x 36" alum. pipe with 3 1/2"
 Alum. cap with magnetic insert, 34" in ground.
 BT's - 18" fir, N. 67° W., 87.8 ft.
 11" Oak, S. 57 1/4° E., 28.5 ft. with yellow metal location poster.
 Bearing Objects:
 4" x 4" x 72" white painted cedar post bears S. 48° W., 1.5 ft.
 Gravel road 8 ft. wide east 11.0 ft. course N. 33° E., by S. 33° W.

134

NW corner Govt Lot 3 (Sec. 18)
 Set - Oreg. St. Bd. of Forestry 1 1/2" x 36" alum. pipe with 3 1/2"
 alum. cap with magnetic insert, 34" in ground.
 BT's - 15" fir, S. 20° E., 125.0 ft. with yellow metal location poster.
 11" fir, S. 47° E., 115.4 ft.
 Bearing Objects:
 4" x 4" x 72" white painted cedar post bears S. 51° E., 1.2 ft.
 Sandstone 6" above ground, S. 03 1/2° E., 49.5 ft. (chiseled X visible)
 in fence corner. See Ren. #28
 Woven wire fence east 5.2 ft. course S. 02° W., by N. 02° E.

135

NW corner U.S. Govt. Lot 4 (Sec. 18)
 Set - OSBF 1 1/2" x 36" alum. pipe with 3 1/2" alum. cap with magnetic
 insert, 32" in ground.
 BTs - 11" fir, N. 57 1/2° E., 38.4 ft.
 16" fir, S. 54 1/2° E., 27.6 ft. with yellow metal location poster.
 4" x 4" x 72" white painted cedar post bears S. 46° E., 1.4 ft.
 Woven wire fence east 10.0 ft. course North by South.

136

SW corner U.S. Govt. Lot 4 (Sec. 18)
 Set - OSBF 1 1/2" x 36" alum. pipe with 3 1/2" alum. cap with magnetic
 insert, 30" in ground.
 Bearing Objects:
 13" fir, N. 03 1/4° E., 84.8 ft. with yellow metal location poster.
 7" fir, N. 84° E., 69.7 ft.
 4" x 4" x 72" white painted cedar post bears N. 79 1/2° W., 2.0 ft.
 Woven wire fence, East 26.1 ft.

137

Easterly SE corner, DLC #50
 Set - 5/8" x 30" iron rod with plastic cap 28" in ground.
 BTs - 8" fir bears N. 64 1/4° E., 16.1 ft.
 6" fir, N. 39° W., 2.7 ft.

138

Interior L Corner DLC #50
 Set - 5/8" x 30" iron rod with plastic cap 28" in ground.
 BTs - 37" oak, S. 26° E., 69.1 ft.

Lloyd D. Smith For:
 Oregon State Board of Forestry
 March 30, 1983
 M 94 - 1