

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 25      T. S.      R 4      R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

cont. - - -

(Int. L. Cor. DLC #50)  
36" oak, N.22 1/2°E., 116.0 ft.  
Woven wire fence east 45.0 ft. course North by South.

**138**

L. D. Smith For  
Oreg. St. Bd. of  
Forestry  
March 30, 1983  
M 94 - 1

SE corner for DLC #50  
Set - 5/8" x 30" iron rod with plastic cap 28" in ground.  
BTs - 26" fir, N.12 1/2°E., 34.6 ft.  
9" oak, S.75 1/2°E., 63.2 ft.  
Woven wire fence North 53.0 ft. course N.36°W. by S.36°E.,

**139**

3/30/83

James W. Byron  
G. Welker  
J. Fee  
Nov. 20, 1956  
C.S. 47/133

1/4 Corner for Sections 14 and 23.  
Found - Orig. SW BT, now down, scribing visible.  
NE BT, Cedar stump only, no scribes. Checks for record bearing  
and dist. Also checks calls to creek.  
Set - Brass cap marked County Surveyors Office 1956 1/4 S 14 T25S  
R 4 W. 23  
From which:  
15" cedar bears N.34 1/2°E., 83.3 ft. scribed 1/4 S 14 CS BT.  
10" W. fir, S.64°W., 70.0 ft. scribe 1/4 S 23 CS BT.

**140**

11/20/56

**141**

Section corner for Sections 6 and 7; and Secs. 1 & 12 of T.25-5.  
Set - 2" x 30" iron pipe with 2 1/2" brass cap marked "T25S R5W T25S  
R4W 1 12 6 7 L.S. 418 1984".

New accessories:  
30" eastern oak, bears N.89°E., 62.8 ft. which I bark scribe  
"T25S R4W S6 BT".  
10" horse chestnut bears S.31°E., 41.6 ft. which I bark scribe  
"T25S R4W S7 BT".  
20" maple bears S.11°W., 66.7 ft. which I bark scribe "T25S R5W  
S12 BT".  
5/8" x 30" iron rod bears N.2°W., 31.1 ft. in fence line.  
The corner lies 100 ft. + east of farmhouse and all bearing trees are  
domestic shade trees. Bark scribing used to avoid any possible damage to  
these trees.

7/84

**142**

L. W. Barber For:  
Bureau of Land Manage-  
ment  
May 15, 1974 (filed  
Nov. 1984)  
M 97 - 62

1/4 Corner for Section 2; and Sec. 35 of T.24-4  
Set - Rebar, 1/2" x 18" (See ALSO REN #32)  
BTs - 14" fir, N.17°E., 59.5 ft.  
48" cedar, S.75°E., 55.5 ft.  
18" fir, S.23°30'E., 38.6 ft.

**143**

NNW corner for DLC #37  
Found - A 3" x 10" x 13" stone buried with top protruding 3" above  
ground. Possible original monument.  
20" now 21" dia. 15 ft. high snag, previously opened, we find  
older axe marks and small pieces of blaze with no scribing,  
bears S.75°E., 75.1 ft. (Rec. S.71°E., 73.9 ft. Distance a  
possible face measurement.  
Set - We monument the position of stone as the most probable location  
of the orig. NNW DLC 37 corner based on the following ob-  
servations. Stone appears to be a locally accepted corner. It  
is the intersection point of an old northerly-southerly and  
easterly fence line. Stone was tied in survey (M44-7) by  
Victor McLind as the DLC corner. The orig. call of Calapooya  
Creek to the east checks out well. The position of stone fits  
well with other government corners in area (SE cor DLC #46 and  
section corner for 1 1/6 (See computations in C.S. folder.)  
12 1/7

Set - 2 3/8" dia. brass cap on a 1" Inside dia. x 32" long iron pipe  
protruding 8" above ground. Reset 3"x10"x13" stone along  
east edge of I.P. protruding 3" above ground.  
New BTs - 9" D. fir double blazed and scribed "NNW DLC 37 CS BT" bears N.  
81 3/4°E., 25.9 ft.  
12" I. cedar double blazed and scribed "NNW DLC 37 CS BT" bears  
N.51 1/2°W., 31.8 ft.

Douglas County  
Surveyors Office  
Randall W. Smith  
Stephen J. Flause  
April 14, 1987  
C.S. 62/40