

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 5 R. W. W. M.

J. W. Cole
N. E. Richardson
Sep. 2, 1933

H. L. Eppstein Co. Sur.
Wit. N. E. Richardson
B. A. Lane
Feb. 5, 1931

N. E. Richardson
B. A. Lane
Milton Palm
D. L. Byers
J. H. Byers

H. L. Eppstein
Wit. F. C. Frear
Jas. Wolford
G. W. Milam
8-25-1934

A. R. Evans - Surv.
Godfrey
Matthews - Wit.
Wm. W. Elmer
Surveyor
4-14-48
April 1950
C.S. #752

26-27-34-35

Marked New trees

Fir 11" dia. N. 51 1/2° E. 9.0 ft.
Fir 24" dia. S. 46° 30' W. 13.0 ft.
B. Oak 24" dia. S. 54° 30' W., 91.3 ft.
Fir 12" dia. N. 64° 30' W., 27.0 ft.

RE-RENEWED, SEE CORNER NO. 74

18

1/4 COR. BET. SECS. 17 and 18.

Renewed corner from Original B.T. 2 oaks one down other standing but dead. Set 3/4" x 36" pipe for corner marked new witness trees

A 10" Fir N. 61° 30' W., 63.7 feet.
A 15" Pine S. 58° E., 56.0 feet.

SEE CORNER NO. 55

19

CORNER 7-8-18-17.

Set car axle for corner from white Oak witness tree scribe marks plain, tree down, in Sec. 17, the tree in Sec. 8 standing but burnt out, tree in Sec. 7 down but stump in place no scribe marks, tree in sec. 18 gone. Marked new witness trees:

10" Fir S. 80° E., 31.1 ft.
8" Fir N. 49° E., 81.4 ft.
24" B.O. N. 83° W., 81.5 ft.
12" W. Oak S. 65° W., 140.4 ft.

SEE CORNER NO. 65 & 77

20

SEC. COR. TO SECS. 1-2-11-12.

Found three original B.T.'s. One tree blown down. Scribe marks visible. One tree in good shape did not chop in to good scars, other tree badly rotted, scribe marks visible. Corner stake O.K. Cedar. Marked

An Oak 10" dia. N. 16° W., 27.4 ft.
Laurel 10" dia. N. 38 1/2° E., 33.8 ft.

SEE CORNER NO. 67

21

N.W. COR. OF CL. 43

Found old stake badly rotted found old scribe marks. Measures out correctly for distance from Sec. Cor. could not find old B.T.'S. Set 4" x 4" x 24" Cedar Post marked on it N.W. Cor. Cl. 43. Marked:

Oak 10" dia. bears S. 34 1/2° W., 13 ft.

SEE CORNER NO. 87

22

COR. 10-11-14-15.

Re-established from Original B.T. to wit, ash 36", marks still visible bears B. 76 1/2" dia. 99.9 ft. I remark this tree also an ash 10" N. 18 1/2° W., 61.7 ft.

An Ash 14" N. 13° E., 97.0 ft.

Also set a 1/4" x 1 1/4" x 36" Spring and an 18" Rasp for Corner.

RE-RENEWED, SEE CORNER NO. 57

23

1/4 Sec. Cor. Bet. Secs 20 & 21 - FOUND - O.K. - May, 1964. J.L. Sec C. 8. 49/124

Reestablished by W. W. Elmer; Reg. Prof. Eng'r. # 593

Witness: Claud Schrack

Found original Black Oak B. T. scribed by J. W. Cole, Nov. 20, 1920 - Ren # 13

Rescribed: 1/4 Cor. B. T. Set a 2" x 34" steel shaft, 30" in ground, North 49° 45' W., 42.1 ft. for reestablished 1/4 cor.

Stamped on top surface of this shaft, inscription. W.W. Elmer #593

Scribed new bearing tree: A White Oak, 18" diam. bears S 41° 43' W, 137.94 ft.

RE-RENEWED, SEE CORNER NO. # 136

24

SECTION CORNER 4-5-8-9

Corner is a 6" diam. concrete block, set in the ground with a bolt for the center. Apparently set recently. Ties:

3/4" iron rod, stamped, 593, bears N 16° E 263.6 feet.

Iron Pipe, Init. pt. for Wilder, bears N 66° E 227.2 ft.

B. T. bears S 63° 30' E 316.5 ft.

Found bolt set by Eck in 1947, and rock set by Frear 1917, taken out and lying alongside. Jack Chapman testifies Eck referenced point on rock before removing and set bolt in accordance with these reference points.

I blazed and scribed an Elm tree for new B. T.

30" American Elm bears S 62° 00' E 319.5 ft., mkd.

T 25 S, R 5 W, S 9 C.S.B.T.

Distance to tack in face of blaze.

SEE CORNER NO. 34

25