Douglas County Surveyor's Record of Government Corners Renewed

25 T. S. 5 R. W. W. M.

KOKE CHAPMAN CO., EUGENE, ORE. 81008

26

¼ COR. BET. SEC'S. 4 and 5
Drove a Ford axle for corner in position of old stub placed by B.H. Manning in position of original corner.
A 14" Cedar bears S 70° E 92 lks.
An 8" B. Oak bears S 12° W 57 lks.
Affidavits in Vault 14, E 30 by H.L. Kruse, B.H. Manning, and Alfred Hand; witnesses; who state that this is the proper location of the corner.

Ben B. Irving-Deputy
County Surveyor
Alfred Hand-Witnesses
R.L. Irving
May 1, 1928
C.S. 14/50

RE-ESTABLISHED, SEE CORNER NO. #125

27

N. E. COR. OF DLC # 52 (A. C. JENKINS) — SEARCHED FOR - NOT FOUND - MAY 1964 C.S. 49/124 M.E.G.
Set 8" x 12" x 24" sandstone 21" in ground. Chiseled N.E. Cl. 52 on South and 593 on North with cross for transit point.
5/8" x 30" iron rod at base of 8" Laurel scribed N.E. Cor. 52 - BT bears N 49° 02' E 27.04 ft.

Wm. W. Elmer
November 7, 1947 &
July 7, 1948
C.S. 40/112

SEE → A.E. EVANS 9/1950 CS44/58

28

¼ SEC. COR. BETW. SECS. 33, T 24 S, R 5 W, & 4, T 25 S, R 5 W.
Found rock with X.
36" W. Oak (Y) S 20° W 19 ft. Blaze plain; Old B.T. fits for distance.
B.T. remarked by Thiel ¼S - RS 4 - B.T.
Thiel remarked new B.T. - 24" B. Oak N 70° W 45.8 ft.

C.F. Thiel

(See Thiel's Book 3 P642 (Not Described) IN this Reference)

RE-ESTABLISHED, SEE CORNER NO. #136

SEC. COR. 1-2-35-36 (N side Twp) March, 1884
Set post from which
A W. Oak 5 in. dia. bears S 65° W 46 lks.
A W. Oak 4 in. dia. bears S 9½° E 80 lks.

29

SEE CORNER NO. 48

30

¼ sec. cor. bet. secs 10 and 11.
Set a stone 20 x 15 x 5 ins. for cor. from which
A white oak 24 ins diam bears S. 42½° E 152 lks dist,
A fir 20 ins. diam bears S 85° W 119 lks distant,
The old B T have been cut down year ago but one stump remaining by which I establish the new cor. July 2, 1900.
Present, May and Arthur Thiel.

C.S. Vol 2, Page 262

RE-ESTABLISHED, SEE CORNER NO. 59

¼ sec. cor. bet. secs. 3 and 10.
Set a sawed post and buried a brick alongside from which
A fir 18 ins. diam. bears N 35°W 40 lks. dist. from which a fir 20 inches diam. bears S 36° E 50 lks. dist. The new B T. the only one standing had the marks destroyed by fire several years ago but being vigorous I remarked same I have known this tree to be and original bearing tree for 18 years or longer.

31

N. W. corner D. L. C. # 55.
Feb. 14, 1896 Hayden
Set stone 5" x 9" x 10" marked B. T.
W.O. 24" N 83°-30'E 47 lks.

32

S. W. Cor. D. L. C. 46 ← COR. SEARCHED FOR - NOT FOUND - MAY 1964 - M.E.G. See C.S. 49/124
July 7, 1884 by Wm. Thiel
Set rock 15 x 8 x 4 with 3 more smaller rocks.

33

RE-ESTABLISHED, SEE CORNER NO. #140