

Douglas County Surveyor's Record of  
Government Corners Renewed

25

T. S.

5

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

34

A. R. Evans  
For Martin Bros.  
Box Co.  
April, 1954  
Sur. file 41/299

Section corner to secs. 4, 5, 8 and 9.  
Found a  $\frac{1}{2}$  inch iron bolt set in concrete and one B.T., an  
American Elm, S.63°14'E., 319.5 feet. REN. #25  
Set a 1 inch iron post in concrete with brass cap marked  
T25S, R5W, 4-5-8-9-R.E. 2741.  
Set 2  $\frac{7}{8}$  inch iron rods for reference points:  
S.63°14'E., 307.5, and N.63°14'W., 234.9.

County Surveyor's Office  
March 28, 1955.  
C. S. File No. 46/108


Section corner to secs. 15, 16, 21 and 22. 35  
Found - 40 inch W. O., S.24 $\frac{1}{2}$ °E., 177 lks. (116.8 feet), scribe marks  
visible of original survey and some scribe marks made about 10  
years later. Otherwise tree was destroyed.  
Set 1 inch by 36 inch iron pipe with brass cap marked County Surveyor's  
Office, T25S, R5W., 16 15 1955.  
From which:  
R. Fir, 10 inches bears S.56°W., 63.2 feet, marked T25S, R5W.,  
S 21 CS BT.  
R. Fir, 16 inches bears S.12°E., 115.3 feet, marked T25S, R5W.,  
S 22 CS BT.  
R. Fir, 8 ins. bears N.22°E., 163.0 feet, marked T25S, R5W.,  
S 15 CS BT.  
No trees of sufficient size available in NW. quad.

Stephen H. Ford  
April, 1955.  
C. S. File No.  
41/376.

$\frac{1}{4}$  sec. corner to secs. 27 and 28. 36  
Set  $\frac{5}{8}$  inch iron pin, from which:  
Found a  $\frac{3}{4}$  inch Fir Original B. T., N.66°E.,  
37.98 feet.  
Found a 28 inch Fir Original Bearing Tree, N.34°W.,  
66.00 feet.

James W. Byron, Deputy County Surveyor  
R. Irving  
J. Fee  
May 6, 1955.  
C. S. File No. 46/150.

$\frac{1}{4}$  sec. corner to secs. 28 and 29. 37  
Found - Stump of W. O. face rotted - checks record distance and bearing  
to 8" x 8" stone with cross under N. S. fence. Also found scribe marks  
on sect. at stone - probably from W. O. stump. The S. W. BT gone.  
Set 1" x 36" pipe with Brass Cap mkd.  $\frac{1}{4}$  corner 29/28 T 25 S, R 5 W,  
County Surveyors Office 1955. SEE CORNER NO. 93  
Blazed and Scribed:  
14" R. Fir, N.8 $\frac{1}{2}$ °E., 56.7 feet, mkd. S 28,  $\frac{1}{4}$  cor. CS BT.  
14" R. Fir, N.64°W., S 29  $\frac{1}{4}$  cor. CS BT., 46.3 feet dist.  
Var. 21 $\frac{1}{4}$ °.

Section corner to secs. 20, 21, 28 and 29. 38  
Found - 48" R. Fir, S.47°E., 66.0 feet scribed (bark) CS BT. Found  
both B. O. as recorded by Cole in 1920. The B. Oaks show old blazes  
but faces are rotted - no scribing visible. All three B.T.s check for  
bearings and distances. Also found 4" x 4" properly scribed at fence  
corner. REN #12  
Set 1" x 36" Iron Pipe with brass cap mkd.  $\frac{20}{29}$  sec. cor. T 25 S, R 5 W.,  
County Surveyors Office 1955.  
Blazed and scribed:  
6" R. Fir, N.50°E., 11.0 feet mkd. S 21 CS BT.  
6" R. Fir, N.64°W., 13.5 feet mkd. S 20 CS BT.  
7" R. Fir, S.38 $\frac{1}{2}$ °W., 40.6 feet mkd. S 29 CS BT.  
Brass cap is at fence corner  Var. 21 $\frac{1}{4}$ °.

(over)