

Douglas County Surveyor's Record of
Government Corners Renewed

25 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21861

J. Byron
C.S. File
No. 49/124

1/4 Section Corner to Sec. 13, T25S R5W, & Sec. 18, T25S R4W. 43
Found - Orig. 12" W. Oak, now 20" (down) S.11°E. 58.1 ft. I open
& find good scribing "1/4 S"
Stump Hole S.49°E. 49.5 ft. (Record 49°E. 49.5 ft.)
Set Brass Cap at Corner Mkd: 1/4 S13/S18 T25S County Surveyor's
R5W R4W Office, 1958
New BT's: 14" R. Fir bears N.67°W. 54.3 ft. scribed 1/4 S13 CS BT.
15" W. Oak bears N.52 1/2°E. 33.7 ft. scribed 1/4 S18 CS BT.

By W.F. Briggs
4 - 18 - 1889
Recorded in
Vol.1,
Pg.135-6

Center of Section 10. 44
40.00 chains, Set Post center of Sec. 10, from which
Laurel 12" diam bears S.09 1/2°W. 21 lks.
Fir 8" diam bears S.51 1/2°E. 19 lks.

James W. Byron
S. A. Bilow
April 28, 1959
C. S. File No. 49/123

1/4 Corner common to Sec. 31, T25S R5W, & Sec. 36, T25S R6W. 45
Found - Both BT's. recorded by Kerr, 1951:
18", now 20" Fir S.77°W. 7.9 ft., standing & in good
condition, shows good scribing "1 1/2".
Fir N.26 1/2°E. 5 ft., now down & down hill. May have
been pushed down by Cat.
No trace of Orig. N.E. BT. It also may have been pushed
by Cat.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959
1/4 R6W S36/S31 R5W T25S
New BT.: 10" R. Fir bears N.46°E. 68.6 ft. scribed 1/4 S31 CS BT.
Note - N S Fence is 15' West of Corner.

Fred L. Dow
For Ray Davis
March 1954
C.S. File No. 50/30

Sec. Cor. Secs. 2 & 3, T25S R5W, & Secs. 34 & 35, T24S R5W. 46
Set Stake for Section corner.
12" Ash S.1°W. 36.6 ft.
18" Oak N.78°W. 45.6 ft. SEE CORNER NO. 39

Sec. Cor. Secs. 3 & 4, T25S R5W, & Secs. 33 & 34, T24S R5W. 46-A
Also noted as S.W. Corner J. Tibbets DLC No. 47.
Found 1" Iron Pipe. SEE CORNER NO. 50
Rotten Stump Original Bearing Tree
24" Oak N.30°E. 310 lks.

James W. Byron
Milo Godfrey
Clete Putnam
Dec. 31, 1959
C. S. File No. 49/124

1/4 Section Corner to Sections 33 & 34. 47
Found - Orig. 30", now 36" Pine Stump S.77°W. 19.8 ft., previously
opened, shows good scribing "BT". This BT. faces approx.
N.65°W., record S.77°W. Ring count & Size O. K.
No trace of N. E. BT.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959
1/4 S33/S34 T25S R5W
New BT's: 22" R. Fir bears N.83°W. 30.4 ft. scribed 1/4 S33 CS BT.
9" R. Fir bears N.85°E. 26.7 ft. scribed 1/4 S34 CS BT.

James W. Byron
Milo Godfrey
Clete Putnam
March 4, 1960
C.S. File No. 49/124

Sec. Cor. Sec. 1 & 2, T25S R5W, & Sec. 35 & 36, T24S R5W. 48
Found - No Trace of Orig. BT's. found.
Stewart's BT's found - 18", now 33" Stump S.62°W. 62.5 ft.,
previously opened, shows good scribing "CS". See Ren. #29
18", now 30" Fir Stump S.57°E. 73.0 ft., shows good scar,
I do not open. PER B. HOLT
M 97-24
NEW BURNED
STUMPS.
8", now 22" Fir N.67°E. 37.0 ft., shows good scribing "W". NEW BURNED
STUMPS.
Note - Distances to BT's. recorded by Stewart are measured on slope.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
S35 | S36 T24S R5W
S 2 | S 1 T25S R5W
New BT's: 8" R. Fir bears N.79°W. 43.6 ft. scribed S35 T24S R5W CS BT.
11" R. Fir bears S.5°W. 45.6 ft. scribed S 2 T25S R5W CS BT.
9" R. Fir bears S.42°E. 50.8 ft. scribed S 1 T25S R5W CS BT.