

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

S. E. Corner D. L. C. No. 47.
SET - 3" Aluminum Cap on a 1 1/2" x 36" G. I. P. at the
intersection of the fences, mkd:

D. L. C. 47
D. L. C. 46
T25S R5W

95

Malcolm N. Clark
For-Hakanson,
Sultan, Knight
Oct. 28, 1968
M 36 - 61

1/4 Corner Common to Sec. 25, T25-5W. & Sec. 30, T25-4W.
This corner is S.35°E. 25.0 ft. from Skid Road and
S.35°E. 40.0 ft. from Creek.

Set - 5/8" I.Rod, 1.0 ft. South of Corner which fell in
center of large uprooted fir, from which:
Mkd: A 38" Fir N.27°W. 56.3 ft. (mkd: "1/4 S25 BT")
A 4" Fir S.19°E. 5.7 ft. (mkd: "X")

96

1/4 Corner common to Sections 25 and 36.
This corner is 1.5 ft. South of E - W. Fence Line.

Set - 5/8" I.Rod at Corner from which:
Mkd: - A 7" Fir N.13°W. 32.2 ft. (Mkd: "1/4 S25 BT")
A 13" Fir S.29°E. 167.5 ft. (Mkd: "1/4 S36 BT")

97

Section Cor. Common to Sections 23 - 24 - 25 - 26.
This corner is located S.78°W. 19.0 ft. from fence corner
4.0 ft. south of an E-W fence and approx. 100 ft. west
of reservoir. Set by Double proportion.

Set - 5/8" I.Rod at corner from which:
Mkd: A 10" Fir S.43°W. 33.3 ft. (Mkd: T25S R5W S26 BT)
A 12" Fir S.36°E. 68.05 ft. (Mkd: T25S R5W S25 BT)
A 12" Fir N.69°E. 27.0 ft. (Mkd: T25S R5W S24 BT)
A 8" Fir N.30°W. 54.5 ft. (Mkd: T25S R5W S23 BT)

98

1/4 Corner common to Sections 25 and 26.
This corner located 15.0 ft. west of Skid Road.
Set by Single Proportion.

Set - 5/8" I. Rod at corner, from which:
Mkd: - A 30" Fir S.85°E. 137.2 ft. (Mkd: "1/4 S25 BT")
A 48" Fir S.39°W. 114.2 ft. (Mkd: "1/4 S26 BT")

99

Center 1/4 Corner to Section 25.
Corner is located on steep, north slope approx. 100 ft.
south of draw, running generally west.

Set - 5/8" Iron Rod at corner, from which:
Mkd: - A 24" Fir S.59°E. 20.0 ft. (Mkd: "C 1/4 S25 BT")
A 10" Fir S.56°W. 13.3 ft. (Mkd: "C 1/4 S25 BT")

100

Sec. Corner to Secs. 18 & 19, T25-4W
and Secs. 13 & 24, T25-5W.

Did not find 1957 BLM Brass Cap.
Reset Corner from BT's., as follows:

12" Ash bears N. 6 1/2°E. 281.8 ft.
11" Ash bears S. 37° E. 390.1 ft.
7" Ash bears S. 22° W. 345.2 ft.
10" Ash bears N. 67 1/4° W. 206.6 ft.

Set - 5/8" Iron Rod at Corner

10/18/71

101

McLind,
Victor M.
For: Bob
Wiley
Map File
M 43-79

Donald A. Bentz
For Joe Denley
March 1970 Map File M 33 - 71

MARCH 71

JAN 1972